


















10/10/15 US Coast
2650 W. 1st St. Bg-
Bullock House
FLA. 32011-1111
Packing 1/2" carbon
10:45
15W, Tony Chri






Viscosity Made Simple

The Cannon SimpleVIS™ portable viscometer offers quick, affordable and reliable kinematic viscosity measurement.

Visit Cannon at www.cannoninstrument.com or call 800-676-6232 for more details

THOMAS SCIENTIFIC

CATALOG NUMBER: 9721B71



VISCOMETER CALIB. SIZE 350

Put away ID

1255240

UOM

EA



PO # 313442

REC # 887262

MANU#


CFRC-350

05/21/2015 1:58 PM

LABEL NAME: Tho PO No Lot 2X3 Label

THOMAS SCIENTIFIC

CATALOG NUMBER: 1209Q33



Hydrometer ASTM 27H 30 to 36 API


Hydrometer ASTM 26H 25 to 31 API

Putaway ID

1277200

UOM

EA



PO # 316625

REC # 903339

MANU#

251-000-26H

06/19/2015 11:15 AM

LABEL NAME: Tho PO No Lot 2X3 Label

THERMCO

GW085H

.800/.850

THERMCO

GW087H

.900/.950



FIRE
↓



MOORE
13A 1" 1000 PSI 1/4" MPT
2500 NO. 4200-100 2000
1/2" 1000 PSI 1/4" MPT
4200-4200 50000/2.5mm
1/2" 1000 PSI

LIQUID

CAUTION
DO NOT
PULL OUT
THIS LINE





10 KG
↓



LIQUITOTE
HERNANDEZ EQUIPMENT COMPANY, INC.
HOUSTON, TX 77040
800-844-6000

Product Number

351370

Product Name

SODIUM SILICATE 41

Technical

Lot Number

AL053878471

Sequential Numbering

Net Contents

625 LBS.

VOC Information

TETRAETHYLENEPENTAMINE.

DANGER!

CAUSES SEVERE EYE BURNS.
CAUSES SEVERE SKIN BURNS
CAUSES BURNS OF THE MOUTH AND THROAT.
HARMFUL IF ABSORBED THROUGH SKIN.
MAY CAUSE ALLERGIC SKIN REACTION.
ASPIRATION HAZARD. CAN ENTER LUNGS AND CAUSE DAMAGE.

BEFORE HANDLING OR USING THIS PRODUCT, SEE YOUR EMPLOYER
AND READ THE CURRENT MATERIAL SAFETY DATA SHEET.

Do not get in eyes, on skin, on clothing.
Do not swallow.
Avoid prolonged or repeated contact with skin.
Avoid breathing vapor.

Keep container closed.
Use with adequate ventilation.
Wash thoroughly after handling.

Do not use secondary or tertiary amines in formulations containing this
product. Suspected cancer-causing nitrosamines could be formed.

FOR SPILL:

Evacuate area. Only trained and properly protected personnel must be in clean-up operations.

See MSDS for exposure limits of components.

DISPOSAL:

Content Disposal: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. **FOR UNUSED & UNCONTAMINATED PRODUCT,** the preferred options include sending to a licensed, permitted Incinerator or other thermal destruction device. **Container Disposal:** DO REUSE CONTAINER. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

Emergency Telephone Number: 989-636-4400

GMID: 175086

Batch: 2C1101HW08

Net Weight: 209.11 KG 461.00 LB

09-078738

Rev. 08/09/2010

Made in USA

The Dow Chemical Company
2030 Wilshire Blvd.
Midland, TX 79701
Indicates







LIQUITOTE

FORKS THIS SIDE



