


### DEPARTMENT OF ENVIRONMENTAL PROTECTION

### REQUEST FOR ADDITIONAL INFORMATION

SUMTER COUNTY LANDFILL, LONG-TERM CARE PERMIT RENEWAL PENDING PERMIT NOS: 22926-002-SF, SUMTER COUNTY

#### PREPARED FOR



SUMTÉR COUNTY BOARD OF COUNTY COMMISSIONERS 209 NORTH ELORIDA STREET BUSHNELL, ELORIDA 33513

October 1, 1997

921100.003

### Springstead Engineering, inc.

Consulting Engineers – Architects – Planners – Surveyors
727 South 14th Street
Leesburg, Florida 34748
Lake (352) 787-1414
Sumter (352) 793-3639
Fax (352) 787-7221

FILE



EB - 0001723 AA - 0002820 LB-0001723

727 South 14th Street Leesburg, Florida 34748

Lake (352) 787-1414 Sumter (352) 793-3639 Fax (352) 787-7221

October 2, 1997

Ms. Allison Amram, P.G. Southwest District - Solid Waste Florida Department of Environmental Protection 3804 Coconut Palm Drive Tampa, Florida 33619

OCTO3 193 RE: Sumter County Landfill, Long-term Care Permit Renewal Pending Permit No. 22926-002-SF, Sumter County

SEI File No. 921100.000

Dear Ms. Amram:

We are in receipt of your Request for Additional Information dated September 2, 1997 regarding the above referenced project; please find the following responses:

- Solid Waste Management Facility Permit application: Please complete the following sections 1. (and provide the required supporting data/reports) as they pertain to the closed landfill: B3, B8, B21, N3d, N3e, O4, O6, and Q. Section B contains general information concerning the closed landfill; Section N requires an engineering evaluation of the existing closed landfill systems (gas and water quality monitoring, cover conditions, stormwater control, etc.); Section O concerns the current use of the landfill areas (vacant land and recyclable storage only?) as well as documentation in the property deed that a landfill is present (see attached rule language from 17-701.074(4), dated December 10, 1985); and Section Q requires information about the financial responsibility accounts.
- 1. See the following responses:
  - **B3**) Disposal area 110 acres; used 60 acres, available 50 acres.
  - **B8**) The types of waste received include:
    - 1. Residential
    - 2. Commercial
    - Yard Trash 3.
    - Domestic Sludge for current composting process
  - B21) The closed landfill unit has a natural soil bottom.
  - Gas migration survey reports have been performed each year and submitted to N3d) FDEP. A copy of the report for 1996 is presented in Appendix A. These reports have indicated that landfill gasses are not present in the closed portion of the landfill.

- N3e) The report addressing the effectiveness of the landfill design is presented in Appendix B.
- O4) A declaration is being prepared by the County Attorney for submission to DEP.
- O6) The closed landfill areas are not in use at this time with exception of Phase III which is used for recyclables storage. The cover over Phase III consists of asphaltic concrete.
- Q1) Long term care costs for a third party to perform the work are attached.
- Q2) Annual cost adjustments will be made by using the Department's cost increase percentage or a percentage of 2% per year whichever is lower.
- Q3) Sumter County established an escrow account for the facility on September 29, 1992.
- 2. Based on the text provided, the FDEP understands that the applicant wishes to continue with the annual gas surveys. This is acceptable to FDEP.
- 2. The results of the past two (2) years of methane gas migration reports indicate that the amount of gas measured at the facility is below the detection limits in all areas except the tipping floor of the MRF building. Based on the measurements and the fact that the landfill is approximately ten (10) years old at this time, we request that the requirement for annual gas monitoring be deleted.
- 3. The ground water parameters missing from the last quarterly sampling event (listed in your August 20, 1997 letter to Ms. Danielle Nichols) are included in the EPA 601 parameter list. These parameters are part of the required sampling parameters and must be included in future sampling events. For your reference, the EPA 601 and 602 parameters as listed in 40 CFR, Part 136, Appendix A are attached to this letter.
- 3. The groundwater parameters will be included on future sampling events.

#### GROUNDWATER MONITORING PLAN EVALUATION

- 4. Appendix A, Groundwater Elevation Contours Maps. Please provide the groundwater elevation at each measurement point, and include the outline of the closed landfill and other pertinent structures in this area.
- 4. The revised maps are presented in Appendix C.
- 5. The evaluation included data from the past year only. The evaluation should include sampling events that occurred after those included in the May 1994 ground water evaluation.
- 5. The data for the last three (3) years is presented in Appendix "D".
- 6. A request to decrease sampling frequency must be supported by site-specific ground water flow velocity calculations. Please submit this data with supporting calculations. Well testing should be conducted on a representative number of wells.

- 6. At this time, we do not request a decrease in the frequency of the groundwater monitoring testing.
- The evaluation stated that turbidity is a problem during some sampling events. Wells that are purged with bailers often exhibit higher turbidity than wells purged with pumps. If the wells are purged with bailers, the applicant may want to instruct the samplers to gently lower the bailers in and out of the wells. If problems persist, the applicant may wish to have the wells redeveloped, or institute another method for purging the wells.
- 7. Response is noted.
- 8. If the applicant would like to reduce the parameter list, a proposed list must be submitted along with rationale for the proposed changes.
- 8. We request that the Volatile Organic Compounds and Pesticides and PCB's portion of the primary drinking water standards be deleted from the monitoring well testing requirements. Throughout the past five (5) years of testing, a minimum number of hits have been detected of these compounds and only on very few occurrences have compounds having levels above MCL been detected. In these instances the level was BDL or below MCL on the next sampling. Based on the age of the landfill it is our opinion that it is unlikely that these compounds will be detected in the future.

Should you have any office.

Springstead Engineering

David W. Springstead

Florida Registration No. 48229

DWS/jall

cc: Garry Breeden - Sumter County
Terry Hurst - Sumter County
TIA Solid Waste Management
Denise Reynolds - Sumter County

(October 2 - a:amram.rai)

### STATE OF FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION

#### FINANCIAL ASSURANCE COST ESTIMATES

				Date:	10/1/9/	
		Da	ite of FDEP Ap	pproval:		
L GENERAL	NFORMATION	٧:				
Facility Name:	Sumter Courand Compost	ity Recycl	ing, Proce	essing	GMS No.:	4060C00092
Permit No.:	22926-002-9	SF			Expiration Date:	Pending
Address (facility	):835 CR 5	29 Sumter	ville, Flo	orida 1	33585	
Address (mailin	g):319	Andersor	Avenue, I	Bushne.	ll, Florida 3	3513
Permittee (opera	ting authority):_	Sumter (	County Publ	Lic Wor	rks	
Facility	Lat. <u>28-44</u>	<u>-30</u> Lo	ng. <u>82-05</u> -	-20	or UTM's	<u></u>
with impe		, methane	e vents and	d moni	s I soil bott toring wells.	om landfill unit
	X					
Exempt	; Type of Exemp	tion:				
Closure Plan Ap	proved: Yes	/ <b>N</b>	<u>C</u>			
II. TÝPE OF F	INANCIAL DO	CUMENT S	UBMITTED T	ro ens	URE FINANCIA	L ASSURANCE:
Trust Fund	Agreement	Perform	nance Bond (or	nly for la	indfills with an app	proved closure plan)
Letter of Cro	edit	Standb	y Trust Fund A	greemer	ıt	
Insurance C	ertificate	XX Escrow	Account			·
Financial G	arantee Bond	Other (	Evolain)			

#### IV. ANNUAL COST FOR LONG-TERM CARE

( for 20 or 30 yrs., see 17-701.600(1)a.1.) (circle one)

- \*\*Third Party Estimate/Quote must be provided for each item
- \*\*Costs must be for a third party providing material and labor.

All items must be addressed. Attach a detailed explanation for all items marked not applicable (N/A).

DESCRIPTION	UNIT	QUANTITY	UNIT COST	ANNUAL CO	
	(A)	(B)	(C)	(D)=(A)x(B)x	(C)
1. Groundwater Monitoring 17-701.510(6), (8)(a)	sampling frequency events/yr	# of wells	\$/well/event	\$/yr	
Monthly			\$652	\$18,256	5
Quarterly				•	
Semi-Annual			<del></del>		<u>.</u>
Annual		<u> </u>		·	
		Subto	tal Groundwater N	Monitoring	\$18,256
2. Gas Monitoring 17-701.400(10)	sampling frequency	# of locations	\$/location/event	\$/yr	
2, 702, 100(20)	events/yr	•			• • • • • • • • • • • • • • • • • • • •
Monthly	<del></del>			<del></del>	
Quarterly		, <del></del>			
Semi-Annual					
Annual	1	29	\$27.50	\$800	
	,	S	ubtotal Gas Migra	tion Monitorin	\$800 g
3. Leachate Monitoring 17-701.510(5), (6)(b), 17-701.510(8)(c)	sampling frequency events/yr	# of locations	\$/location/event	\$/ут	
Monthly					
Quarterly				<del></del>	
Semi-Annual	2	1.	\$1055	\$2110	
Annual					
* .			Subtotal Leach	ate Monitoring	\$2110.00

DESCRIPTION	UNIT (A)	QUANTITY (B)	UNIT COST (C)	ANNUAL COS' $(D)=(A)x(B)x(C)$	
Monitoring 17-701.510(4), (8)(b)	sampling frequency events/yr	# of locations	\$/location/event	\$/yr	
Monthly				<u> </u>	
Quarterly				<del></del>	
Semi-Annual					
Annual					
		Subto	tal Surface Water	Monitoring _	\$0
. Maintenance of Leachat	e Collection/Tr	eatment Systems			
Collection Pipes	LF				
Sumps, Traps	EA				•
Lift Stations	EA		<del></del> '.		
Impoundments- Liner Repair	SF				
Sludge Remov	al CY				• <u></u>
Aeration Systems Floating Aerat					
Spray Aerators	s EA				
Off-Site Disposal	1000gal				
On-Site Pretreatm System Mainte	<del>-</del>	oe)			
Other (Describe)-					
	C 1		eatment System M	C:	\$2000

.:

**(**}

DES	CRIPTION	UNIT	QUANTITY	UNIT COST	ANNUAL COST**	]
		(A) ]	(B)	(C)	(D)=(A)x(B)x(C)	_
6. Maii	ntenance of Ground	water .				
	Monitoring Wells	LF				
•		Subto	otal Groundwater N	Monitoring Well N	Maintenance	\$0
7. Mair	ntenance of Gas Mig	gration Systen	n			
	Piping, Vents	LF				
,	Blowers	EA				
	Flaring Units	EA		<del></del>		•
	Meters, Valves	EA				
			Subtotal Gas N	Migration System	Maintenance	\$200
8. Land	dscape Maintenance					
	Mowing	AC	<u>.</u>		·	
	Fertilizer	AC				
	Irrigation	AC				
			Subto	tal Landscape Ma	intenance	\$1305 
9. Benc	chmark Maintenance	: EA				
			Subto	tal Benchmark M	aintenance	\$260
10. Adı	ministrative/Overhea	ad-				
	P.E. Supervisor	HR		·		
	On-Site Engineer	HR		<u> </u>		
	Office Engineer	HR				,
	On-Site Technician	n HR				
	Other (explain):		,			
	Electricity-include	: LS				
	Leachate Pump	os,				
	Blowers, Light	ing, etc.		Subtotal Admi	nistrative	\$0

DESCRIPTION	UNIT (A)	QUANTITY (B)	UNIT COST (C)	ANNUAL CO $(D)=(A)x(B)x(B)$	
11. Maintenance of C	over				
Sodding, Soi	I AC				
Regrading	AC				
Liner Repair Synthetic					
Clay	CY		· · · · · · · · · · · · · · · · · · ·	<u> </u>	
		Subto	tal Cover Integrity	Maintenance	\$1050
12. Surface Water Dr.	ainage Maintenance				
Ditch Cleani	ng LF				
Stormwater Conveyar	EA ace Maint.	Subto	tal Drainage Mair	ntenance	\$0
13. Security System N	Maintenance				
Fences	LF				<u></u>
Gate(s)	EA				
Sign(s)	EA				
		Subto	tal Security Syster	m Maintenance	\$0
14. Remedial Actions	LS		Subtotal Reme	dial Actions	\$0
15. Site Specific Cost	s (explain):		Suoioiai Acine	diai Actions	
		_			
		Subto	tal Site Specific C	costs	\$0
		I ONO men.	CART CORMS		\$25,981
		LUNG-TERM	CARE COSTS (S	o/yt)	

\$ 25	,98	31

#### **TOTAL LONG-TERM CARE COSTS (\$)**

#### CERTIFICATION BY ENGINEER

This is to certify that the Financial Assurance Cost Estimates pertaining to the engineering features of this solid waste management facility have been examined by me and found to conform to engineering principals applicable to such facilities. In my professional judgement, the Cost Estimates are a true, correct and complete representation of the financial liabilities for closing and long-term care of the facility, and comply with the requirements of Florida Administrative Code (FAC), Rule 17-701.630 and all other Department of Environmental Protection rules, and statutes of the State of Florida. It is understood that the Financial Assurance Cost Estimates shall be revised and subfattles to the Department annually as required by FAC 17-701.630(4).

OHAL ROOM	727 S. 14th Street
Signature D	Mailing Address
David-W: Springstead, P.E., Engine	er Leesburg, Florida 34748
Name and Title (please type)	City, State, Zip Code
48229	(352) 787–1414
Florida Registration Number (please affix seal)	Telephone Number
	Date: 10/1/97

APPENDIX A

### Central Testing Laboratory

**Engineering and Materials Testing** 

Reply to:

December 31, 1996

Leesburg

Mr. Garry Breeden, Director of Public Works Sumter County Public Works Department 222 East McCollum Avenue Bushnell, FL 33513

RE: Gas Migration Study Report
Gas Monitoring In and Around Buildings
Sumter County Solid Waste Management Facility
9684452.300

Dear Mr. Breeden:

As is required by specific condition of the permit, Central Testing Laboratory (CTL) performed a gas migration study at the above referenced facility on December 6, 1996. Permanent monitoring assemblies were installed, October 5, 1994, at various locations at the facility. The locations are shown on the aerial photograph presented ' in Appendix Α. A diagram showing the construction of the monitoring assembly is presented in Appendix B. The purpose of this study is to determine if generation and possible migration of combustible gases occur at the closed Class I Landfill.

The monitoring assemblies were placed at sampling locations chosen to detect methane gas migrating off areas of the subject site to areas of concern which include the structures. The sampling locations were analyzed by inserting a probe of a Foxboro Organic Vapor Analyzer (OVA), Model 128, (Serial Number A41775) through a rubber stopper then inserting the rubber stopper into the top of the monitoring assembly. The meter on the OVA was visually monitored, allowing the meter to stabilize. The OVA was calibrated using air and 100 ppm methane (CH $_4$ ) in air. The results of the OVA analysis are tabulated in the table entitled <u>Gas Migration Survey</u> - <u>December 6, 1996</u>, presented below.

Florida Department of Environmental Protection (FDEP) has requested that the OVA test results be converted to percentage of Lower Explosive Limit (LEL) for methane. The LEL for methane reported in various publications is 5.0 percent. This value was used to make the conversion from percent methane to percent LEL of methane. To simplify, divide the ppm methane by 50,000 to obtain percent LEL of methane.

Gas Migration Study Report
Gas Monitoring In and Around Buildings
Sumter County Solid Waste Management Facility
9684452.300

December 31, 1996

GAS MIGRATION SURVEY DECEMBER 6, 1996					
MONITORING POINT N°	ppm CH <sub>4</sub>	%LEL CH <sub>4</sub>			
M-1	0 1	0			
M-2	0	0			
M-3	0	0			
M-4	0	0			
M-5	0	0			
M-6	360	7.2-3			
M-7	0	0			
M-8	0	0			
<b>M</b> -9	0	0			
M-10	0	0			
M-11	0	0			
M-12	0	0			
M-13	0	0			
M-14	0	0			

Gas Migration Study Report
Gas Monitoring In and Around Buildings
Sumter County Solid Waste Management Facility
9684452.300

December 31, 1996

GAS MIGRATION SURVEY DECEMBER 6, 1996						
MONITORING POINT N°	ppm CH <sub>4</sub>	%LEL CH <sub>4</sub>				
M-15	0	0				
M-16	0	0				
M-17	0	0				
M-18	0	0				
M-19	0	0				
M-20	0	0				
M-21	0	0				
M-22	0	0				
M-23	0	0				
M-24	0	0				
M-25	0	0				
M-26	0	0				
M-27	0	0				
M-28	0	0				
M-29	0	0				

Gas Migration Study Report

Gas Monitoring In and Around Buildings
Sumter County Solid Waste Management Facility
9684452.300

December 31, 1996

Based upon the results of the tests conducted as part of this gas migration survey, it is CTL's opinion that the existing gas venting system is functioning satisfactorily and that no recommendations for additional measures or corrective actions are required at this time.

We hope that the provided information meets your needs at the present time. Should you have any questions, or if you require additional information, please contact our office.

Very Truly Yours, Central Testing Laboratory

Dua mekele

Judi M. Kelch Environmental Technician David W Springstead, P.E

Engineer

Florida Reg. No. 48229

#### **GAS MIGRATION SURVEY**

ΑT

THE SUMTER COUNTY
SOLID WASTE MANAGEMENT FACILITY
SUMTER COUNTY, FLORIDA

# APPENDIX A AERIAL PHOTOGRAPH SHOWING LOCATION OF GAS MONITORING POINTS



# CENTRAL TESTING LABORATORY LEESBURG, FLORIDA

DECEMBER 1996 9684452.300

#### **GAS MIGRATION SURVEY**

ΑT

THE SUMTER COUNTY SOLID WASTE MANAGEMENT FACILITY SUMTER COUNTY, FLORIDA

## APPENDIX B DIAGRAM OF GAS MONITORING POINT CONSTRUCTION




### CENTRAL TESTING LABORATORY LEESBURG, FLORIDA

DECEMBER 1996 9684452.300



#### TYPICAL GAS MONITORING POINT CONSTRUCTION



APPENDIX B

#### Report of Effectiveness of Landfill Design

This report addresses the requirements of FAC 62-701.600(4)(e) for the closed landfill at the Sumter County Recycling, Processing and Composting Facility in Sumterville, Florida. The purpose of the report is to describe the effects of the landfill on adjacent ground and surface waters and the landfill area.

The results of the geotechnical testing on the landfill site and adjacent parcels not indicate any detrimental effects on the site or adjacent sites due to the landfill operation at the subject site. No settling or sloughing has occurred due to foundation support. Settlement has occurred on the top of the landfill due to degradation of the organic materials in the landfilled materials.


The drainage design of the landfill has been effective and has operated as designed. It is Springstead Engineering, Inc.'s opinion that the stormwater and drainage system will continue to operate properly in the future.


Based on the results of the gas migration studies performed for the site, the gas vents are in proper working condition and the landfill is exhibiting very low to no methane gas generation over the landfill cover.


The existing cover for the closed landfill consists of 1 foot of sand over an impervious membrane for the majority of the site and an asphaltic concrete section cover over the remainder of the site. The sand/membrane cover is in very good condition, having a good stand of native grasses growing in the sand. This cover is effective for preventing the flow of water into the closed landfill system. The asphalt cover is in good condition. Several areas are unlevel due to settlement of materials which were landfilled. The asphalt covers are currently being releveled and repaved to prevent any ponding on the asphalt, and to reseal the cover. The asphalt cover is also effective for preventing the flow of water into the closed landfill system.


The waste disposed in the closed landfill consisted primarily of household waste with mixed with tree limbs and construction debris.

APPENDIX C









APPENDIX D

### ALUMINUM mg/L MCL = 0.2 mg/L

DAT	ΓE .	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01	-94	0.213	< 0.002	0.259	0.46	< 0.002	0.0506	0.205
10-01	-94	0.386	0.279	0.331	1.36	0.105	2.59	0.575
01-01	-95	0.512	0.065	0.652	1.01	0.448	0.109	0.246
04-01	-95	0.3	0.052	0.172	0.225	0.185	0.0275	0.0855
07-01	-95	0.476	0.227	2.83	0.71	0.767	0.263	0.41
10-01	-95	0.614	0.379	0.648	1.18	0.122	0.265	0.362
01-01	-96	0.53	0.399	0.429	0.924	0.492	0.232	0.368
04-01	-96	1.42	0.764	5.7	4.71	1.38	0.429	0.559
08-01	-96	1.5	0.839	2.81	11.9	28.5	3.75	1.59
10-30	)-96	2.17	0.179	1.41	0.367	0.11	0.592	0.162
02-11	-97	0.29	0.189	1.02	0.337	0.303	0.401	0.194
05-19	97	0.243	0.023	0.073	0.117	0.192	0.022	0.024

#### AMMONIUM mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	< 0.01	< 0.01	0.348	< 0.01	< 0.01	0.916	< 0.01
10-01-94	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
01-01-95	< 0.01	0.0126	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
04-01-95	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	0.145	< 0.01
07-01-95	< 0.01	< 0.01	0.136	0.0134	0.0301	0.136	< 0.01
10-01-95	0.279	< 0.01	< 0.01	0.175	< 0.01	0.252	<0.01
01-01-96	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	0.575	< 0.01
04-01-96	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	0.09	< 0.01
08-01-96	< 0.01	< 0.01	0.0348	< 0.01	< 0.01	0.0841	< 0.01
10-30-96	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01	0.0321	< 0.01
02-11-96	< 0.01	0.202	< 0.01	< 0.01	< 0.01	0.231	0.0289
05-19-97	0.0267	0.0209	< 0.01	< 0.01	< 0.01	< 0.01	0.0919

### CADMIUM mg/I MCL = 0.005

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-04	0.0003	< 0.0001	0.0003	0.0014	< 0.000	0.0003	0.0019
10-01-94	0.00026	0.00019	0.00039	0.00243	0.00018	0.00087	0.00574
01-01-95	0.0003	0.0003	0.0012	0.001	0.0023	0.0065	0.0018
04-01-95	0.0004	0.0002	0.001	0.0005	0.0016	0.0003	0.0029
07-01-95	0.0006	0.0003	0.0061	0.0011	0.0019	< 0.0001	0.0044
10-01-95	0.0012	0.0022	0.005	0.0024	0.0022	0.0008	0.0025
01-01-96	0.0012	0.0017	0.0021	0.0036	0.0016	0.0024	0.0029
04-01-96	0.001	0.001	0.0022	0.002	0.0021	0.001	0.0014
08-01-96	0.00888	0.00895	0.00993	0.0133	0.0124	0.0129	0.00741
10-30-96	0.02	0.0104	0.004	0.0003	0.0006	0.0005	0.0022
02-11-97	< 0.0001	< 0.0001	0.00208	< 0.0001	0.00058	< 0.0001	< 0.0001
05-19-97	< 0.0001	< 0.0001	< 0.0001	< 0.0001	< 0.0001	< 0.0001	< 0.0001

### CHLORIDE mg/L MCL = 250 mg/L

MW9	8WM	MW7	MW6A	MW4	MW2	MW1	DATE
33.6	36.8	28.5	18.8	36	42.3	8.99	07-01-94
11.7	13	9.34	6.74	19	24.1	3.41	10-01-94
14.3	14.8	11.1	9.39	38.9	24.8	4.82	01-01-95
14.8	14	9.29	9.22	53.3	44.4	3.99	04-01-95
17.1	13.7	10.3	10.4	62.5	38.6	6.69	07-01-95
14.9	8.51	6.21	6.59	65.6	11	2.07	10-01-95
_ 11.4	8.45	7.74	7.85	64.2	25.9	2.89	01-01-96
22	11.5	10.2	9.63	79.8	48.1	2.44	04-01-96
15.8	8.64	8.23	8.47	70.4	71.8	3.04	08-01-96
13.6	8.18	8.46	9.17	68.4	50.8	4.8	10-30-96
17.5	10.6	11.2	11.3	66.1	50.8	4.04	02-11-97
7.54	8.6	8.01	62	35.1	3.72	18.7	05-19-97

### CHROMIUM mg/L MCL = 0.1 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	0.6	0.8	1.5	8.7	2	1.4	1.3
10-01-94	0.552	1.56	1.2	5.48	0.00184	1.79	2
01-01-95	0.0006	0.0016	0.0018	0.005	0.0061	0.0065	0.001
04-01-95	0.0048	0.0022	0.0025	0.0057	0.0084	0.0028	0.0016
07-01-95	0.0016	0.0017	0.0102	0.0061	0.0081	0.0022	0.0022
10-01-95	0.002	0.0075	0.0066	0.0175	0.006	0.0028	0.0013
01-01-96	0.002	0.002	0.0024	0.049	0.0034	0.0283	0.002
04-01-96	0.002	0.002	0.0045	0.012	0.0049	0.0025	0.002
08-01-96	< 0.002	< 0.002	0.00672	0.0244	0.0492	0.0141	0.0355
10-30-96	0.0085	0.002	0.0084	0.0045	0.0026	0.0027	0.0012
02-11-97	0.00467	0.00698	0.0149	0.00894	0.0135	0.00939	0.0128
05-19-97	0.00894	0.00911	0.00792	0.0108	0.0117	0.00917	0.00751

#### COLOR PTU MCL = 15 PTU

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	10	<5	20	120	<5	10	20
10-01-94	10	20	20	180	<5	10	<5
01-01-95	20	<5	40	160	120	240	10
04-01-95	20	10	50	25	55	20	20
07-01-95	20	15	170	150	50	10	20
10-01-95	20	100	120	350	20	10	<5
01-01-96	<5	<5	<5	300	30	140	30
04-01-96	<5	40	70	200	40	20	<5
08-01-96	20	40	200	300	200	200	20
10-30-96	<5.0	<5.0	<5.0	<5.0	< 5.0	<5.0	<5.0
02-11-97	< 5.0	< 5.0	20	<5.0	< 5.0	< 5.0	< 5.0
05-19-97	20	<5.0	< 5.0	< 5.0	10	<5.0	<5.0

#### SPECIFIC CONDUCTANCE umhos

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	42	260	398	168	214	348	467
10-01-94	37	204	308	90	165	366	444
01-01-95	83	425	556	193	234	501	675
04-01-95	71	578	519	173	241	602	629
07-01-95	61	413	454	216	216	488	607
10-01-95	480	297	417	142	151	362	459
01-01-96	875	648	851	298	322	676	902
04-01-96	67	443	68	221	244	529	748
08-01-96	83	394	647	151	183	333	652
10-30-96	79	486	651	230	401	234	706
02-11-97	88	419	530	182	219	318	670
07-19-97	145	447	799	274	334	447	866

### IRON mg/L MCL = 0.3 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	0.0976	0.0073	0.391	0.178	0.001	0.934	0.366
10-01-94	0.0439	0.0453	0.235	0.117	0.00539	5.66	0.388
01-01-95	0.0943	0.042	0.201	0.0791	0.146	6.96	0.227
04-01-95	0.056	0.0392	0.0935	0.0811	0.329	0.518	0.276
07-01-95	0.0815	0.0716	1.52	0.105	0.173	0.258	0.556
10-01-95	0.104	0.238	0.38	0.503	0.167	0.56	0.171
01-01-96	0.00661	0.105	0.158	0.246	0.119	20.3	0.434
04-01-96	0.0585	0.082	0.273	0.448	0.156	0.695	0.27
08-01-96	0.115	0.248	0.656	1.3	2.07	0.684	9.1
10-30-96	0.309	0.0821	0.264	0.052	0.0383	0.223	0.339
02-11-97	0.0336	0.326	0.261	0.406	0.105	0.112	0.381
05-19-97	0.071	0.0602	0.0457	0.0719	0.141	0.0944	0.464

### NITRATE mg/L MCL = 10 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	3.7	6.52	4.06	4.35	4.72	<.01	<.01
10-01-94	3.64	6.92	3.65	4.03	4.36	0.365	<.01
01-01-95	4.27	6.77	2.96	3.57	4.58	1.16	1.12
04-01-95	3.35	9.72	4.05	3.64	3.76	1.03	0.0361
07-01-95	66.2	99.7	62	55.3	81.6	14.3	0.0855
10-01-95	1.78	2.86	5.03	5.8	4.49	0.154	<.01
01-01-96	2.35	0.642	8.72	5.7	4.22	1.3	0.589
04-01-96	2.53	1.78	8.27	7.34	4.67	2.34	0.131
08-01-96	3.85	2.01	8.86	6	4.66	2.53	0.058
10-30-96	2.51	3.47	3.68	4.97	3.12	1.33	0.0708
02-11-97	3.6	7.63	7.45	5.82	5.12	4.84	0.359
05-19-97	0.156	0.541	0.797	0.526	0.431	1.7	< 0.01

### pH pH UNITS Min pH 6.5, Max pH 8.5 @ collection point

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	6.28	6.49	6.94	7.62	7.44	6.72	6.56
10-01-94	5.85	6.62	6.95	7.72	7.49	6.72	6.65
01-01-95	6.29	6.62	6.96	7.85	7.63	6.9	6.83
04-01-95	7.55	6.58	7.02	7.79	7.14	6.84	6.86
07-01-95	6.99	6.51	6.68	7.24	7.02	6.86	6.65
10-01 <b>-</b> 95	7.48	6.95	7	6.82	6.65	6.71	6.84
01-01-96	7.69	6.94	6.64	8.03	7.64	6.92	6.74
04-01-96	6.97	6.65	6.55	7.45	7.43	7.01	6.84
08-01-96	7.84	7	6.85	7.74	7.55	7.05	6.83
10-30-96	7.25	6.71	6.95	7.35	6.55	6.73	6.62
02-11-97	7.48	6.92	6.5	6.5	7.41	7.16	6.82
05-19-97	7.29	6.78	6.32	7.25	6.94	7.15	6.79

### SULFATE mg/L MCL = 250 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	1.93	9.31	2.66	2.79	2.13	3.82	14.8
10-01-94	5.22	7.8	<1.00	1.43	<1.00	5.35	14
01-01-95	<1.00	4.6	3.72	2.65	1.94	<1.00	4.78
04-01-95	1.81	3.95	4.26	5.65	1.81	2.11	4.57
07-01-95	1.39	13.5	3.29	1.39	2.01	4.35	7.01
10-01-95	9.82	12.7	3.71	7.55	1.96	5.09	<1.00
01-01-96	5.79	25.6	3.48	6.06	2.19	5.37	3.15
04-01-96	3.84	15.8	3.92	5.39	1.81	3.16	1.49
08-01-96	2.62	32.3	3.47	3.11	<1.00	<1.00	<1.00
10-30-96	<1.00	34.3	2.02	<1.00	2.99	<1.00	<1.00
02-11-97	2.35	19.6	5	5.62	<1.00	<1.00	<1.00
05-19-97	2.62	16	6.45	6.04	2.32	4	3.58

#### TEMPERATURE DEGREES CENTIGRADE

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	25.1	27.1	26.6	24.2	23.8	24.2	27.1
10-01-94	26.6	24.8	27.3	23.9	23.8	24.3	26.2
01-01-95	23	24.1	24.1	21.3	21.3	23.6	25
04-01-95	25.7	25.3	25.9	22.1	22.7	24.2	27.7
07-01-95	25.8	25.9	27	26	24.5	24.5	27.6
10-01-95	25.7	25.3	26.5	23.1	22.9	23.9	25
01-01-96	24.2	23.3	23	18	16.2	19	24.3
04-01-96	20.8	22.5	23.2	21.8	22.2	21.9	24.5
08-01-96	24.6	23.7	27	24	24.2	23.6	25
10-30-96	28	24.3	27.4	25	23.1	22.4	23.5
02-11-97	20.4	22.4	20.5	19.2	22.1	22.5	23.8
05-19-97	25	25.1	26.6	26.3	23.4	24.9	25.8

#### TURBIDITY NTU MCL = 1 NTU

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	8.6	2.5	17	208	0.6	4.9	15
10-01-94	13	25	6.9	204	3.6	12	2
01-01-95	90	99	44	87	30	2.2	6
04-01-95	19	1.9	34	76	170	3.05	16.5
07-01-95	<.05	2.7	225	115	41	2.25	11
10-01-95	3.2	5.4	30.1	140	17	16	3.4
01-01-96	16	1.4	22.5	335	62	38.3	22
04-01-96	17	8.9	81	290	65	5.5	15
08-01-96	8.4	16	64	340	62	8.9	12
10-30-96	90	12	200	32	6.5	1.4	2.8
02-11-97	3.8	1.1	34	9.2	17	3.1	3.1
05-19-97	12	2.4	3.1	4.3	58	1.3	2.9

SODIUM mg/L MCL = 150 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	MW8	MW9
07-01-94	2.5	21.4	9.25	3.22	4.7	10.2	31.4
10-01-94	3.77	20.6	11.4	3.47	6.49	12.7	31.3
01-01-95	4.49	19.2	17.4	4.16	5.47	11.1	30.2
04-01-95	7.26	33.4	25.7	5.65	8.19	13.2	31.8
07-01-95	5.71	31.7	24	4.97	5.97	10.2	31.8
10-01-95	4.28	18.8	23.5	5.44	6.15	12.2	11.9
01-01-96	4.76	51.4	40.8	6.15	7.99	12.9	21.2
04-01-96	2.83	33.9	30.9	4.22	4.85	9.04	8.99
08-01-96	5.47	63.8	79.4	37	7.53	7.1	10.38
10-30-96	2.96	66.7	33.8	3.85	4.56	7.74	10.2
02-11-97	4	57.3	35	4.97	5.58	8.61	11.2
05-19-97	3.82	44.7	34.8	4.44	5.23	5.73	11.6

TOTAL DISSOLVED SOLIDS mg/L MCL = 500 mg/L

DATE	MW1	MW2	MW4	MW6A	MW7	8WM	MW9
07-01-94	74	250	332	196	220	372	560
10-01-94	78	302	320	224	206	344	446
01-01-95	88	288	364	192	256	380	472
04-01-95	85	324	452	214	216	360	478
07-01-95	100	254	384	176	224	320	500
10-01-95	42	328	426	234	180	350	446
01-01-96	34	302	434	205	174	364	462
04-01-96	36	270	420	198	156	326	··· 442
08-01-96	44	358	460	212	194	310	458
10-30-96	98	386	436	140	190	328	464
02-11-97	100	346	502	196	232	226	446
05-19-97	68	194	422	150	174	214	416