Johnson, Sabrina O

From: Pelley, Cindy <PelleyCA@HillsboroughCounty.ORG>

Sent: Friday, April 13, 2018 3:31 PM

To: SWD_Waste

Cc: Morgan, Steve; Ruiz, Larry; Cope, Ronald; Byer, Kimberly; Madden, Melissa; 'Curtis, Bob'; O'Neill,

Joseph; KGuilbeault@scsengineers.com

Subject: WACS ID 41193 - Qtr 1 2018 Water Balance & Waste Tire Report for Southeast County

Attachments: 1Q2018 Water Balance Report.pdf; 1Q2018 Waste Tire rpt.pdf

Mr. Morgan:

The Quarterly Water Balance and Waste Tire Reports for the Southeast County Landfill are attached (WACS ID 41193).

Please note, revisions have been made to the Phases I – VI condensate line data originally reported in Tables I & II for the months of January and February 2018 leachate balance. Leachate totals being obtained from the condensate lines is tracked by 2 separate methods; a flow meter, and individual counters at each pump. It was determined that the flow meter was installed incorrectly and was not capturing the entire flow being collected. Both sets of data were reported for those months however the final leachate balance has been revised to show the corrected values per the pumps counters.

Please advise should you have any questions concerning the information provided.

Thank you,

Cindy A. Pelley
General Manager II
Solid Waste Management Division
Public Works Department

M: (813) 455-2193 P: (813) 671-7707

E: pelleyca@HCFLGov.net

W: <u>HCFLGov.net</u>

Hillsborough County

601 E. Kennedy Blvd., Tampa, FL 33602

Facebook | Twitter | YouTube | LinkedIn

Please note: All correspondence to or from this office is subject to Florida's Public Records law.



PUBLIC WORKS

PO Box 1110 Tampa, FL 33601-1110 (813) 272-5912 | Fax: (813) 272-5811

April 12, 2018

Mr. Steve Morgan Solid Waste Section Florida Department of Environmental Protection, Southwest District 13051 N. Telecom Pkwy Temple Terrace, Florida 33637

RE: Southeast County Landfill - Leachate Data Quarterly Report

Dear Mr. Morgan:

In accordance with Specific Condition No. C.12.d of Permit No. 35435-023-SO/01, the Solid Waste Management Division (SWMD) is submitting the Quarterly Leachate Water Balance summary for the Southeast County Landfill for the quarter ending March 31, 2018.

The data is being submitted as separate monthly reports for January, February, and March 2018. The attached reports include the leachate level in Pump Station B (PS-B).

Please advise should you have any questions concerning the attached submittal.

Sincerely,

fary E. Larry E. Ruiz, SC

Manager Landfill Operations

Solid Waste Management Division

LER/cp Attachment

xc: Ken Guilbeault, SCS Ron Cope, EPC SOARD OF COUNTY COMMISSIONERS

Victor D. Crist Ken Hagan Al Higginbotham Pat Kemp Lesley "Les" Miller, Jr. Sandra L. Murman Stacy R. White

COUNTY ADMINISTRATOR
Michael S. Merrill

COUNTY ATTORNEY
Chip Fletcher

INTERNAL AUDITOR

Peggy Caskey

CHIEF DEV. & INFRA. SERVICES ADMINISTRATOR

Lucia E. Garsys



PUBLIC WORKS

PO Box 1110 Tampa, FL 33601-1110 (813) 272-5912 | Fax: (813) 272-5811

MEMORANDUM

DATE: February 13, 2018

TO: Larry E. Ruiz, Manager Landfill Operations, Solid Waste

Management Division

FROM: Cindy A. Pelley, Landfill Supervisor, Solid Waste Management

Division

SUBJECT: Leachate Water Balance Report Forms for January 2018

Southeast County Landfill, Hillsborough County, Florida

BOARD OF COUNTY COMMISSIONERS

Victor D. Crist Ken Hagan Al Higginbotham Pat Kemp Lesley "Les" Miller, Jr. Sandra L. Murman Stacy R. White

COUNTY ADMINISTRATOR

Michael S. Merrill COUNTY ATTORNEY Chip Fletcher

INTERNAL AUDITOR
Peggy Caskey

CHIEF DEV. & INFRA. SERVICES ADMINISTRATOR

Lucia E. Garsys

The Solid Waste Management Division (SWMD) staff has compiled and reviewed the leachate management operational data from the Southeast County Landfill Phases I-VI, Sections 7-8, and Section 9. Attached are the Leachate Water Balance Report Form (Table 1), the Leachate Field Data Entry Form (Table 2), and the 2018 Summary (Table 3). Also, attached find Figure 1 showing leachate levels in Pump Station B sump of Phases I-VI and rainfall for the month.

TABLE 1

Day (Column I)

Column I presents the calendar days for the month.

Rainfall (Column II)

Column II presents the average rainfall, in inches, as measured in the field from rainfall stations at the site. This month there was 3.63 inches of rainfall recorded at the Southeast County Landfill (SCLF).

Depth in Pond A (Column III)

Column III presents the daily depth, in feet, of effluent stored in effluent pond (Pond A). The daily depth in Pond A varies as a function of the spray irrigation frequency/duration and effluent hauled from the pond. This month the daily average depth of effluent stored in Pond A was 2.5 feet.

Depth in Pond B (Column IV)

Column IV presents the daily depth, in feet, of effluent or leachate that is stored in the effluent/leachate storage pond (Pond B). The depth in Pond B varies as a function of the evaporation frequency/duration and effluent or leachate hauled from the pond. This month the daily average depth of effluent stored in Pond B was 1.9.

Memorandum February 13, 2018 Page 2 of 5

Estimated Depth at Pump Station B Sump (PS-B) (Column V)

Column V presents the depth of leachate, in inches, in the PS-B sump. Leachate from Phases I-VI flows to the PS-B sump for removal from the landfill. PS-B then pumps the leachate to Pump Station A (PS-A). Daily depth readings from the PS-B sump are included in this column. This month PS-B was below the normal operation level except January 4th, 23rd, 27th, 28th and 30th due to power outages and pump malfunctions. The average recorded depth of leachate in the PS-B sump was 18.1 inches.

Leachate Pumped to Pump Station A Sump from Phases I-VI Condensate Line (Column VI)

Column VI presents the daily amount of leachate, in gallons, collected from the Phases I-VI condensate line and pumped to Pump Station A (PS-A). The average daily amount of leachate pumped from the Phases I-VI condensate line was 22,965 gallons. A total of 711,920 gallons of leachate was pumped this month.

Leachate Pumped to MLPS from Phases I-VI (Column VII)

Column VIII presents the daily amount of leachate, in gallons, collected from PS-A and pumped through the MLPS to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. This column also includes the Phase II data from the dewatering wells and temporary pump stations TPS-2B and PS-2. The average daily amount of leachate pumped from PS-A was 87,093 gallons. A total of 2,699,895 gallons of leachate was pumped this month.

Leachate Pumped from Sections 7-8 LDS (Column VIII)

Column IX presents the quantity of leachate removed from the leak detection system (LDS) of Sections 7-8. The quantity is measured by a flow meter before being pumped for removal with Sections 7-8 leachate. The removal rate did not exceed 1,930 gallons per day. This month a total of 125 gallons of leachate was removed from the leak detection system of Sections 7-8.

Leachate Pumped to MLPS from Sections 7-8 (Column IX)

Column X presents the quantity of leachate collected at Sections 7-8 and pumped to the MLPS. The quantity is measured by a flow meter and includes any leachate removed from the leak detection system of Sections 7-8 (Column IX). This month a total of 132,787 gallons was removed.

Leachate Pumped to LTRF from the MLPS (Column X)

Column XI presents the total quantity of leachate pumped to the LTRF from Phases I-VI (including condensate removed from LFG Wells and Condensate Traps), and Sections 7-8. This month a total of 2,832,682 gallons of leachate was pumped to the LTRF.

Memorandum February 13, 2018 Page 3 of 5

Leachate Pumped to LTRF from Section 9 (Column XI)

Column XII presents the daily amount of leachate, in gallons, collected from Section 9 and pumped to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. A total of 136,192 gallons of leachate was pumped this month.

Leachate Pumped from Section 9 LDS (Column XII)

Column XIII presents the daily amount of leachate, in gallons, collected from the LDS of Section 9 and pumped to the 575,000-gallon storage tank at the LTRF for treatment or disposal. The removal rate did not exceed 4,651 gallons per day. This month a leachate was not removed from the leak detection system.

Leachate Pumped from Compost Area Sump (Column XIII)

Column XIV presents the total quantity of leachate pumped to the LTRF and Pond B from the Compost Project Area Sump. This month there was no leachate from the compost area pumped to the LTRF.

Leachate in 575,000-Gallon Tank (Column XIV)

Column XV presents the daily amount of leachate, in gallons, stored in the 575,000-gallon leachate holding tank T1 at the LTRF. The amount of leachate stored in T1 is calculated based on the circumference of the tank and the daily level reading. This month an average of 302,600 gallons of leachate was stored in the tank.

Effluent in 575,000-Gallon Tank (Column XV)

Column XVI typically presents the daily amount of effluent, in gallons, stored in the 575,000-gallon effluent holding tank T6 at the LTRF. The amount of effluent stored in T6 is calculated based on the circumference of the tank and the daily level reading. This month an average of 366,100 gallons of effluent was stored in the tank.

Leachate Treated at LTRF (Column XVI)

Column XIIV presents the daily amount of leachate, in gallons, treated at the LTRF. This month a total of 728,100 gallons of leachate was treated at the plant.

Total Leachate Hauled (Column XVII)

Column XVIII presents the daily amount of leachate, in gallons, hauled off site. This month a total of 2,278,282 gallons of leachate was hauled off site.

Memorandum February 13, 2018 Page 4 of 5

Leachate Dust Control Sprayed (Column XVIII)

Column XIX presents the daily amount of leachate, in gallons, measured from the flow meter at the bypass-loading arm at the leachate storage tank. The leachate is used for dust control in the active area of the landfill. This month a total of 9,334 gallons of leachate was used for dust control.

Pond A Storage (Column XIX)

Column XX presents the daily amount of effluent, in gallons, stored in Pond A. The daily amount stored in the pond is calculated by using the daily depth of effluent in the Pond A (Column III). Under normal operating conditions, the daily amount of effluent stored in the pond varies depending upon the daily amount of leachate treated at the LTRF, the daily rainfall, daily effluent hauling operations, daily spray irrigation operations, and the daily amount of effluent used for dust control/evaporation. This month a daily average of 70,500 gallons of effluent was stored in Pond A.

Pond B Storage (Column XX)

Column XXI presents the daily amount of effluent, in gallons, stored in Pond B. The daily amount stored in the pond is calculated by using the daily depth of liquid in Pond B (Column IV). Under normal operating conditions, the amount stored in the pond will vary depending upon the daily amount of leachate/effluent removed from the pond by the evaporation system, hauled from the pond, used for dust control or evaporated; however during January the storage pond was empty and then filled with effluent. This month a daily average of 72,000 gallons of effluent was stored in Pond B.

Effluent Sprayed at Pond B (Column XXI)

Column XXII presents the daily amount of effluent, in gallons, sprayed for evaporation at Pond B. The amount evaporated is calculated by using 5 percent of the daily flow meter quantity sprayed at Pond B and it is included in Column XXVI. This month a total of 100,548 gallons of effluent was sprayed in Pond B.

Effluent Irrigation (Column XXII)

Column XXIII presents the daily amount of effluent, in gallons, used for spray irrigation on top of Phases IV-VI. The daily amount of effluent irrigation on Phases I-VI is measured from the flow meter at the irrigation pump station. This month a total of 410,330 gallons of effluent was used for spray irrigation.

Memorandum February 13, 2018 Page 5 of 5

Effluent Dust Control Sprayed (Column XXIII)

Column XXIV presents the daily amount of effluent, in gallons, sprayed for dust control in the active areas of the SCLF. The daily amount of effluent used for dust control, is measured from the flow meter at the bypass-loading arm. This month effluent was not sprayed as dust control.

Total Effluent Hauled (Column XXIV)

Column XXV presents the daily amount of effluent, in gallons, hauled off site, as measured from the flow meter at the bypass-loading arm. This month a total of 249,302 gallons was hauled off site.

Total Evaporation (Column XXV)

Column XXVI presents the daily amount of leachate and effluent, in gallons, that evaporates and therefore will not be returned to the SCLF and/or requires treatment. Evaporation rates of 80 percent and 5 percent evaporation rate for spray in Pond B are assumed. Total evaporation estimated for this month was 340,700 gallons.

TABLE 2

Table 2 presents data assembled from daily logs compiled by the SWMD staff.

TABLE 3

Leachate Balance Summary

The Leachate Balance Summary (see Table 3) presents a review of inflow and outflow quantities for the LTRF, as well as rainfall and effluent disposal quantities at the landfill. Total inflow quantity to the LTRF was 2,969,860 gallons. Total outflow quantity from the LTRF was 3,015,716 gallons. The change in storage for the month decreased by 45,856 gallons.

Please advise should you have any questions concerning the information provided.

TABLE 1. LEACHATE WATER BALANCE REPORT FORM JANUARY 2018 SOUTHEAST COUNTY LANDFILL, HILLSBOROUGH COUNTY, FLORIDA

	S		Total	ration	9	0	0	0	19,100	24,000	25,300	20,900	18,600	0	0	0	300	12,900	0	46,700	0	0	26,700	0	39,700	0	34,100	0	0	26,600	0	43,300	0	0	0	2,500	340,700		10,990
	XXV		É	Evaporation	(gal)	0	0	0	3	69	0	0	0	0	0	1.1	11	0	0	0	0	84	0	8	0	0	0	0	0	11	13	12	0	0	0	0			
	XXIV		Feffuent	Hanled	(gal.)				7,813	21,339						67,177	14,901					7,308		58,508						43,651	7,303	21,302					249,302		8,000
	XXIII		Effluent Duet Control	(Spraved)	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0
	XXII		Effluent	monagum	(gal.)	0	0	0	23,871	24,092	31,599	26,159	23,309	0	0	0	0	16,167	0	52,199	0	0	33,404	0	49,590	0	42,590	0	0	33,281	0	54,069	0	0	0	0	410,330		13,200
	XXI	Effluent	Sprayed	B	(gal)	0	0	0	0	93,586	0	0	0	0	0	0	6,962	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	100,548		
	XX		Pond	Storage	(gal)	64,000	64,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	19,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	80,000	51,000	33,000	72,000	72,000		72,000	
	XIX		Pond	Storage	(gal.)	118,000	113,000	113,000	113,000	129,000	0	0	0	0	103,000	113,000	129,000	129,000	123,000	113,000	61,000	79,000	000'86	93,000	93,000	74,000	0	0	48,000	74,000	48,000	52,000	44,000	36,000	36,000	52,000		70,500	
	XVIII		Leachate Duet Control	(Spraved)	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	6,233	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3,101	9,334		300
	XVII		Total		(gal.)	0	131,990	161,290	131,899	103,287	70,859	0	81,135	59,682	124,592	7,532	116,728	49,709	0	87,707	81,400	116,867	124,316	29,169	42,471	0	89,349	81,985	131,941	72,842	72,271	21,242	0	87,402	81,278	119,339	2,278,282		_
	XVI	Leachate	Treated	14.		27,000	27,000	27,000	18,800	20,300	27,400	27,400	27,400	17,700	35,100	25,000	26,800	20,300	20,300	20,300	20,300	19,200	17,500	21,500	21,200	21,200	21,200	21,900	21,100	20,100	25,300	27,000	27,000	27,000	22,700	26,100	728,100		_
FLORIDA	XV	ent	m 575K	Tank	(gal.)	353,000	355,000	365,000	374,000	367,000	369,000	391,000	415,000	396,000	398,000	403,000	345,000	343,000	362,000	381,000	403,000	401,000	391,000	381,000	329,000	344,000	360,000	353,000	367,000	348,000	302,000	322,000	337,000	353,000	372,000	369,000		366,100	_
COUNTY,	XIV	nate	m 575K	Tank	(gal.)	421,000	475,000	415,000	322,000	259,000	221,000	216,000	283,000	293,000	293,000	238,000	324,000	302,000	342,000	381,000	355,000	317,000	269,000	209,000	221,000	290,000	360,000	309,000	309,000	235,000	218,000	158,000	256,000	353,000	386,000	350,000		302,600	_
SBOROUGH	XIII	1	Commont	Leachate	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
L, HILLS		9			1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	_
LANDFII	XII	Leachate	Pumped from	LDS	(gal.)																	0	0																
SOUTHEAST COUNTY LANDFILL, HILLSBOROUGH COUNTY, FLORIDA	XI	Leachate	Pumped to I TPE from	Section 9	(gal.)	6,224	6,224	0		_	723	1,560	1,787	2,380	2,477	2,296	2,889	2,896	38,432	38,432))		1,201	1,703	2,282	2,282	2,322	2,543	1,925	2,595	2,466	2,510	2,510	2,652	2,881	136,192	4,393	
SOUTHEA	X	Leachate	Pumped		(gal.)	107,914	108,208	106,552	66,444	100,616	89,351	88,799	116,145	77,167	86,325	129,560	116,355	98,216	86,683	88,151	61,728	104,563	84,825	70,143	71,433	21,717	780,76	54,755	98,401	74,220	94,427	59,320	107,232	105,977	97,795	86,575	2,832,682	91,377	
	IX	Leachate	Pumped of MT DS from		(gal.)	4,362	4,362	5,173	2,683	134	10,360	2,008	2,068	252	4,725	9,400	5,715	892	4,806	4,806	4,249	3,037	331	7,543	5,860	4,759	4,759	3,366	3,703	6,348	454	324	1,289	1,289	691'6	8,688	132,787	4,283	_
	VIII	Leachate	Pumped from			0	0	0	0	0	0	0	0	4	0	0	0	83	14	14	7	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	125	4	_
	Λ	Lea	Pump			.52	347	628	192	182	160	16.	770	115	009	091	940	148	.28	345	621	526	194	009	573	858	828	889	869	372	173	966	143	889	979	887	395	933	
	ΛII	Leachate	Pumped	from Phases I-VI	(gal.)	103,5	103,847	101,379	63,761	100,482	18,991	83,791	111,077	76,915	81,600	120,160	110,640	97,448	81,878	83,345	57,479	101,526	84,494	62,600	65,573	92,958	92,328	51,389	94,698	67,872	93,973	966'85	105,943	104,688	88,626	77,887	2,699,895	87,093	
	VI		Dhacac I - VI	Condensate	(gal.)	27,093	7,144	15,680	7,025	7,004	12,847	12,847	28,113	635	4	23,744	28,131	29,815	29,815	29,815	865'9	22,803	27,913	28,551	30,106	30,106	31,156	30,293	27,673	30,289	30,469	29,807	29,807	31,715	32,527	32,398	711,920	22,965	
	Λ	Estimated		PS-B		14.7	14.3	16.8	42.2	13.3	13.0	16.0	14.7	13.8	12.5	18.1	11.9	11.3	12.0	12.6	11.2	18.6	18.2	8.6	12.3	14.0	15.7	50.1	13.9	10.1	18.8	40.1	29.3	18.5	28.4	14.2		1.8.1	_
	IV	Depth	III Dond	B	(H)	1.9	1.8	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1.7	1.3	1.9	1.9		1.9	
	Ш	epth	n D	, our	(H)	3.2	3.1	3.1	3.1	3.4	3.0	2.4	1.9	2.4	2.9	3.1	3.4	3.4	3.3	3.1	2.0	2.4	2.8	2.7	2.7	2.3	1.8	1.5	1.7	2.3	1.7	1.8	9.1	1.4	1.4	1.8		2.5	_
	П	n n		Rainfall		03	10.0	19.0	10.0	00'0	00'0	00'0	00:00	0.58	00'0	0.28	00:00	0.00	00:00	00'0	00'0	00:00	00:00	00:00	00'0	00'0	0.00	0.00	0.00	00'0	00'0	0.00	1.80	0.20	0.05	0.00	3.63		_
	I				Day	1	2	3	4	2	9	7	œ	6	10	11	12	13	14	1.5	16	17	18	16	2.0	21	22	23	24	2.5	26	2.7	28	29	3.0	31	Total	Daily Average	Mo. Average

Notes:

1. NR = No Records, NA = Not Available.

2. Values in bold are estimated; values in faile are substitute for missing data and are based on averaged values.

2. Values in bold are estimated; values in faile are substitute for missing data and are based on averaged values.

3. Daily average is calculated by divising the total by the actual days measured in the menth.

4. Menthly average exclassing by divising the total by the aumber of days of the month.

5. Column II. Trace is less than 0.01 rethes and is not included in total.

6. Columns III and IV, field measured at staff gauges.

Columns IX & X, Section 7-8 bak detection pumped into Section 7 leachate sump riser.
 Column XY and XVI, calculated from depth in 755:009 lat units.
 Column VXIX, XVIVIX, and XXIX.IXV quanties from a pum eners.
 Column XXVI includes 80% of the duity values from Column XIX, XXIII, and XXIV piculudes 80% of the duity values from Column XXIX. XXIII, and XXIV piculudes 80% of the duity values from Column XIX. XXIII, and XXIV piculudes 80% of the duity values from Column XXIII.

TABLE 2. FIELD DATA ENTRY FORM JANUARY 2018 SOUTHEAST COUNTY, LANDFILL, HILLSBOROUGH COUNTY, FLORIDA

	ient ontrol	yed)																																
×	Effluent Dust Control	(Sprayed) (gal)	0																															0
W	Effluent Hauled	County (gal.)	0			7,813	21,339												7,308		28,297						36,244	7,303	21,302					129,606
Λ	Effluen	Contractor (gal.)	0	0	0	0	0	0	0	0	0	0	67,177	14,901	0	0	0	0	0	0	30,211	0	0	0	0	0	7,407	0	0	0	0	0	0	119,696
U	Leachate Dust Control	(Sprayed) (gal.)	0	0	0	3,225	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3,225
Τ		ξ. ~	0	86,715	78,885	64,775	21,221	70,859	0	43,992	7,321	42,432		49,707	49,709	0	42,367	43,977	79,300	79,257	14,130	42,471	0	43,981	36,685	86,636	42,981	35,483	21,242		49,813	43,863	44,031	1,221,833
S	Leachate Hauled	Contractor (gal.)	0	45,275	82,405	67,124	82,066	0	0	37,143	52,361	82,160	7,532	67,021	0	0	45,340	37,423	37,567	45,059	15,039	0	0	45,368	45,300	45,305	29,861	36,788	0	0	37,589	37,415	75,308	1,056,449
R	Leachate	at LTRF (gal.)	27,013	27,013	26,965	18,790	20,272	27,375	27,375	27,376	17,747	35,085	25,024	26,771	20,271	20,271	20,271	20,271	19,174	17,473	21,510	21,243	21,243	21,243	21,911	21,138	20,145	25,287	26,982	286,982	26,982	22,744	26,145	728,092
Ò	Depth in 575K Tank	Effluent (ft.)	12.28	12.33	12.67	13.00	12.75	12.83	13.58	14.42	13.75	13.83	14.00	12.00	11.92	12.59	13.25	14.00	13.92	13.58	13.25	11.42	11.96	12.50	12.25	12.75	12.08	10.50	11.17	11.71	12.25	12.92	12.83	
Ь	Depth in 575K Tank	Leachate (ft.)	14.64	16.50	14.42	11.17	9.00	79.7	7.50	9.83	10.17	10.17	8.25	11.25	10.50	11.88	13.25	12.33	11.00	9.33	7.25	79.7	10.09	12.50	10.75	10.75	8.17	7.58	5.50	88.88	12.25	13.42	12.17	
0	Effluent	Irrigation (gal.)	0	0	0	23,871	24,092	31,599	26,159	23,309	0	0	0	0	16,167	0	52,199	0	0	33,404	0	49,590	0	42,590	0	0	33,281	0	54,069	0	0	0		410,330
Z	Pond A	Depth (ft.)	3.15	3.10	3.10	3.10	3.40	3.00	2.40	1.90	2.40	2.90	3.10	3.40	3.40	3.25	3.10	2.00	2.40	2.80	2.70	2.70	2.25	1.80	1.50	1.70	2.30	1.70	1.80	1.60	1.40	1.40	1.80	
M	Pond B Effluent	Sprayed (gal)	00:0	0.0	0.0	0.0	93586.0	0	0.0	0.0	0.0	0	0.0	6962.0	0	0	0.0	0.0	0.0	0.0	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0	0.0	0.0		100,548
Г	Pond B	Depth (ft.)	1.85	1.80	1.90	1.90	1.90	1.90	1.90	1.90	1.90	1.90	1.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	1.65	1.3	1.9	1.9	
К	Sections 7-8	LDS (gal.)	51,696	51,696	51,696	51,696	51,696	51,696	51,696	51,696	51,700	51,700	51,700	51,700	51,783	51,797	51,810	51,817	51,817	51,817	51,817	51,821	51,821	51,821	51,821	51,821	51,821	51,821	51,821	51,821	51,821	51,821	51,821	
J	Sections 7-8		5,466,223	5,470,584	5,475,757	5,478,440	5,478,574	5,488,934	5,493,942	5,499,010	5,499,262	5,503,987	5,513,387	5,519,102	5,519,870	5,524,676	5,529,481	5,533,730	5,536,767	5,537,098	5,544,641	5,550,501	5,555,260	5,560,019	5,563,385	5,567,088	5,573,436	5,573,890	5,574,214	5,575,503	5,576,791	5,585,960	5,594,648	_
I	Compost 5		157	157	157	157	157	157	157	157	157	157	157	157		Н	157	157	157	157	157	157	157	157	157	157	157	157	157	157	157	157	157	
Н	Section 9	LDS (gal.)	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,333	5,846,332	5,846,331	5,846,331	5,846,331	
g	Section 9	Pump 2 (gal.)	213,555	216,633	216,633	Н	_	216,714	217,040	H	Н	219,042	Н		220,932	Н	Н	287,214	287,214	287,214	287,857	288,709	289,183	_	_	_	292,494	H	293,031	. 803,903	H	Н	297,009	
Н	Section 9	Pump 1 (gal.)	182,596	185,741	185,741	185,741	185,741	186,383	187,617	188,476	190,277	192,259	194,191	196,238	198,450	203,741	209,032	209,032	209,032	209,032	209,590	210,441	212,250	214,058	214,835	216,904	218,010	220,231	222,534	224,172	225,810	227,658	229,109	
Ε	Reading	PS-B (in.)	14.70	14.30	16.80	42.20	13.30	13.00	16.00	14.70	13.80	12.50	18.10	11.90	11.30	11.95	12.60	11.20	18.60	18.20	08.6	12.30	14.00	_			10.10	18.80	40.10	29.30			14.2	
D	Flow Meter	Pump Sta. A (gal.)	722,889	,795,148	1,865,000	,916,146	2,000,298	2,067,266	2,135,895	2,210,668	2,287,500	2,369,100	2,451,846	2,530,260	2,602,719	2,659,608	2,716,497	2,773,773	2,842,468	2,907,084	2,967,991	3,031,806	.096,244	3,160,682	3,188,782	,281,785	3,349,421	3,414,352	3,446,573	,525,741	3,604,909	3,669,295	3,725,600	
С	Phases I - VI F1		27,093	7,144		7,025		12,847 2	12,847 2	28,113 2	635 2	_	23,744 2	28,131 2	29,815 2	Н	29,815 2	6,598 2	22,803 2	27,913 2	28,551 2	30,106 3	30,106 3,		П	Т	30,289 3	30,469 3	29,807 3	29,807 3,	Н	П	32,398 3	
В	Phs	Rainfall Co	.03	0.01	19.0	101		00.0	0.00		0.58			0.00			0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		_	0.00	0.00	0.00	7.80				3.63
V		Rai Day (i	H	2 0	3 0	4 0	5 0	0 9	7 0	0 8	0 6	10 0	11 0	12 0	H	14 0	15 0	16 0	17 0	18 0	19 0	20 0	Н	22 0		_		H	27 0	H	H	H	Ш	Totals 3
					L	L		L		L					L					L	L	L						L	L		L			Ĥ

Notes: 1. 2. 3.

NR = No Records, NA = Not Available.
Values in bold are estimated; values in italic are substitute for missing data and are based on averaged values Columns I and L include quantities from leak detection system.

Type of Cover

inches.
_
0
Ξ.
0
than
less
. S
trace
В
Column
4.

5. Columns C, D, E, G, H, I, J, K, L, N, P, S-X and Y are quantities from flow meters. 6. Columns M and O measured from staff gages in each pond.




Figure 1. Leachate Levels in Pump Station B and Rainfall for January 2018.



PUBLIC WORKS

PO Box 1110 Tampa, FL 33601-1110 (813) 272-5912 | Fax: (813) 272-5811

MEMORANDUM

DATE: March 13, 2018

TO: Larry E. Ruiz, Manager Landfill Operations, Solid Waste

Management Division

FROM: Cindy A. Pelley, Landfill Supervisor, Solid Waste Management

Division

SUBJECT: Leachate Water Balance Report Forms for February 2018

Southeast County Landfill, Hillsborough County, Florida

BOARD OF COUNTY COMMISSIONERS

Victor D. Crist Ken Hagan Al Higginbotham Pat Kemp Lesley "Les" Miller, Jr. Sandra L. Murman Stacy R. White

COUNTY ADMINISTRATOR

Michael S. Merrill
COUNTY ATTORNEY
Chip Fletcher

INTERNAL AUDITOR

Peggy Caskey

CHIEF DEV. & INFRA.
SERVICES ADMINISTRATOR

Lucia E. Garsys

The Solid Waste Management Division (SWMD) staff has compiled and reviewed the leachate management operational data from the Southeast County Landfill Phases I-VI, Sections 7-8, and Section 9. Attached are the Leachate Water Balance Report Form (Table 1), the Leachate Field Data Entry Form (Table 2), and the 2018 Summary (Table 3). Also, attached find Figure 1 showing leachate levels in Pump Station B sump of Phases I-VI and rainfall for the month.

TABLE 1

Day (Column I)

Column I presents the calendar days for the month.

Rainfall (Column II)

Column II presents the average rainfall, in inches, as measured in the field from rainfall stations at the site. This month there was 0.82 inches of rainfall recorded at the Southeast County Landfill (SCLF).

Depth in Pond A (Column III)

Column III presents the daily depth, in feet, of effluent stored in effluent pond (Pond A). The daily depth in Pond A varies as a function of the spray irrigation frequency/duration and effluent hauled from the pond. This month the daily average depth of effluent stored in Pond A was 1.7 feet.

Depth in Pond B (Column IV)

Column IV presents the daily depth, in feet, of effluent or leachate that is stored in the effluent/leachate storage pond (Pond B). The depth in Pond B varies as a function of the evaporation frequency/duration and effluent or leachate hauled from the pond. This month the daily average depth of effluent stored in Pond B was 1.3.

Estimated Depth at Pump Station B Sump (PS-B) (Column V)

Column V presents the depth of leachate, in inches, in the PS-B sump. Leachate from Phases I-VI flows to the PS-B sump for removal from the landfill. PS-B then pumps the leachate to Pump Station A (PS-A). Daily depth readings from the PS-B sump are included in this column. This month PS-B was below the normal operation level. The average recorded depth of leachate in the PS-B sump was 17.8 inches.

Leachate Pumped to Pump Station A Sump from Phases I-VI Condensate Line (Column VI)

Column VI presents the daily amount of leachate, in gallons, collected from the Phases I-VI condensate line and pumped to Pump Station A (PS-A). The average daily amount of leachate pumped from the Phases I-VI condensate line was 8,597 gallons. A total of 240,723 gallons of leachate was pumped this month.

Leachate Pumped to MLPS from Phases I-VI (Column VII)

Column VIII presents the daily amount of leachate, in gallons, collected from PS-A and pumped through the MLPS to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. This column also includes the Phase II data from the dewatering wells and PS-2. The average daily amount of leachate pumped from PS-A was 78,387 gallons. A total of 2,194,846 gallons of leachate was pumped this month.

Leachate Pumped from Sections 7-8 LDS (Column VIII)

Column IX presents the quantity of leachate removed from the leak detection system (LDS) of Sections 7-8. The quantity is measured by a flow meter before being pumped for removal with Sections 7-8 leachate. The removal rate did not exceed 1,930 gallons per day. This month a total of 1,561 gallons of leachate was removed from the leak detection system of Sections 7-8.

Leachate Pumped to MLPS from Sections 7-8 (Column IX)

Column X presents the quantity of leachate collected at Sections 7-8 and pumped to the MLPS. The quantity is measured by a flow meter and includes any leachate removed from the leak detection system of Sections 7-8 (Column IX). This month a total of 20,127 gallons was removed.

Leachate Pumped to LTRF from the MLPS (Column X)

Column XI presents the total quantity of leachate pumped to the LTRF from Phases I-VI (including condensate removed from LFG Wells and Condensate Traps), and Sections 7-8. This month a total of 2,214,973 gallons of leachate was pumped to the LTRF.

Memorandum March 13, 2018 Page 3 of 5

Leachate Pumped to LTRF from Section 9 (Column XI)

Column XII presents the daily amount of leachate, in gallons, collected from Section 9 and pumped to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. A total of 102,640 gallons of leachate was pumped this month.

Leachate Pumped from Section 9 LDS (Column XII)

Column XIII presents the daily amount of leachate, in gallons, collected from the LDS of Section 9 and pumped to the 575,000-gallon storage tank at the LTRF for treatment or disposal. The removal rate did not exceed 4,651 gallons per day. This month leachate was not removed from the leak detection system.

Leachate Pumped from Compost Area Sump (Column XIII)

Column XIV presents the total quantity of leachate pumped to the LTRF and Pond B from the Compost Project Area Sump. This month 62,685 gallons of leachate was removed from the compost area and pumped to the LTRF.

Leachate in 575,000-Gallon Tank (Column XIV)

Column XV presents the daily amount of leachate, in gallons, stored in the 575,000-gallon leachate holding tank T1 at the LTRF. The amount of leachate stored in T1 is calculated based on the circumference of the tank and the daily level reading. This month an average of 323,300 gallons of leachate was stored in the tank.

Effluent in 575,000-Gallon Tank (Column XV)

Column XVI typically presents the daily amount of effluent, in gallons, stored in the 575,000-gallon effluent holding tank T6 at the LTRF. The amount of effluent stored in T6 is calculated based on the circumference of the tank and the daily level reading. This month an average of 329,500 gallons of effluent was stored in the tank.

Leachate Treated at LTRF (Column XVI)

Column XIIV presents the daily amount of leachate, in gallons, treated at the LTRF. This month a total of 518,100 gallons of leachate was treated at the plant.

Total Leachate Hauled (Column XVII)

Column XVIII presents the daily amount of leachate, in gallons, hauled off site. This month a total of 1,716,430 gallons of leachate was hauled off site.

Memorandum March 13, 2018 Page 4 of 5

Leachate Dust Control Sprayed (Column XVIII)

Column XIX presents the daily amount of leachate, in gallons, measured from the flow meter at the bypass-loading arm at the leachate storage tank. The leachate is used for dust control in the active area of the landfill. This month a total of 1,584 gallons of leachate was used for dust control.

Pond A Storage (Column XIX)

Column XX presents the daily amount of effluent, in gallons, stored in Pond A. The daily amount stored in the pond is calculated by using the daily depth of effluent in the Pond A (Column III). Under normal operating conditions, the daily amount of effluent stored in the pond varies depending upon the daily amount of leachate treated at the LTRF, the daily rainfall, daily effluent hauling operations, daily spray irrigation operations, and the daily amount of effluent used for dust control/evaporation. This month a daily average of 20,500 gallons of effluent was stored in Pond A.

Pond B Storage (Column XX)

Column XXI presents the daily amount of effluent, in gallons, stored in Pond B. The daily amount stored in the pond is calculated by using the daily depth of liquid in Pond B (Column IV). Under normal operating conditions, the amount stored in the pond will vary depending upon the daily amount of leachate/effluent removed from the pond by the evaporation system, hauled from the pond, used for dust control or evaporated; however during February leachate from the compost pad was stored in Pond B. This month a daily average of 40,800 gallons of leachate was stored in Pond B.

Effluent Sprayed at Pond B (Column XXI)

Column XXII presents the daily amount of effluent, in gallons, sprayed for evaporation at Pond B. The amount evaporated is calculated by using 5 percent of the daily flow meter quantity sprayed at Pond B and it is included in Column XXVI. This month a total of 87,976 gallons of effluent was sprayed in Pond B.

Effluent Irrigation (Column XXII)

Column XXIII presents the daily amount of effluent, in gallons, used for spray irrigation on top of Phases IV-VI. The daily amount of effluent irrigation on Phases I-VI is measured from the flow meter at the irrigation pump station. This month a total of 357,793 gallons of effluent was used for spray irrigation.

Memorandum March 13, 2018 Page 5 of 5

Effluent Dust Control Sprayed (Column XXIII)

Column XXIV presents the daily amount of effluent, in gallons, sprayed for dust control in the active areas of the SCLF. The daily amount of effluent used for dust control, is measured from the flow meter at the bypass-loading arm. This month effluent was not sprayed as dust control.

Total Effluent Hauled (Column XXIV)

Column XXV presents the daily amount of effluent, in gallons, hauled off site, as measured from the flow meter at the bypass-loading arm. This month a total of 136,771 gallons was hauled off site.

Total Evaporation (Column XXV)

Column XXVI presents the daily amount of leachate and effluent, in gallons, that evaporates and therefore will not be returned to the SCLF and/or requires treatment. Evaporation rates of 80 percent and 5 percent evaporation rate for spray in Pond B are assumed. Total evaporation estimated for this month was 292,000 gallons.

TABLE 2

Table 2 presents data assembled from daily logs compiled by the SWMD staff.

TABLE 3

Leachate Balance Summary

The Leachate Balance Summary (see Table 3) presents a review of inflow and outflow quantities for the LTRF, as well as rainfall and effluent disposal quantities at the landfill. Total inflow quantity to the LTRF was 2,382,005 gallons. Total outflow quantity from the LTRF was 2,236,014 gallons. The change in storage for the month increased by 145,991 gallons.

Please advise should you have any questions concerning the information provided.

TABLE 1. LEACHATE WATER BALANCE REPORT FORM FEBRUARY 2018 SOUTHEAST COUNTY LANDFILL, HILLSBOROUGH COUNTY, FLORIDA

XXV			Total	Evaporation	(gal)	3,800	0	58,300	0	0	0	0	19,100	0	36,200	0	9,700	10,300	17,100	0	36,200	19,200	0	0	5,300	14,300	11,800	22,500	26,600	0	1,600	0	0			000 000	292,000		4,900 10,430
XXIV		Total	Effluent	Hauled	(gal.)	7,107	43,149	0	0	0	0	14,399	14,199	0	0	0	0	43,714	0	0	14,203	0	0	0	0	0	0	0	0	0	0	0	0			146 701	136,771		4,900
XXIII		Effluent	Dust Control	(Sprayed)	(gal)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0				0		0
XXII		Effluent	Irrigation		(gal.)	0	0	72,860	0	0	0	0	23,920	0	45,310	0	12,122	12,835	21,335	0	42,861	23,980	0	0	6,621	116,71	14,746	28,083	33,207	0	2,002	0	0		1	0000000	357,793		12,800
IXX	Effluent	Sprayed	Pond	В	(gal)	76,072	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11,904	0	0	0	0	0	0	0	0	0	0	0	0			20000	87,976		
XX		Pond	В	Storage	(gal)	72,000	72,000	80,000	64,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	51,000	81,000	51,000	51,000	19,000	19,000	0	0	0	0	0	0					40,800	
XIX		Pond	٧	Storage	(gal)	74,000	79,000	83,000	48,000	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	70,000	48,000	32,000	17,000	61,000	61,000					20,500	
XVIII		Leachate	Dust Control	(Sprayed)	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1,584	0	0	0	0	0	0	0	0	0	0	0	0			9 0 0	1,584		100
IIAX		Total	Leachate	Hauled	(gal.)	141,226	51,824	21,504	0	51,560	44,027	65,064	94,262	79,949	49,780	0	132,646	51,865	153,436	144,767	117,298	49,646	0	28,371	35,507	78,934	79,420	49,731	42,627	0	43,944	36,637	72,405			1 717 400	1,716,430		
IVX	Leachate	Treated	at	LTRF	(gal.)	26,200	25,900	27,500	27,500	27,500	26,400	25,800	29,600	5,700	2,000	0	0	0	0	0	4,200	21,800	21,800	21,800	21,800	18,800	18,700	25,800	27,400	27,400	27,400	29,500	27,500			000011	518,000		
ΛX	Effluent	.g	575K	Tank	(gal.)	372,000	374,000	358,000	381,000	405,000	417,000	427,000	408,000	394,000	369,000	361,000	353,000	348,000	305,000	264,000	266,000	261,000	276,000	290,000	271,000	245,000	259,000	261,000	278,000	306,000	333,000	312,000	333,000					329,500	
XIV	Leachate	. Е	575K	Tank	(gal)	295,000	214,000	230,000	303,000	377,000	377,000	374,000	365,000	341,000	358,000	409,000	461,000	405,000	398,000	317,000	230,000	197,000	229,000	261,000	269,000	309,000	283,000	302,000	300,000	334,000	367,000	372,000	374,000					323,300	
XIII			Compost	Leachate	(gal.)	0	0	62,685	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			000	62,685	2,239	
IIX	Leachate	Pumped from	Section 9	TDS	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			-	0	0	
IX	Leachate		to LTRF from	Section 9	(gal.)	2,723	3,150	2,310	2,906	2,906	1,763	2,994	2,379	2,621	3,279	2,727	2,727	2,706	3,973	5,162	7,136	3,549	0	0	968'6	15,539	6,802	2,772	2,272	2,725	2,725	2,424	2,977			07 001	102,640	3,666	
×	Leachate		щ	MPLS	(gal)	91,143	90,123	85,900	85,778	82,953	56,859	83,873	85,902	79,126	81,650	80,916	83,374	74,482	70,095	77,967	84,039	80,544	77,643	77,137	74,965	74,780	72,106	73,296	76,016	80,447	966'08	76,313	76,551			0 0 1 1 0 00	2,214,973	79,106	
X	Leachate		9	Sections 7-8	(gal.)	6,625	3,529	3,640	240	240	961	252	225	224	229	919	919	222	220	140	009	236	223	223	193	249	237	861	163	156	156	137	143			20100	20,127	719	
VIII				TDS	(gal.)	436	0	0	0	0	0	0	22	0	0	522	522	0	0	48	12	0	0	0	0	0	0	0	0	0	0	0	0		+	1 200	1,561	99	-
VII	Leachate			I-VI		84,518	86,594	82,260	85,538	82,713	56,663	83,621	85,677	78,902	81,421	80,301	82,759	74,260	69,875	77,827	83,439	80,308	77,420	76,914	74,772	74,531	71,869	73,098	75,853	80,291	80,840	76,176	76,408			2000000	2,194,846	78,387	
VI			Phases I - VI	Condensate	(gal.)	17,962	19,197	18,518	15,377	18,306	10,794	15,109	14,513	13,788	13,888	13,888	14,781	14,956	844	3,874	513	542	538	2,391	3,666	3,609	3,452	3,569	3,735	3,735	3,780	1,600	3,799			CAR OLO	240,723	8,597	
>	Estimated	Depth	at	PS-B	(in.)	14.2	16.0	16.0	16.3	16.6	19.3	19.3	18.8	18.8	19.3	19.3	19.3	18.5	16.1	17.3	16.1	17.2	17.3	17.3	18.2	15.9	19.4	21.3	19.4	19.5	9.61	15.1	16.7					17.8	
V	Depth	.EI	Pond	В	(ff.)	1.9	1.9	2.0	1.8	9.1	1.6	9.1	1.6	1.6	1.6	9.7	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0		1	†	1	1.3	1
Ħ	Depth	.E	Pond	٧	(fr.)	2.3	2.4	2.5	1.7	6.0	1.3	1.6	2.1	1.9	2.4	2.0	1.6	1.5	1.2	1.8	1.8	8.0	0.7	9.0	9.0	2.5	2.1	2.2	1.7	1.3	8.0	2.0	2.0			†	1	1.7	
п				Rainfall	(in.)	00'0	00.00	00.00	0.82	00'0	00'0	00.00	00.00	00'0	00.00	00'0	00.00	00.00	00'0	00'0	00'0	00'0	00'0	00.00	00'0	00:00	00'0	00'0	00.00	00'0	00.00	00'0	00.00			000	0.82	9.	
-		_		_	Day	1	2	3	4	5	9	7	8	6	10	П	12	13	14	15	91	17	18	61	20	21	22	23	24	25	56	27	28		Ī	7	Total	Daily Average	Mo. Average

Notes:

2. Values in Vol Records, NN = Nea Available.

2. Values in bolt are estimated, whites in tails are substitute for missing that and are based on averaged values.

3. Daily average is calculated by offering the total by the statual days measured in the month.

5. Daily average calculated by dividing the total by the statual days required in the month.

5. Column Litter se is set han OUI traces and are included in total.

6. Column Litter for the column and the diffigures.

Columns IX & X, Section 7-8 leak detection pumped into Section 7 leadules sump riser.
 Columns Van WY, Leaduled from clopp in 52500 get lands.
 Columns CAW VI, calculated from clopp in 52500 get lands.
 Columns VXVVI includes 40% of the daily values from Columns XIX. XXIII, and XXIV plats 5% of the daily values from column XXII.

TABLE 2. FIELD DATA ENTRY FORM FEBRUARY 2018
SOUTHEAST COUNTY, LANDFILL, HILLSBOROUGH COUNTY, FLORIDA

×	Effluent	Tonillo Services	(aprayed)																														0
W	Houled	Janea	(gal.)	7,107	28,608					14,399	14,199					14,032			14,203														92,548
Λ	Defined Hendel	Cindent	(gal.)		14,541											29,682																	44,223
n	Leachate	Just Collitor	(Sprayeu)																														0
Т		Ţ	(gal.)	65,076	21,740	21,504		51,560	44,027	65,064	56,851	49,783	49,780		50,164	14,224	78,169	78,051	28,371	49,646		28,371	35,507	78,934	79,420	49,731	42,627		43,944	36,637	72,405		1,191,586
S	F-1	Cartage	(gal.)	76,150	30,084						37,411	30,166			82,482	37,641	75,267	66,716	88,927														524,844
R	Leachate	1 Icalcu	(gal.)	26,151	25,868	27,453	27,453	27,454	26,366	25,796	29,592	5,660	2,040	0	0	0	0	0	4,186	21,806	21,806	21,806	21,806	18,835	18,739	25,833	27,377	27,377	27,377	29,507	27,542		517,830
0	Depth in	Definer	(ft.)	12.92	13.00	12.42	13.25	14.08	14.50	14.83	14.17	13.67	12.83	12.54	12.25	12	10.58	9.17	9.25	80.6	9.58	10.08	9.42	8.50	9.00	80.6	29.6	10.63	11.58	10.83	11.58		
Ь	Depth in	J.Dr. Lallik	(ft.)	10.25	7.42	8.00	10.54	13.08	13.08	13.00	12.67	11.83	12.42	14.21	16.00	14	13.83	11.00	8.00	6.83	96.7	80.6	9.33	10.75	9.83	10.50	10.42	11.59	12.75	12.92	13.00		
0	Effluent	Spray	(gal.)	0	0	72,860		0	0	0	23,920	0	45,310		12,122	12,835	21,335	0	42,861	23,980		0	6,621	17,911	14,746	28,083	33,207		2,002	0	0		357,793
z	4	Polid A	₹ (#)	2.3	2.4	2.5	1.7	6.0	1	1.6	2.1	1.9	2.4	2.0	1.6	2	1.2	1.8	1.8	8.0	0.7	9.0	9.0	2.5	2.1	2.2	1.7	1.3	8.0	2.0	2.0		
M	Pond B	Camara	(gal)	76,072.0	0.0	0.0	0.0	0.0	0	0.0	0.0	0.0	0	0.0	0.0	0	0.0	0.0	11904.0	0.0		0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0		87,976
Γ	. T		(f.)		1.9	2.0	1.8	1.6	2	1.6	1.6	1.6	1.6	9.1	1.6	2	1.6	9.1	1.6	1.6	9.1	9.1	1.6	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0		
Ж	0 1			52,257	52,257	52,257	52,257	52,257	52,257	52,257	52,279	52,279	52,279	52,801	53,322	53,322	53,322	53,370	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382		
ſ	0 1		(gal.)	5,601,273	5,604,802	5,608,442	5,608,682	5,608,922	5,609,118	5,609,370	5,609,595	5,609,819	5,610,048	5,610,664	5,611,279	5,611,501	5,611,721	5,611,861	5,612,461	5,612,697	5,612,920	5,613,143	5,613,336	5,613,585	5,613,822	5,614,020	5,614,183	5,614,339	5,614,495	5,614,632	5,614,775		
_		e nedulos	(gal.)		157	62,842	52,842		H		62,842		H	62,842	H		H	62,842	H		62,842	-	H			H	62,842	-	-				
Н		7 6 11011235		5,846,331	5,846,331	5,846,331	846,331		H	5,846,332	5,846,332	5,846,332	5,846,331	5,846,331	5,846,331	5,846,331	H		H	7	5,846,327		L		5,846,326	L	5,846,325	846,324					
Ğ		Section 9	(gal.)	_	298,779 5,	300,117 5,	300,911 5,	-	H		H	H	304,491 5,	H	306,461 5,	-	H	308,925 5,	Н		-	309,628 5,	H	_	_	H	338,245 5,	38,299 5,	H	338,359 5,			
Н	_	December 35		L	233,212 29		6,296 30	238,408 30	H	241,776 30	L		248,657 30	-		254,247 3(H	261,517 30	H	271,499 30	H		H	_	274,650 33	H	279,663 33	H	285,004 33	287,422 33			
Е	_	De Billing		_	16.0 23.		16.3 23.	16.6 23		19.3 24	18.8 24.	18.8	19.3 24	19.3 250	19.3 2.5			17.3 26		17.2 27	7.3 27	17.3 27		15.9 27.	19.4 27	21.3	19.4	19.5 28.	19.6 28	15.1 28	16.7 29		
							I																					57					
D	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_		3,784,879	3,846,900	3,904,732	3,965,842	4,026,951	4,081,190	4,144,166	4,207,295	4,263,085	4,323,285	4,382,365	4,441,444	4,494,487	4,543,102	4,598,343	4,659,380	4,717,512	4,772,756	4,828,000	4,881,962	4,935,680	4,986,545	5,039,416	5,094,203	5,153,428	5,212,653	5,267,500	5,322,000		
C	DI 1 1/1	rilases 1 - v 1	(gal.)	17,962	19,197	18,518	15,377	18,306	10,794	15,109	14,513	13,788	13,888	13,888	14,781	14,956	844	3,874	513	542	538	2,391	3,666	3,609	3,452	3,569	3,735	3,735	3,780	1,600	3,799		
В		D.:	(in.)	0.00	0.00	0.00	0.82	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.82
Α			Day	_	2	3	4	5	9	7	~	6	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	56	27	28		Totals

Notes: 1. 2. 3.

NR = No Records, NA = Not Available. Values in italic are substitute for missing data and are based on averaged values Columns I and L include quantities from leak detection system.

83	
ĕ	
Ĕ.	
-=	
_	
0	
0	
æ	
ਕ	
-	
-	
ŝ	
- 83	
<u>. 2</u>	
100	
.13	
e	
0	
2	
±	
B	
п	
- 8	
=	
-5	
_	
Ŭ.	

5. Columns C, D, E, G, H, I, J, K, L, N, P, S-X and Y are quantities from flow meters. 6. Columns M and O measured from staff gages in each pond.

Section 9	acres	0	15	0	0	
Phases I-VI	acres	5	134.4	23	0	
Type of Cover	Jpc or core.	Open	ntermediate	Final	Not Opened	




Figure 1. Leachate Levels in Pump Station B and Rainfall for February 2018.



PUBLIC WORKS

PO Box 1110 Tampa, FL 33601-1110 (813) 272-5912 | Fax: (813) 272-5811

MEMORANDUM

DATE: April 12, 2018

TO: Larry E. Ruiz, Manager Landfill Operations, Solid Waste

Management Division

FROM: Cindy A. Pelley, Landfill Supervisor, Solid Waste Management

Division

SUBJECT: Leachate Water Balance Report Forms for March 2018

Southeast County Landfill, Hillsborough County, Florida

BOARD OF COUNTY COMMISSIONERS

Victor D. Crist Ken Hagan Al Higginbotham Pat Kemp Lesley "Les" Miller, Jr. Sandra L. Murman Stacy R. White

COUNTY ADMINISTRATOR

Michael S. Merrill COUNTY ATTORNEY Chip Fletcher

INTERNAL AUDITOR

Peggy Caskey

CHIEF DEV. & INFRA.
SERVICES ADMINISTRATOR

Lucia E. Garsys

The Solid Waste Management Division (SWMD) staff has compiled and reviewed the leachate management operational data from the Southeast County Landfill Phases I-VI, Sections 7-8, and Section 9. Attached are the Leachate Water Balance Report Form (Table 1), the Leachate Field Data Entry Form (Table 2), and the 2018 Summary (Table 3). Also, attached find Figure 1 showing leachate levels in Pump Station B sump of Phases I-VI and rainfall for the month.

TABLE 1

Day (Column I)

Column I presents the calendar days for the month.

Rainfall (Column II)

Column II presents the average rainfall, in inches, as measured in the field from rainfall stations at the site. This month there was 1.06 inches of rainfall recorded at the Southeast County Landfill (SCLF).

Depth in Pond A (Column III)

Column III presents the daily depth, in feet, of effluent stored in effluent pond (Pond A). The daily depth in Pond A varies as a function of the spray irrigation frequency/duration and effluent hauled from the pond. This month the daily average depth of effluent stored in Pond A was 2.8 feet.

Depth in Pond B (Column IV)

Column IV presents the daily depth, in feet, of effluent or leachate that is stored in the effluent/leachate storage pond (Pond B). The depth in Pond B varies as a function of the evaporation frequency/duration and effluent or leachate hauled from the pond. This month the daily average depth of effluent stored in Pond B was 0.7.

Estimated Depth at Pump Station B Sump (PS-B) (Column V)

Column V presents the depth of leachate, in inches, in the PS-B sump. Leachate from Phases I-VI flows to the PS-B sump for removal from the landfill. PS-B then pumps the leachate to Pump Station A (PS-A). Daily depth readings from the PS-B sump are included in this column. This month PS-B was below the normal operation level. The average recorded depth of leachate in the PS-B sump was 17.1 inches.

Leachate Pumped to Pump Station A Sump from Phases I-VI Condensate Line (Column VI)

Column VI presents the daily amount of leachate in gallons, pumped to Pump Station A (PS-A), collected from the Phases I-VI condensate line. The average daily amount of leachate pumped from the Phases I-VI condensate was 2,102 gallons. A total of 65,160 gallons of leachate was pumped this month.

Leachate Pumped to MLPS from Phases I-VI (Column VII)

Column VIII presents the daily amount of leachate, in gallons, collected from PS-A and pumped through the MLPS to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. This column also includes the Phase II data from the dewatering wells and PS-2. The average daily amount of leachate pumped from PS-A was 68,489 gallons. A total of 2,123,174 gallons of leachate was pumped this month.

Leachate Pumped from Sections 7-8 LDS (Column VIII)

Column IX presents the quantity of leachate removed from the leak detection system (LDS) of Sections 7-8. The quantity is measured by a flow meter before being pumped for removal with Sections 7-8 leachate. The removal rate did not exceed 1,930 gallons per day. This month leachate was not removed from the leak detection system of Sections 7-8.

Leachate Pumped to MLPS from Sections 7-8 (Column IX)

Column X presents the quantity of leachate collected at Sections 7-8 and pumped to the MLPS. The quantity is measured by a flow meter and includes any leachate removed from the leak detection system of Sections 7-8 (Column IX). This month a total of 74,047 gallons was removed.

Leachate Pumped to LTRF from the MLPS (Column X)

Column XI presents the total quantity of leachate pumped to the LTRF from Phases I-VI (including condensate removed from LFG Wells and Condensate Traps), and Sections 7-8. This month a total of 2,197,221 gallons of leachate was pumped to the LTRF.

Leachate Pumped to LTRF from Section 9 (Column XI)

Column XII presents the daily amount of leachate, in gallons, collected from Section 9 and pumped to the 575,000-gallon storage tank at the Leachate Treatment and Reclamation Facility (LTRF) for treatment or disposal. A total of 73,738 gallons of leachate was pumped this month.

Leachate Pumped from Section 9 LDS (Column XII)

Column XIII presents the daily amount of leachate, in gallons, collected from the LDS of Section 9 and pumped to the 575,000-gallon storage tank at the LTRF for treatment or disposal. The removal rate did not exceed 4,651 gallons per day. This month leachate was not removed from the leak detection system.

Leachate Pumped from Compost Area Sump (Column XIII)

Column XIV presents the total quantity of leachate pumped to the LTRF and Pond B from the Compost Project Area Sump. This month 23,840 gallons of leachate was removed from the compost area and pumped to the LTRF.

Leachate in 575,000-Gallon Tank (Column XIV)

Column XV presents the daily amount of leachate, in gallons, stored in the 575,000-gallon leachate holding tank T1 at the LTRF. The amount of leachate stored in T1 is calculated based on the circumference of the tank and the daily level reading. This month an average of 288,600 gallons of leachate was stored in the tank.

Effluent in 575,000-Gallon Tank (Column XV)

Column XVI typically presents the daily amount of effluent, in gallons, stored in the 575,000-gallon effluent holding tank T6 at the LTRF. The amount of effluent stored in T6 is calculated based on the circumference of the tank and the daily level reading. This month an average of 367,800 gallons of effluent was stored in the tank.

Leachate Treated at LTRF (Column XVI)

Column XIIV presents the daily amount of leachate, in gallons, treated at the LTRF. This month a total of 814,870 gallons of leachate was treated at the plant.

Total Leachate Hauled (Column XVII)

Column XVIII presents the daily amount of leachate, in gallons, hauled off site. This month a total of 1,495,682 gallons of leachate was hauled off site.

Memorandum April 12, 2018 Page 4 of 5

Leachate Dust Control Sprayed (Column XVIII)

Column XIX presents the daily amount of leachate, in gallons, measured from the flow meter at the bypass-loading arm at the leachate storage tank. The leachate is used for dust control in the active area of the landfill. This month a total of 9,695 gallons of leachate was used for dust control.

Pond A Storage (Column XIX)

Column XX presents the daily amount of effluent, in gallons, stored in Pond A. The daily amount stored in the pond is calculated by using the daily depth of effluent in the Pond A (Column III). Under normal operating conditions, the daily amount of effluent stored in the pond varies depending upon the daily amount of leachate treated at the LTRF, the daily rainfall, daily effluent hauling operations, daily spray irrigation operations, and the daily amount of effluent used for dust control/evaporation. This month a daily average of 96,500 gallons of effluent was stored in Pond A.

Pond B Storage (Column XX)

Column XXI presents the daily amount of effluent, in gallons, stored in Pond B. The daily amount stored in the pond is calculated by using the daily depth of liquid in Pond B (Column IV). Under normal operating conditions, the amount stored in the pond will vary depending upon the daily amount of leachate/effluent removed from the pond by the evaporation system, hauled from the pond, used for dust control or evaporated; however during March leachate from the compost pad was stored in Pond B. This month a daily average of 14,100 gallons of leachate was stored in Pond B.

Effluent Sprayed at Pond B (Column XXI)

Column XXII presents the daily amount of effluent, in gallons, sprayed for evaporation at Pond B. The amount evaporated is calculated by using 5 percent of the daily flow meter quantity sprayed at Pond B and it is included in Column XXVI. This month effluent was not sprayed in Pond B.

Effluent Irrigation (Column XXII)

Column XXIII presents the daily amount of effluent, in gallons, used for spray irrigation on top of Phases IV-VI. The daily amount of effluent irrigation on Phases I-VI is measured from the flow meter at the irrigation pump station. This month a total of 336,300 gallons of effluent was used for spray irrigation.

Memorandum April 12, 2018 Page 5 of 5

Effluent Dust Control Sprayed (Column XXIII)

Column XXIV presents the daily amount of effluent, in gallons, sprayed for dust control in the active areas of the SCLF. The daily amount of effluent used for dust control, is measured from the flow meter at the bypass-loading arm. This month effluent was not sprayed as dust control.

Total Effluent Hauled (Column XXIV)

Column XXV presents the daily amount of effluent, in gallons, hauled off site, as measured from the flow meter at the bypass-loading arm. This month a total of 311,813 gallons was hauled off site.

Total Evaporation (Column XXV)

Column XXVI presents the daily amount of leachate and effluent, in gallons, that evaporates and therefore will not be returned to the SCLF and/or requires treatment. Evaporation rates of 80 percent and 5 percent evaporation rate for spray in Pond B are assumed. Total evaporation estimated for this month was 276,800 gallons.

TABLE 2

Table 2 presents data assembled from daily logs compiled by the SWMD staff.

TABLE 3

Leachate Balance Summary

The Leachate Balance Summary (see Table 3) presents a review of inflow and outflow quantities for the LTRF, as well as rainfall and effluent disposal quantities at the landfill. Total inflow quantity to the LTRF was 2,299,499 gallons. Total outflow quantity from the LTRF was 2,320,247 gallons. The change in storage for the month decreased by 20,748 gallons.

Please advise should you have any questions concerning the information provided.

TABLE 1. LEACHATE WATER BALANCE REPORT FORM MARCH 2018 SOUTHEAST COUNTY LANDFILL, HILLSBOROUGH COUNTY, FLORIDA

XXV			Total	Evaporation	(gal.)	0	19,100	46,200	0	0	14,500	0	3,900	2,600	0	0	0	0	0	32,200	0	38,000	0	15,000	0	2,600	27,000	16,100	26,200	0	22,900	0	0	300	10,200	0	276,800		8,930
XXIV		Total	Effluent		(gal.)	0	0	0	0	0	0	0	0	0	0	0	29,251	36,534	36,558	36,532	28,415	0	0	0	0	0	0	35,423	7,110	0	7,306	72,778	14,798	7,108	0	0	311,813		10,100
XXIII		Effluent	Dust Control	(Sprayed)	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0
XXII			Irrigation		(gal.)	0	23,932	57,791	0	0	18,098	0	0	3,273	0	0	0	0	0	40,207	0	47,471	0	18,705	0	3,198	33,757	15,372	32,748	0	28,624	0	0	327	12,797	0	336,300		10,800
IXX	Effluent	Sprayed	Pond	В	(gal)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
XX		Pond	В	Storage	(gal)	0	0	0	0	0	0	0	0	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000	19,000		14,100	
XIX		Pond	٧	Storage	(gal.)	93,000	129,000	113,000	103,000	93,000	000'86	79,000	123,000	129,000	129,000	129,000	129,000	129,000	129,000	118,000	88,000	88,000	20,000	48,000	74,000	79,000	79,000	88,000	79,000	74,000	70,000	88,000	88,000	88,000	88,000	79,000		96,500	
XVIII		Leachate	Dust Control	(Sprayed)	(gal.)	0	0	0	0	0	0	0	4,893	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4,802	0	0	0	0	0	0	0	0	9,695		300
IIAX		Total	Leachate	Hauled	(gal.)	79,442	49,737	49,762	0	43,973	43,958	78,483	86,524	36,133	43,872	0	52,561	45,201	80,727	94,827	44,467	42,584	0	880'68	43,662	72,040	86,361	7,014	42,431	0	81,645	7,518	74,168	74,386	45,123	0	1,495,682		
IVX	Leachate	Treated	at	LTRF	(gal.)	33,253	30,764	27,902	27,902	27,902	30,489	28,194	28,220	19,093	32,662	32,663	32,663	24,504	28,674	28,033	26,196	26,910	26,910	26,910	27,869	15,996	31,736	22,708	22,203	23,203	23,205	22,441	22,812	22,113	17,280	23,460	814,870		
XX	Effluent	.EI	575K	Tank	(gal.)	326,000	317,000	331,000	335,000	338,000	362,000	389,000	367,000	345,000	362,000	386,000	410,000	398,000	386,000	374,000	369,000	362,000	386,000	410,000	386,000	410,000	430,000	410,000	386,000	391,000	396,000	360,000	307,000	312,000	324,000	336,000		367,800	
XIV	Leachate	.ш	575K	Tank	(gal.)	350,000	302,000	331,000	345,000	360,000	360,000	358,000	322,000	274,000	288,000	314,000	341,000	341,000	333,000	288,000	238,000	245,000	274,000	302,000	281,000	290,000	245,000	199,000	230,000	248,000	266,000	230,000	261,000	235,000	214,000	281,000		288,600	
XIII			Compost	Leachate	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	22,530	0	0	0	0	0	0	0	0	0	1,310	23,840	692	_
IIX	Leachate	Pumped from	6		(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
			_			2,335	2,582	2,718	4,250	4,250	8,847	268	0	0	895	1,947	1,947	1,969	2,362	2,001	3,022	2,591	7,569	7,569	165	0	0	486	1,884	1,728	1,728	1,564	2,174	1,780	2,758	1,722	73,738	2,379	
X	Leachate		m to LTRF from	Section 9	(gal.)	38	128	920	24	93	662	130	200	346	792	.25	120	949	903	213	50,317	70,945	19.	164	213	136	38	000	69	99.)22	940	103	346	183	731	121	878	
×	Leachate	Pumped	to LTRF fron	MPLS	(gal.)	59,736	83,428	67,650	66,074	59,693	68,799	91,430	86,620	73,346	72,792	79,825	79,420	73,949	606,903	66,617			74,464	56,764	61,617	76,136	81,938	58,000	62,169	998'99	66,022	62,640	64,403	69,846	66,083	132,731	2,1	70,878	
X	Leachate	Pumped	to MLPS from	Sections 7-8	(gal.)	144	129	134	147	147	18	163	158	118	961	136	136	264	305	322	297	232	201	201	332	487	449	287	238	476	476	788	099	519	333	65,493	74,047	2,389	
VIII	Leachate		99	TDS	(gal.)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	_
					•	59,592	83,299	67,516	65,928	59,547	812,89	91,267	86,462	73,228	72,596	069'62	79,285	73,685	865'99	66,295	50,020	70,713	74,263	56,563	61,285	75,649	61,489	57,713	61,931	96,390	65,546	61,852	63,743	69,327	65,750	67,238	2,123,174	68,489	-
IIA	Leachate	Pumped	to MLPS	from	(gal.)	3	2	2	2	9	5	6	6	4	0	6	4	0	2	4	4	9	9	2	8	2	1	6	8	8	2	∞	6	8	2	3		2	
IA			Phases I-VI	Condensate	(gal.)	2,983	3,612	3,332	3,332	902	2,255	3,079	389	514	2,530	2,530	2,984	3,890	4,112	3,284	3,904	3,446	3,446	2,255	418	3,172	1,921	2,089	298	298	1,052	899	1,199	48	535	983	65,160	2,102	
>	Estimated	Depth	at	PS-B	(in.)	9.61	20.9	15.3	16.2	17.1	15.1	14.0	8.91	8.91	20.6	18.2	15.8	13.9	1.91	18.8	14.2	16.6	17.3	17.9	16.2	15.8	18.8	18.6	17.4	16.8	1.91	16.8	9.91	18.2	20.5	16.0		17.1	
2	Depth	.ш	Pond	В	(ft.)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0		0.7	
Ħ	Depth	.П	Pond	V	(ft.)	2.7		3.1	2.9	2.7	2.8	2.4	3.3	3.4	3.4	3.4	3.4	3.4	3.4	3.2	2.6	2.6	2.2	1.7	2.3	2.4	2.4	2.6	2.4	2.3	2.2	2.6	2.6	2.6	2.6	2.4		2.8	
=				Rainfall	(in.)	00'0	00'0	00'0	00'0	00'0	0.00	00'0	00'0	00'0	00'0	00'0	00'0	000	00'0	00'0	00'0	0.00	00'0	000	1.06	00.0	0.00	00'0	0.00	00'0	00'0	00'0	000	00'0	00'0	00'0	1.06	ge	0.
-					Day	-	2	3	4	2	9	7	∞	6	10	11	12	13	14	15	91	17	81	61	20	21	22	23	24	25	26	27	28	29	30	31	Total	Daily Average	Mo. Average

Notes:

1. NR = No Records, NA = Not Available.

2. Values in bold are estimated, values in tale are substitute for missing data and are based on averaged values.

3. Dayla verage is calculated by dividing the total by the attent days measured in the month.

4. Monthly wearge estimated by dividing the total by the number of days of the month.

5. Colomn I, There is less than 0.0 inches and is not included in total.

6. Colomns III and IV, field measured at staff gauges.

Columns IX & X, Section 7-8 leak detection pumped into Section 7 leachate sump riser.
 Columns Van VKI calculated from depth in 755000 gel. lanks.
 Columns VAVI VXIV. XVII-XXIV. and XXIV. XVII-XXIV. and XXIV. Avii calculated from column XXIII. and XXIV plus 5% of the daily values from column XXII. and XXIV plus 5% of the daily values from column XXII.

TABLE 2. FIELD DATA ENTRY FORM MARCH 2018 SOUTHEAST COUNTY, FLORIDA

×	Effluent Dust Control	(Sprayed)	(Ear)																															0
M	Janled	County	(gar)											29,251	36,534	36,558	36,532	28,415							35,423	7,110		7,306	35,633	7,311	7,108			267,181
Λ	Effluent Hauled	Contractor	(gar.)																										37,145	7,487				44,632
U	Leachate	(Sprayed)	(gal.)							4,893															4,802									9,695
Т		20	79.442	49,737	49,762		43,973	43,958	78,483	86,524	36,133	43,872		7,313		35,516	49,708	14,385	42,584		43,868	43,662	72,040	86,361	7,014	42,431		36,529		36,520	29,227			1,059,042
S	Deline Heatedage I	Contractor	(Sall.)											45,248	45,201	45,211	45,119	30,082			45,215							45,116	7,518	37,648	45,159	45,123	Н	436,640
R	Leachate	at LTRF	33,253	30,764	27,902	27,902	27,902	30,489	28,194	28,220	19,093	32,662	32,663	32,663	24,504	28,674	28,033	26,196	26,910	26,910	26,910	27,869	15,996	31,736	22,708	22,203	23,203	23,205	22,441	22,812	22,113	17,280	23,460	814,870
0	Depth in	Effluent	(11.)	11.00	11.50	11.63	11.75	12.58	13.50	12.75	12.00	12.58	13.42	14.25	13.83	13.42	13.00	12.83	12.58	13.42	14.25	13.42	14.25	14.92	14.25	13.42	13.59	13.75	12.50	10.67	10.83	11.25	11.67	
Ь	Depth in	Leachate	(II.) 12.17	10.50	11.50	12.0	12.50	12.50	12.42	11.17	9.50	10.00	10.92	11.83	11.83	11.58	10.00	8.25	8.50	9.50	10.50	9.75	10.08	8.50	6.92	8.00	8.63	9.25	8.00	80.6	8.17	7.42	9.75	
0	Effluent	Irrigation	(gai.)	23,932	57,791	0	0	18,098	0	0	3,273	0	0	0	0	0	40,207	0	47,471	0	18,705	0	3,198	33,757	15,372	32,748	0	28,624	0	0	327	12,797	0	336,300
z	Pond A	Depth	2.7	3.4	3.1	2.9	2.7	2.80	2.4	3.3	3.4	3.4	3.4	3.4	3.40	3.4	3.2	2.6	2.6	2.2	1.7	2.3	2.4	2.4	2.6	2.4	2.3	2.2	2.6	2.6	2.6	2.6	2.4	
M	Pond B	Sprayed	0.0	0.0	0.0	0.0	0.0	0	0.0	0.0	0.0	0	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0
Γ	Pond B	Depth	0.0	0.0	0.0	0.0	0.0	0.00	0.0	0.0	1.0	1.0	1.0	1.0	1.00	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	I.0	1.0	1.0	1.0	1.0	1.0	1.0	
К	Sactions 7.8	TDS	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	53,382	
J	Sections 7-8	Pump	5.614.919	5,615,048	5,615,182	5,615,329	5,615,475	5,615,556	5,615,719	5,615,877	5,615,995	5,616,191	5,616,327	5,616,462	5,616,726	5,617,031	5,617,353	5,617,650	5,617,882	5,618,083	5,618,284	5,618,616	5,619,103	5,619,552	5,619,839	5,620,077	5,620,553	5,621,029	5,621,817	5,622,477	5,622,996	5,623,329	5,688,822	
I	Commost		t	62,842		Н		H		H		62,842		H	62,842	H			62,842	Н		H		85,372		85,372	85,372		Н		85,372	Н	86,682	
Н	Section 0	TDS	5.846,320	5,846,319	5,846,319	5,846,318	5,846,317	5,846,316	5,846,316	5,846,316	5,846,316	5,846,315	5,846,315	5,846,314	5,846,313	5,846,313	5,846,312	5,846,311	5,846,311	5,846,309	5,846,307	5,846,307	5,846,307	5,846,307	5,846,307	5,846,307	5,846,306	5,846,305	5,846,305	5,846,305	5,846,304	5,846,303	5,846,303	
Ð	Section 0	Pump 2	338,415	338,464	338,473	338,533	338,592	338,723		Н	338,724	338,732	338,736	338,740		H	338,760	338,787	338,791	338,831	338,870	338,871	338,871	338,871	338,871	338,876	338,879	338,881	338,882	338,884	338,887	338,890	338,891	
F	Section 9	Pump 1	(gar.) 292.678	295,211	297,920	302,111	306,301	315,017	315,913	315,913	315,913	316,800	318,743	320,685	322,647	325,005	326,997	329,992	332,579	340,108	347,637	347,801	347,801	347,801	348,287	350,166	351,892	353,617	355,180	357,352	359,129	361,884	363,605	
Е	Reading	PS-B	19.6	20.9	15.3	16.2	17.1		14.0	8.91	16.8	20.6	18.2	15.8	13.90	16.1	18.8	14.2	16.6	17.3	17.9	16.2	15.8	18.8	18.6	17.4	8.91	16.1	16.8	16.6	18.2	20.5	16.0	
D	Flow Meter	Pump Sta. A	5.381,000	5,447,400	5,508,535	5,568,082	5,627,628	5,691,036	5,763,200	5,827,732	5,879,800	5,931,171	5,989,636	6,048,100	6,102,600	6,150,250	6,197,629	6,245,630	6,296,500	6,350,920	6,405,340	6,464,525	6,521,900	6,566,942	808,709,8	6,651,766	6,700,183	6,748,600	6,793,731	6,839,510	6,891,062	6,942,847	6,992,885	
C	Dhasas I - VI		2.983		3,332				_		514	2,530	2,530	2,984					3,446	3,446	2,255	418	3,172				298	_				535		
В	<u> </u>	=	0.00	0.00	0.00	00.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	00.0	0.00	0.00	0.00	0.00	0.00	1.06	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.06
A			1 dy	2 0	3 0	4 0	5 0	0 9	7 0	0 8	0 6	10 0	11 0	12 0	13 0	H	15 0	16 0	17 0	18 0	_	H	_	22 0	_	H	_		H			30 0	Ш	Totals 1
7			1				.,	Ĺ				_			_			_			1	2	7	۲,	. 7	7	7	7	2	2	7	3	3	To

Notes: 1. 2. 3.

NR = No Records, NA = Not Available. Values in italic are substitute for missing data and are based on averaged values Columns I and L include quantities from leak detection system.

Phases I-VI Section 9	acres	5 0	134.4 15	23 0	0 0
Tyne of Cover	along to add.	Open	Intermediate	Final	Not Opened

inches.
100
0
than
less
·S
trace
B,
Column
4.

5. Columns C, D, E, G, H, I, J, K, L, N, P, S-X and Y are quantities from flow meters.

6. Columns M and O measured from staff gages in each pond.




Figure 1. Leachate Levels in Pump Station B and Rainfall for March 2018.

TABLE 3. LEACHATE BALANCE SUMMARY SOUTHEAST COUNTY LANDFILL HILLSBOROUGH COUNTY, FLORIDA YEAR-2018

			Le	Leachate Arriving at LTRF	TRF		Leach	Leachate Leaving LTRF	T.	I	Effluent Disposal		Inflo	Inflow / Outflow For LTRF	TRF
		Condensate	Leachate	Leachate	Leachate		Total Leachate	Leachate	Leachate	Total	Effluent	Effluent	Total Inflow	Total Outflow	Change
	Rainfall	from LFG	from Section 9	from Section 7-8 from Phases I-VI	from Phases I-VI	Compost	Hauled	Dust Control	Treated at	Effluent	Dust Control	Irrigation	to	from	in
		CS-1	Pumped to LTRF	Pumped to LTRF Pumped to LTRF	Pumped to LTRF	Leachate	from LTRF	(Sprayed)	LTRF	Hauled	(Sprayed)		LTRF	LTRF	Storage ³
Month	(in.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)	(gal.)
January	3.63	986	136,192	132,787	2,699,895	0	2,278,282	9,334	728,100	249,302	0	410,330	2,969,860	3,015,716	-45,856
February	0.82	1,707	102,640	20,127	2,194,846	62,685	1,716,430	1,584	518,000	136,771	0	357,793	2,382,005	2,236,014	145,991
March	1.06	4,700	73,738	74,047	2,123,174	23,840	1,495,682	9,695	814,870	311,813	0	336,300	2,299,499	2,320,247	-20,748
April															
May															
June															
July															
August															
September															
October															
November															
December															
YTD Total 5.51	5.51	7,393	312,570	226,961	7,017,915	86,525	5,490,394	20,613	2,060,970	697,886	0	1,104,423	7,651,364	7,571,977	79,387

Note:

1. If the bypass at the effluent pond is ever used to pump effluent back to the LTRF, this table must be modified.

2. Change in storage represents total inflow to LTRF minus total outflow from LTRF.



PUBLIC WORKS

PO Box 1110 Tampa, FL 33601-1110 (813) 272-5912 | Fax: (813) 272-5811

April 12, 2018

Mr. Steve Morgan Solid Waste Section Florida Department of Environmental Protection Southwest District 13051 N. Telecom Pkwy Temple Terrace, Florida 33637 BOARD OF COUNTY COMMISSIONERS

Victor D. Crist

Ken Hagan Al Higginbotham Pat Kemp Lesley "Les" Miller, Ir. Sandra L. Murman Stacy R. White

COUNTY ADMINISTRATOR

Michael S. Merrill
COUNTY ATTORNEY
Chip Fletcher
INTERNAL AUDITOR
Peggy Caskey

CHIEF DEV. & INFRA. SERVICES ADMINISTRATOR

Lucia E. Garsys

RE: Waste Tire Facility Quarterly Report - Permit No. 126787-005-WT/02

Dear Mr. Morgan:

In accordance with Rule 62-711, F.A.C. and Permit No 126787-005-WT/02, the Solid Waste Management Division (SWMD) is submitting the Quarterly Report for the Waste Tire Facility for the period January 1, 2018 through March 31, 2018.

The SWMD staff compiled the information from the site's daily reports for this Quarterly Report.

Should you have any questions or require additional information concerning this submittal, please contact me at (813) 671-7707.

Sincerely,

Larry E. Ruiz

Manager Landfill Operations Solid Waste Management Division Public Works Department

LER/cp Attachments

xc: Ron Cope, EPC

Kimberly Byer, SWMD



Department of Environmental Protection

DEP Form #	‡ <u>62-701.900(21)</u>
Form Title	Waste Tire Processing Facility Quarterly Report
Effective Da	te <u>3/22/00</u>
DEP Applica	ation No(Filled in by DEP)

Waste Tire Processing Facility Quarterly Report

Pursuant to Rule 62-711.530, Florida Administrative Code, the owner or operator of a waste tire processing facility shall submit the following information to the Department quarterly.

uarter covered	by this report	01/01/18 th	ru 03/31/18	(First quarter	begins on Ja	nuary 1 of any	given year)
1. Facility nam	e: Hillsboro	ugh County S	Southeast Lan	dfill Waste T	ire Facility		
2. Facility mail	ing address:	332 N. Falke	nburg Road				
City: Tamp	City: Tampa County: Hillsborough Zip: 33619)	
3. Facility pern	nit number:	126787-005-V	VT/02			· ·	
4. Facility telep	·			110.100			- WALES
5. Authorized			arry E. Ruiz				
6. Affiliation w			resentative - N	Manager Lan	dfill Operatio	ns	
7. Telephone n	,)	-am operation		
8. Activity: R		erent from abt	<u>(</u>				*******
o. Activity. R	Beginning	Received	Processed	Consumed	Removed	Adjustments	Ending
Used Tires	Inventory			00.10411104		Adjustments	Inventory
Other whole	699.33	302.74			-395.32		
Tires Processed tires							
Processing			 				
Waste			ļ			-27.13	
Total	699.33	302.74			-395.32	-27.13	579.62
a. Explain all in	ventory adius	tments -27	.13 tons of ur	processed t	ruck tires		
		cments			. 40.7 (11.00		
List any peri category. Ho		ne or more cat ondition reliev		ntory exceeds	ed the permitt	ed maximum fo	or that
For any exce Attach Addit	ess inventory a tional sheets,	at the end of t if necessary.	he quarter, sta	ate how and v	when this con	dition will be r	elieved.
O. Certification	:	-574 tota		ta kan da	Porting		***************************************
To the best of	of my knowledg	e and belief, I c	ertify the inform	ation provided	in this report is	true, accurate,	and complete.
larva	E. Roiz	pr.	\mathcal{A}	Mu G.	li:	4/	2/18
Print Nar	ne of Authoriz	zed Agent	Siç	gnature of Au	thorized Ager	nt //	Date
		i	Mail complete f	form to			

Mail complete form to the appropriate district office

WASTE TIRE FACILITY QUARTERLY TONNAGE REPORT FIRST QUARTER 2018

		FIRST QUARTER	Beginning Tonnage		
			(Jan. 1, 2018)	699.33	
		Tires Removed by			
Month	Tires Received	Contractor	Tires to SCTS	Tons Adjusted	
Jan. 2018	113.78	25.91		· · · · · · · · · · · · · · · · · · ·	
Beginning Tons	699.33				
	813.11	-25.91	-27.01	-10.92	
			Ending Tonnage	749.27	
		Tires Removed by	T		
Month	Tires Received	Contractor	Tires to SCTS	Tons Adjusted	
Feb. 2018	84.90	68.38		4.44	
Beginning Tons	749.27				
	834.17	-68.38	-115.25	-4.44	
			Ending Tonnage	646.10	
		Tires Removed by			
Month	Tires Received	Contractor	Tires to SCTS	Tons Adjusted	
Mar. 2018	104.06	84.82	73.95	11.77	
Paginning Tons	(46.10				
Beginning Tons	646.10 750.16	04.00	72.05	11.55	
	/30.16	-84.82	-73.95 Ending Tonnage	-11.77 579.62	
2.6	T: 5 . 1	Tires Removed by			
Month	Tires Received	Contractor	Tires to SCTS	Tons Adjusted	
Jan. 2018	113.78	25.91	27.01	10.92	
Feb. 2018	84.90	68.38	115.25	4.44	
Mar. 2018 Sub-Total	104.06	84.82	73.95	11.77	
	302.74	179.11	216.21	27.13	
Beginning Tons	699.33				
TOTAL	1,002.07	-179.11	-216.21	-27.13	
			Ending Tonnage	579.62	