


**COOLANT CAGE
ONLY**





Safety Data Sheet

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

CAT ® ELC (Extended Life Coolant)

Product Use: Antifreeze/Coolant

Product Number(s): 226387

Company Identification

Chevron Products Company

Global Lubricants

6001 Bollinger Canyon Rd.

San Ramon, CA 94583

United States of America

www.chevronlubricants.com

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

Health Emergency

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800)

231-0623 or (510) 231-0623

email : lubemsds@chevron.com

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION: Target organ toxicant (repeated exposure): Category 2. Reproductive toxicant (developmental): Category 2.



Signal Word: Warning

Health Hazards: Suspected of damaging the unborn child.

Target Organs: May cause damage to organs (Kidney) through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use personal protective equipment as required.

Response: Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

HAZARDS NOT OTHERWISE CLASSIFIED: Not Applicable

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Ethylene Glycol	107-21-1	34 - < 80 %weight
Sodium 2-ethylhexanoate	19766-89-3	0.1 - < 3 %weight

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed**IMMEDIATE HEALTH EFFECTS**

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Inhalation: Not expected to be harmful if inhaled. Breathing this material at concentrations above the

recommended exposure limits may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

DELAYED OR OTHER HEALTH EFFECTS:

Reproduction and Birth Defects: Contains material that may cause harm to the unborn child if swallowed based on animal data.

Target Organs: Contains material that may cause damage to the following organ(s) following repeated inhalation at concentrations above the recommended exposure limit: Kidney See Section 11 for additional information. Risk depends on duration and level of exposure.

Indication of any immediate medical attention and special treatment needed Not Applicable

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames. Dry Chemical, CO₂, AFFF Foam or alcohol resistant foam.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Sodium.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

SECTION 7 HANDLING AND STORAGE

General Handling Information: Do not taste or swallow antifreeze or solution. Keep out of the reach of children and animals.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not

breathe vapor or fumes. Wash thoroughly after handling. Keep out of the reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

General Storage Information: Do not store in open or unlabeled containers.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: Natural rubber, Neoprene, Nitrile Rubber, Polyvinyl Chloride (PVC or Vinyl).

Respiratory Protection: Air-Purifying Respirator for Organic Vapors, Dusts and Mists.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Component	Agency	TWA	STEL	Ceiling	Notation
-----------	--------	-----	------	---------	----------

Ethylene Glycol	ACGIH	25 ppm (weight)	50 ppm (weight)	--	Skin A3
Ethylene Glycol	OSHA Z-1	1 mg/m3	--	--	Skin
Sodium 2-ethylhexanoate	Not Applicable	--	--	--	--

Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Red

Physical State: Liquid

Odor: Faint or Mild

Odor Threshold: No data available

pH: 8.10 - 8.50

Vapor Pressure: No data available

Vapor Density (Air = 1): 2.10

Initial Boiling Point: 109°C (228.2°F)

Solubility: Soluble in water.

Freezing Point: -37°C (-34.6°F) (Max)

Melting Point: Not Applicable

Specific Gravity: 1.06 - 1.09

Density: 1.0710 kg/l @ 15°C (59°F) (Min)

Viscosity: No data available

Coefficient of Therm. Expansion / °F: No data available

Evaporation Rate: No data available

Decomposition temperature: No data available

Octanol/Water Partition Coefficient: No data available

FLAMMABLE PROPERTIES:

Flammability (solid, gas): No Data Available

Flashpoint: Not Applicable

Autoignition: No data available

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: Aldehydes (Elevated temperatures), Ketones (Elevated temperatures)

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for similar materials.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate: Not Determined

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Single Exposure: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Repeated Exposure: The hazard evaluation is based on data for components or a similar material.

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains ethylene glycol (EG). The toxicity of EG via inhalation or skin contact is expected to be slight at room temperature. The estimated oral lethal dose is about 100 cc (3.3 oz.) for an adult human. Ethylene glycol is oxidized to oxalic acid which results in the deposition of calcium oxalate crystals mainly in the brain and kidneys. Early signs and symptoms of EG poisoning may resemble those of alcohol intoxication. Later, the victim may experience nausea, vomiting, weakness, abdominal and muscle pain, difficulty in breathing and decreased urine output. When EG was heated above the boiling point of water, vapors formed which reportedly caused unconsciousness, increased lymphocyte count, and a rapid, jerky movement of the eyes in persons chronically exposed. When EG was administered orally to pregnant rats and mice, there was an increase in fetal deaths and birth defects. Some of these effects occurred at doses

that had no toxic effects on the mothers. We are not aware of any reports that EG causes reproductive toxicity in human beings.

2-Ethylhexanoic acid (2-EXA) caused an increase in liver size and enzyme levels when repeatedly administered to rats via the diet. When administered to pregnant rats by gavage or in drinking water, 2-EXA caused teratogenicity (birth defects) and delayed postnatal development of the pups. Additionally, 2-EXA impaired female fertility in rats. Birth defects were seen in the offspring of mice who were administered sodium 2-ethylhexanoate via intraperitoneal injection during pregnancy.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from products of a similar structure and composition.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material.

The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Octanol/Water Partition Coefficient: No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: PROPRIETARY ANTIFREEZE PREPARATION IN NON-BULK PACKAGING;
NOT REGULATED FOR TRANSPORT UNDER 49 CFR

Additional Information: Bulk shipments containing a reportable quantity (RQ, 5000 pounds or more) of ethylene glycol in a single packaging are transported as hazardous material. The shipping description is: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ETHYLENE GLYCOL CONTAINS BITTERANT), 9, III, RQ (ETHYLENE GLYCOL)

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: Anti-freeze Preparations, Proprietary; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:
Not applicable

SECTION 15 REGULATORY INFORMATION

EPCRA 311/312 CATEGORIES:	1. Immediate (Acute) Health Effects:	YES
	2. Delayed (Chronic) Health Effects:	YES
	3. Fire Hazard:	NO
	4. Sudden Release of Pressure Hazard:	NO
	5. Reactivity Hazard:	NO

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1	03=EPCRA 313
01-2A=IARC Group 2A	04=CA Proposition 65
01-2B=IARC Group 2B	05=MA RTK
02=NTP Carcinogen	06=NJ RTK
	07=PA RTK

The following components of this material are found on the regulatory lists indicated.

Ethylene Glycol 01-2B, 02, 03, 04, 05, 06, 07

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: Refer to components listed in Section 3.

SECTION 16 OTHER INFORMATION

NFPA RATINGS: Health: 2 Flammability: 1 Reactivity: 0

HMIS RATINGS: Health: 2* Flammability: 1 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

REVISION STATEMENT: SECTION 04 - Immediate Health Effects - Ingestion information was deleted.
SECTION 05 - Fire Fighters Protection Measures information was modified.
SECTION 05 - Special hazards arising from the substance or mixture information was added.
SECTION 08 - Engineering Control Measures information was modified.
SECTION 08 - Occupational Exposure Limit Table information was modified.
SECTION 08 - Respiratory Protection information was deleted.
SECTION 15 - Regulatory Information information was modified.

Revision Date: April 04, 2018

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
GHS - Globally Harmonized System	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code
API - American Petroleum Institute	SDS - Safety Data Sheet
HMIS - Hazardous Materials Information System	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration
NCEL - New Chemical Exposure Limit	EPA - Environmental Protection Agency
SCBA - Self-Contained Breathing Apparatus	

Prepared according to the 29 CFR 1910.1200 (2012) by Chevron Energy Technology Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with

which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.



Cliff Berry, Incorporated
Environmental Services
P.O. Box 13079 Ft. Lauderdale, FL 33316
1 800 899 7745

580022

IN CASE OF EMERGENCY
CONTACT 3E@ 800-451-8346

DISPATCH TICKET

Manifest Doc #: 390781

1. Generator's US EPA ID No.: FLCESQG

PO#: P1P052523YM

2. Generator Site:

PANTROPIC POWER MIAMI
8205 NW 58TH STREET
MIAMI FL33166

3. Bill To:

PANTROPIC POWER MIAMI
8205 NW 58TH STREET
MIAMI FL, 33166
Contact Name: EXT 3169,
Contact Phone #: 305-592-4944

4. Generator Phone: 305-592-4944

Generator Contact: EXT 3169

5. Transporter Name/Phone: 954-763-3390

Cliff Berry (DANIA)

EPA ID#: FLR000083071

6. Designated Facility/Phone: 800-899-7745

MIAMI BULK DRUM
3033 NW NORTH RIVER DRIVE
MIAMI FL, 33142

EPA ID#: FLD058560699

7. Description of Service/Instructions:

PLEASE SWAP OUT 7 FILTER DRUM TO BE BILLED \$50 PER DRUM
PLEASE SWAP OUT 1 DRUM OF RAGS TO BE BILLED \$150 PER DRUM

Department Location: FTL USED OIL Driver/Tech: Tony/0.09 Truck: SV 171
Scheduled Date of Work: _____ Scheduled Time: _____ Method of Payment: NET30

8. Work Site Remarks:

Time Left Yard (Start): _____ Time Arrived On Site: _____ Date: _____
Time Left Site: 2:10 Time Arrived At Yard (Stop): 3:30 Date: 6-1-23

A I M	9. PROPER SHIPPING NAME/DESCRIPTION	HAZ CLASS	I.D. #	PKG. GP	CONTAINERS		TOTAL QTY	UNIT Wt/Vol
					No.	TYPE		
a.	"Non-Hazardous Solid, (oil filters)" 390781				10	DM	550	G
b.	"Non-Hazardous Solid, (Pads and Rags)" 390784				1	DM	55	G

10. SPECIAL HANDLING INSTRUCTIONS:

incinerate waste to energy

11. CERTIFICATION: This is to certify that the above named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulation of the Department of Transportation. I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.

TERMS & CONDITIONS: Customer agrees that work has been performed satisfactorily. Payment is due upon completion of services. Where CBI extends credit, a charge of 1-1/2% per month, 18% per annum, will be added to balances unpaid 30 days after date of invoice. Collection costs and/or reasonable attorney's fees will be due in the event any collection process becomes necessary. This is not an invoice, but merely an estimate of charges. Applicable taxes, tariffs and fuel surcharges will be forwarded on invoice.

Printed/Typed Name Walter Lewis Signature [Signature] Month 6 Day 1 Year 23

12. Transporter Acknowledgement of Receipt of Materials

Printed/Typed Name Erin Wallace Signature [Signature] Month 6 Day 1 Year 23

13. Facility Owner or Operator: Certification of receipt of materials covered by this manifest.

Printed/Typed Name _____ Signature _____ Month _____ Day _____ Year _____



Cliff Berry, Incorporated
Environmental Services
P.O. Box 13079 Ft. Lauderdale, FL 33316
1 800 899 7745

580886

IN CASE OF EMERGENCY
CONTACT 3E@ 800-451-8346

DISPATCH TICKET

Manifest Doc #: 392693

PO#:

1. Generator's US EPA ID No.: FLCESQG

2. Generator Site:

PANTROPIC POWER MIAMI
8205 NW 58TH STREET
MIAMI FL33166

3. Bill To:

PANTROPIC POWER MIAMI
8205 NW 58TH STREET
MIAMI FL, 33166
Contact Name: EXT 3169,
Contact Phone #: 305-592-4944

4. Generator Phone: 305-592-4944

Generator Contact: EXT 3169

5. Transporter Name/Phone: 954-763-3390

Cliff Berry (DANIA)

EPA ID#: FLR000083071

6. Designated Facility/Phone: 800 899-7745

MIAMI PLANT
3033 NW NORTH RIVER DRIVE
MIAMI FL, 33142

EPA ID#: FLD058560699

7. Description of Service/Instructions:

PLEASE SERVICE USED OIL @ N/C

Department Location: FTL USED OIL Driver/Tech: Danishy Truck: BT17
Scheduled Date of Work: 06/12/2023 Scheduled Time: _____ Method of Payment: NET30

8. Work Site Remarks:

Time Left Yard (Start): 7:15 Time Arrived On Site: 8:00 Date: 06/12/23
Time Left Site: _____ Time Arrived At Yard (Stop): _____ Date: 06/12/23

A I M	9. PROPER SHIPPING NAME/DESCRIPTION	HAZ CLASS	I.D. #	PKG. GP	CONTAINERS		TOTAL QTY	UNIT Wt/Vol
					No.	TYPE		
a.	"Non-Hazardous Liquid, (Petroleum destined for recycling Halogens <1000 PPM)" 392693				1	TT	430	G
	Water						275	BL

10. SPECIAL HANDLING INSTRUCTIONS:

Halogens are <1000ppm

11. CERTIFICATION: This is to certify that the above named materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation according to the applicable regulation of the Department of Transportation. I certify the materials described above on this manifest are not subject to federal regulations for reporting proper disposal of Hazardous Waste.
TERMS & CONDITIONS: Customer agrees that work has been performed satisfactorily. Payment is due upon completion of services. Where CBI extends credit, a charge of 1-1/2% per month, 18% per annum, will be added to balances unpaid 30 days after date of invoice. Collection costs and/or reasonable attorney's fees will be due in the event any collection process becomes necessary. This is not an invoice, but merely an estimate of charges. Applicable taxes, tariffs and fuel surcharges will be forwarded on invoice.

Printed/Typed Name	Signature	Month	Day	Year
<u>John H. D.</u>	<u>[Signature]</u>	<u>06</u>	<u>12</u>	<u>23</u>
12. Transporter Acknowledgement of Receipt of Materials	Signature	Month	Day	Year
Printed/Typed Name	<u>[Signature]</u>	<u>06</u>	<u>12</u>	<u>23</u>
13. Facility Owner or Operator: Certification of receipt of materials covered by this manifest.	Signature	Month	Day	Year
Printed/Typed Name				

Heritage - Crystal Clean, LLC

877-938-7948

www.crystal-clean.com



WORK ORDER NBR: 00-00N0GMM

****THIS IS NOT AN INVOICE****

SERVICE REQUEST NBR: 463953

CUSTOMER ID NBR: 354832

COMMENTS:

EMERGENCY NBR: 800-424-9300 (CHEMTREC CON10430)

(for accidents/spills)

DATE: 6/13/2023 10:38:14 AM

CRYSTAL CLEAN REPRESENTATIVE: JASON GIPE

CUSTOMER/SHIPPER:

PANTROPIC POWER INC

8205 NW 58TH ST

MIAMI, FL 33166

CONTACT NAME : HECTOR AEDO (305)592-4944

GEN. STATUS: SQG

FEDERAL EPA ID NBR: FLD982091787

STATE EPA ID NBR:

COMMENTS:

DESTINATION:

HERITAGE-CRYSTAL CLEAN, LLC

1300 NE 48TH STREET

POMPANO BEACH , FL 33064

Phone Number: 877-938-7948

CARRIER: HERITAGE-CRYSTAL CLEAN, LLC

Phone Number: (847)836-5670

EPA ID NBR: ILR000130062

TRANSPORTER STATE ID:

BILL OF LADING

(See Manifest 006904280)

NON-DOT/RCRA REGULATED, (ABSORBENT/DEBRIS,
OIL)

Container Type: DF (55G)

Container Count:1

Total Units:50 GAL

DFTATI S



1000010008000021472560

1160 NEW CUBIC YARD BOX 1 289.00 289.00 CHARGE
Interval: One Time

174 ENERGY SURCHARGE 1 0.00 0.00 CHARGE

196 MANIFEST FEE 1 25.00 25.00 CHARGE

1017F CYB SUP FUEL LOOSE P 1 2945.00 2945.00 CHARGE

Interval: 12 Week

Ws Nbr:410955-3-1017 DIESE

Container Type:TP (One Tote)

Container Qty:1 Units Per Container:75 LBS



1000010008000021472556

Net Invoice: \$ 3596.00

Tax: \$ 20.23

Total Invoice: \$3616.23

This is to certify that the above-named materials are properly classified, described, packaged, marked, and labeled and are in proper condition for transport according to the applicable regulations of the Department of Transportation, as required. I also certify that neither hazardous waste, nor PCB's have been mixed with the used oil/or parts cleaner solvent (if applicable).

Customer also hereby verifies that the above services were performed and that said services and the charges therefor are hereby accepted. Customer also hereby reaffirms the accuracy and completeness of all information contained in this work order and all documentation previously submitted to HCC. This work order is deemed part of the service agreement between Heritage-Crystal Clean, LLC and the certifications contained therein concerning the materials to be handled and the services to be provided are incorporated herein by reference and deemed part hereof and said certifications are deemed remote for the services covered by this work order.

CUSTOMER SIGNATURE