



HARTMAN & ASSOCIATES, INC.

engineers, hydrogeologists, surveyors & management consultants

201 EAST PINE STREET -- SUITE 1000 -- ORLANDO, FL 32801
 TELEPHONE (407) 839-3955 -- FAX (407) 481-8447

FAX

Job Number: 99.0331.019

Date: 11/19/04

No. of pages incl. cover page: 2

To: John Morris, P.G.

FDEP

Phone: (813) 744-6100

Fax: (813) 744-6125

cc: _____

Re: Enterprise Groundwater Results

From: Jennifer L. Deal, P.E.

Hartman & Associates, Inc.

Phone: (407) 839-3955 ext. 153

Fax: (407) 839-2066

REMARKS: Urgent For your review As Requested Please comment

John,

Following is a summary of the groundwater exceedences for the Enterprise Recycling & Disposal Facility for the October 2004 semi-annual groundwater sampling event. The results are generally consistent with the previous semi-annual event. No re-sampling will be performed. We will be sending the full semi-annual report on Monday, November 22, via UPS, so you should receive the report on Tuesday, November 23. Please give me a call if you have any questions regarding this data. Thank you.

Jennifer

The information contained in this facsimile transmission may be legally privileged and is intended for the use of the individual(s) or entity(ies) named above. If you are not the intended recipient, you are hereby notified that any use dissemination, distribution or copying of this facsimile or its information is strictly prohibited. If you have received this facsimile in error, please immediately notify the sender by telephone or facsimile using the above referenced number to arrange for the return of the original documents.

TABLE 2
GROUNDWATER EXCEEDENCES
ENTERPRISE RECYCLING AND DISPOSAL FACILITY
DADE CITY, FLORIDA
October 2004

Monitor Well	Parameter	Result	MCL/MC	Units
MW-1	pH	5.96	6.5-8.5	STD
	Iron	3.7	0.3	mg/L
MW-1B	Dissolved Oxygen	68.4	20	%
MW-5A	pH	5.18	6.5-8.5	STD
	Dissolved Oxygen	62.6	20	%
MW-5B	Dissolved Oxygen	36.5	20	%
MW-6	pH	4.71	6.5-8.5	STD
	Iron	0.77	0.3	mg/L
MW-7A	pH	4.83	6.5-8.5	STD
MW-7B	pH	11.55	6.5-8.5	STD
MW-8	pH	5.24	6.5-8.5	STD
	Dissolved Oxygen	64.5	20	%
MCL - Maximum Contaminant Limit per FAC 62-550 and FAC 62-520				
MC - Groundwater Quality Minimum Criteria, per FAC 62-777				