

**SUMTER COUNTY
(CLOSED) LANDFILL
QUARTERLY GROUNDWATER
MONITORING REPORT
Quarter II (May) 2010**

Prepared for:

**SUMTER COUNTY
SOLID WASTE DEPARTMENT
SUMTER COUNTY, FLORIDA**

Prepared by:

**THE COLINAS GROUP, INC.
509 N. Virginia Avenue
Winter Park, Florida 32789**

July 2010

THE COLINAS GROUP, INC.
HYDROGEOLOGISTS & ENGINEERS

July 7, 2010

Mr. John Morris, P.G.
Florida Department of Environmental Protection
13051 N. Telecom Parkway
Temple Terrace, Florida 33637

Subj: **Quarter II 2010 Groundwater Monitoring Report
Sumter County Closed Class I Landfill
Sumter County, Florida
FDEP Permit No. 22926-003-SF**

Dear Mr. Morris:

On behalf of Sumter County Board of County Commissioners, The Colinas Group, Inc. (TCG) herewith submits one (1) copy of the report prepared by TCG entitled:

**Sumter County (Closed) Landfill Quarterly Groundwater Monitoring Report,
Quarter II (May) 2010**

The report was prepared and is submitted in satisfaction of part of the requirements of the Sumter County Closed Landfill Long-Term Care Permit. If you have any questions concerning the contents of the report please do not hesitate to contact me at your convenience.

Very truly yours,
THE COLINAS GROUP, INC.

7/13/10
Richard L. Potts, Jr., P.G.
Principal Consultant
Fl. P. No. 13

cc: Ms. Denise Warnock (Sumter County)
Mr. Jimmy Wise (Sumter County)

**SUMTER COUNTY (CLOSED) LANDFILL
GROUNDWATER MONITORING REPORT,
SUMTER COUNTY, FLORIDA
Quarter II (May) 2010**

TABLE OF CONTENTS

EXECUTIVE SUMMARY

INTRODUCTION
SAMPLING EVENT
RESULTS
SUMMARY

Table I - Field Parameter Results Summary
Table II - Summary of Groundwater Levels
Table III - Summary of Laboratory Results

ATTACHMENTS:

1. Quarter II (May) 2010 Groundwater Contour Map
2. Laboratory Analytical Report
3. Field Data and Testing Logs
4. Chain-of-Custody Forms
5. Laboratory/Field Quality Control Reports
6. FDEP ADaPT/pdf Disc - (In Pocket)

**Sumter County (Closed) Landfill
Quarterly Groundwater Monitoring Report
Quarter II (May) 2010**

INTRODUCTION

The Colinas Group, Inc. (TCG) has reviewed the groundwater monitoring well sampling and analytical results for the Quarter II 2010 sampling event at the Sumter County (Closed) Landfill near Lake Panasoffkee in Sumter County. The sampling event was completed in accordance with the quarterly water quality monitoring and reporting requirements of the closed landfill Long-Term Care Permit #22926-003-SF.

The Groundwater Monitoring Plan for the closed landfill was amended in 2004 to replace three (3) existing monitoring wells deemed unsuitably located with respect to closed solid waste disposal areas. Existing wells MW-1, MW-7 and MW-9 were replaced by installation of new wells MW-11, MW-10 and MW-9A, respectively. The existing wells continue to be used as water level measuring points (piezometers).

New monitoring wells MW-4A and MW-4B, installed as part of a Preliminary Contamination Assessment completed at the landfill in January 2006, were added by the Florida Department of Environmental Protection (FDEP) to the facility groundwater monitoring network in May 2006. Groundwater sample analytical results for these new wells are included in this report. The current array of groundwater monitoring wells and piezometers at the facility is shown on Figure 1.

In accordance with Specific Condition 16d of the facility Long-Term Care Permit, sampling and analytical chemical parameters for this sampling event included the normal list of quarterly monitoring parameters. The Long-Term Care Permit requires an expanded parameter list, to include 40 CFR Appendix II parameters, during Quarter IV of each year.

SAMPLING EVENT

The Quarter II 2010 sampling event at the Sumter County Landfill occurred on May 11 and 12, 2010. Sampling was performed by TCG personnel in accordance with the FDEP Standard Operating Procedures (SOP) for Field Activities. Water samples collected from the facility groundwater monitoring wells were tested for the required field parameters. Monitoring wells were purged and the groundwater discharge allowed to stabilize prior to sample collection. The results of field testing were recorded as part of the Field Reports (Attachment 3) and are listed in Table I. All samples were preserved and stored as required prior to shipment to the analytical laboratory.

Laboratory analytical services were provided by Environmental Conservation Laboratories, Inc. (ENCO) in accordance with the laboratory's NELAP and FDHRS Certification No. E83182. The original analytical reports prepared by ENCO are presented in Attachment 2 to this report.

Water table depth measurements in each facility groundwater monitoring well and piezometer were recorded on May 12, 2010. These measurements were used to develop the Groundwater Contour Map shown on Figure 1 (Attachment 1) for the uppermost receiving groundwater aquifer beneath the site. Depth to water table measurements and corresponding groundwater elevations are listed in Table II.

RESULTS

Field Tested Parameters

Results of field testing completed at groundwater monitoring wells for the May 2010 sampling event are summarized in Table I. Field tests were completed by TCG sampling personnel in strict accordance with the FDEP SOP requirements.

pH

The field testing results indicate pH of groundwater in the uppermost aquifer was within the FDEP secondary standard (6.5 - 8.5 pH units) at eight (8) of the nine (9) groundwater monitoring wells sampled. The nearly neutral to slightly basic pH values measured are consistent across the landfill property and appear normal considering the monitoring well screen intervals at and near the top of carbonate rocks and sediments. One well (**MW-4B**) produced water with a pH above the upper FDEP range at 8.95 pH units. This well has consistently produced pH values above 8.5 since sampling of the well began in Quarter II of 2006.

Fluid Temperature

Temperature of each water sample was measured in the field immediately following discharge into the flow cell used to accept flow from the purging pump. Temperature measurements of groundwater from the monitoring wells ranged from a low of 24.70 C at well **MW-8** to 27.36 C at **MW-4B**.

Dissolved Oxygen

Dissolved oxygen (DO) exceeded the FDEP sampling guidance level of 20% saturation at four (4) of the nine (9) monitoring wells sampled, including the facility background monitoring well **MW-6A**. These wells consistently produce groundwater with elevated DO concentrations.

Specific Conductance

Specific conductance of groundwater samples collected during this sampling event are included in Table I. Specific conductance values varied through a relatively narrow range of 142 umhos/cm to 898 umhos/cm. Lowest specific conductance was measured at well **MW-4B**. Highest specific conductance was measured at detection well **MW-9A**.

Turbidity

The FDEP recommends attainment of turbidity values less than 10 to 20 NTUs in groundwater samples obtained from monitoring wells. As shown in Table I, groundwater samples collected at all wells had measured turbidity values less than 20 NTUs. Fluid turbidity exceeded 10 NTUs at three (3) wells.

Regulatory Exceedances

A summary of groundwater laboratory analytical results that were either equal to or exceeded the regulatory level for the particular parameter in the May 2010 sample set is presented in Table III. As shown, six (6) analytical parameters were reported for certain monitoring wells at concentrations that exceed applicable regulatory levels. Exceeded parameters were aluminum, iron, manganese, nitrate nitrogen, radionucleides and total dissolved solids.

Aluminum

Aluminum was detected at concentrations above the Florida Secondary Drinking Water Standards (FSDWS) MCL (200 ug/l) in samples from three (3) monitoring wells: **MW-4B** (312 ug/l), **MW-9A** (217 ug/l) and **MW-11** (388 ug/l). Aluminum was detected by the laboratory at concentrations below the MCL at three other monitoring wells.

Iron

Dissolved iron was detected in two (2) monitoring wells at concentrations above the FSDWS MCL of 300 ug/l. Iron was reported at 390 ug/l at well **MW-9A** and 666 ug/l at **MW-10**. Iron was detected at concentrations less than 300 ug/l at four other wells, and was below the laboratory method detection limit at the remaining monitoring wells.

Manganese

Manganese was reported above the FSDWS MCL of 50 ug/l in monitoring well **MW-9A** at 79.2 ug/l. Manganese was detected in four other wells at concentrations below 50 ug/l.

Nitrate Nitrogen

Nitrate was reported slightly above the 10 mg/l FPDWS MCL at monitoring well **MW-4A** at 12 mg/l. Elevated nitrate levels less than the MCL are noted in the facility background monitoring well **MW-6A** at 6.2 mg/l and in remaining monitoring wells at lesser values.

Radionucleides

The sum of gross alpha plus radium 226/228 (corrected for the negative error range) reported for **MW-11** (18.50 pCi/l) exceeded the drinking water standard MCL of 15 pCi/l.

Total dissolved Solids (TDS)

TDS is reported at **MW-9A** just above the 500 mg/l MCL at 520 mg/l. TDS in other wells ranged from 90 mg/l to 420 mg/l.

No other exceedance of a parameter regulatory concentration level was reported in the laboratory analytical results for samples from groundwater monitoring wells at the Sumter County Closed Landfill.

Other Detected Parameters

Cadmium was detected in groundwater samples from three monitoring wells (**MW-9A**, **MW-10** and **MW-11**) at concentrations less than the FPDWS MCL. Cadmium was reported below the laboratory detection limit in remaining monitoring wells.

Chromium was detected at three wells (**MW-6A**, **-10** and **-11**), including the facility background well, at low concentrations below the MCL for this constituent.

Mercury was detected at 0.478 ug/l in monitoring well **MW-9A** and at 0.0719 ug/l in **MW-11**, well below the FPDWS MCL of 2 ug/l, and was less than the laboratory method detection limit in samples from remaining wells.

Silver was detected at trace concentrations in three wells, ranging from 0.223 ug/l to 0.257 ug/l. The MCL for silver is 100 ug/l.

Sodium and **chloride** concentrations reported for seven (7) of the nine (9) monitoring wells appear consistent between individual wells and typical for natural shallow groundwaters in Florida. Although significantly below respective regulatory MCLs, sodium/chloride concentrations at monitoring wells **MW-4** and **MW-4A** are somewhat elevated above concentrations measured in samples from other monitoring wells.

Thallium was reported at low concentrations in three wells: **MW-4** (0.331 ug/l), **MW-4A** (0.401 ug/l) and **MW-9A** (0.303 ug/l). The FPDWS MCL for thallium is 2 ug/l.

SUMMARY

Chemical characteristics of groundwater monitored at the Sumter County Landfill are reported for the Quarter II 2010 sampling event. Exceedances of specific constituent regulatory levels and MCLs are reported at specific monitoring wells for **aluminum, iron, manganese, nitrate nitrogen, radionuclides** and **TDS**.

Elevated **dissolved oxygen (DO)** levels were measured in four of the nine groundwater monitoring wells, including the facility background monitoring well. Prior sampling data indicate that elevated DO levels occur frequently and in many of the same monitoring wells, suggesting that high DO in groundwater at these locations is likely a natural condition.

Aluminum was detected in samples from three wells (**MW-4B, MW-9A** and **MW-11**) at concentrations above the FSDWS MCL of 200 ug/l. Aluminum was also detected below the MCL in four other monitoring wells, including the facility background well **MW-6A**. The most likely source of aluminum measured in groundwater samples is natural deposits of aluminum-silicate clay minerals within and near the groundwater monitoring zone tapped by wells at the landfill.

Gross alpha radioactivity, including the sum of radium 226/228, exceeded the 15 pCi/l MCL in a groundwater sample from well **MW-11**, reported at a range of 18.5 - 23.7 pCi/l. Gross alpha individually is reported to range from 15.2 - 18.6 pCi/l in the groundwater sample.

Manganese was reported above the FSDWS MCL in the sample from **MW-9A**, one of the more recently-constructed monitoring wells. **Iron** was detected slightly above the FSDWS MCL in wells **MW-9A** and **MW-10**. Both of these elements occur naturally in sediments and carbonate rocks penetrated by the monitoring wells.

Nitrate nitrogen dissolved in groundwater was reported above the FPDWS MCL of 10 mg/l at well **MW-4A** (12 mg/l). As shown on the groundwater contour map for the May 2010 sampling event (Figure 1) well **MW-4A** was upgradient of well **MW-4** and the closed landfill waste disposal areas. Elevated concentrations of nitrate nitrogen were also reported at background well **MW-6A** and at all but one of the remaining monitoring wells at levels considered well above naturally-occurring nitrate concentrations typically found in groundwater in Florida.

* * * * *

TABLE I
FIELD PARAMETER RESULTS SUMMARY,
SUMTER COUNTY (CLOSED) LANDFILL
SUMTER COUNTY, FLORIDA
Quarter II (May) 2010

Sampling Point	Temp. (C)	Dissolved Oxygen (mg/l)	pH	Specific Conductance (umhos/cm)	Turbidity (NTU)
MW-2	26.51	3.92	7.09	236	3.82
MW-4	25.92	0.71	7.25	602	7.10
MW-4A	26.98	0.23	7.37	682	13.3
MW-4B	27.36	5.40	8.95	142	1.38
MW-6A	25.99	5.32	7.79	261	13.3
MW-8	24.70	3.27	7.37	411	5.01
MW-9A	25.76	0.05	6.80	898	6.33
MW-10	25.20	1.11	7.21	570	9.47
MW-11	25.59	1.31	6.73	437	17.8

Notes: **Bold** lettering indicates: Exceedance of FDEP 20% saturation dissolved oxygen limit
Exceedance of pH range (6.5 - 8.5)
Exceedance of FDEP-recommended turbidity (20 NTU)

TABLE II
QUARTER II 2010
SUMMARY OF GROUNDWATER LEVELS
SUMTER COUNTY (CLOSED) LANDFILL
SUMTER COUNTY, FLORIDA
(May 12, 2010)


Well No.	Measuring Point Elevation (ft. +NGVD)	Depth to Water (ft. - MP)	Groundwater Elevation (ft. +NGVD)
MW-1	70.17	24.73	45.44
MW-2	69.13	23.38	45.75
MW-2A	72.11	26.46	45.65
MW-4	70.36	24.84	45.52
MW-4A	75.73	30.05	45.68
MW-4B	73.83	28.12	45.71
MW-6A	77.54	31.55	45.99
MW-7	73.14	27.41	45.73
MW-8	69.26	22.25	47.01
MW-9	71.95	26.15	45.80
MW-9A	74.26	29.47	44.79
MW-10	68.28	22.41	45.87
MW-11	70.21	24.62	45.59

Notes: 1. Measuring Point is top of PVC well casing.
2. Water levels recorded on May 12, 2010.

**TABLE III
SUMMARY OF LABORATORY RESULTS
SUMTER COUNTY (CLOSED) LANDFILL, QUARTER II (MAY) 2010**

Parameter	units	MW-2	MW-4	MW-4A	MW-4B	MW-6A	MW-8	MW-9A	MW-10	MW-11	MCL
Ammonia	mg/l	BDL	BDL	BDL	BDL	BDL	BDL	0.29	BDL	BDL	2.8
Aluminum	ug/l	BDL	102	124	312	131	BDL	217	170	388	200
Antimony	ug/l	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	6
Cadmium	ug/l	BDL	BDL	BDL	BDL	BDL	BDL	2.34	1.15	3.63	5
Chloride	mg/l	5.7	26	30	3.9	9.1	12	22	8.1	3.5	250
Chromium	ug/l	BDL	BDL	BDL	BDL	7.38	BDL	BDL	11.6	4.84	100
Fluoride	mg/l	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	0.14	4
Gross Alpha	pCi/l	<1.0 ± 0.7	6.3 ± 1.3	<0.6 ± 0.4	1.7 ± 0.8	<1.4 ± 1.0	<1.4 ± 1.2	6.9 ± 1.8	6.9 ± 1.4	16.9 ± 1.7	15
Iron	ug/l	BDL	47.7	BDL	BDL	39.0	49.7	390	666	129	300
Lead	ug/l	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	BDL	15
Manganese	ug/l	BDL	2.97	3.65	BDL	BDL	BDL	79.2	26.0	4.61	50
Mercury	ug/l	BDL	BDL	BDL	BDL	BDL	BDL	0.478	BDL	0.0719	2
Nitrate, as N	mg/l	2.1	7.9	12	4.5	6.2	2.5	0.55	2.2	4.2	10
Radium 226	pCi/l	0.3 ± 0.1	1.2 ± 0.2	0.4 ± 0.1	1.0 ± 0.2	0.2 ± 0.1	0.5 ± 0.2	2.1 ± 0.3	1.6 ± 0.3	3.1 ± 0.3	---
Radium 228	pCi/l	<0.9 ± 0.6	1.6 ± 0.7	1.3 ± 0.6	<0.9 ± 0.6	<0.8 ± 0.5	0.7 ± 0.5	1.2 ± 0.6	<0.8 ± 0.5	1.1 ± 0.6	---
Silver	ug/l	BDL	0.232	0.257	BDL	BDL	BDL	BDL	BDL	0.223	100
Sodium	mg/l	4.10	47.1	26.9	10.1	3.15	6.62	18.4	7.58	9.15	160
TDS	mg/l	150	360	420	90	200	250	520	340	290	500
Thallium	ug/l	BDL	0.331	0.401	BDL	BDL	BDL	0.303	BDL	BDL	2

Notes: 1). BDL means below laboratory method detection limit 2). **Bold lettering** indicates result exceeds MCL/Guidance concentration



The Colinas Group, Inc. 509 N. Virginia Avenue Winter Park, Florida 32789	PROJ. NO.: P-421	GROUNDWATER CONTOUR MAP QUARTER 2 (MAY) 2010 SUMTER COUNTY LANDFILL	FIGURE 1
	DATE: MAY 2010		
	SCALE: 1" = 200'		

FIELD LOG
Well Water Levels

PROJ # P. 431
 PROJECT NAME: Sumter Co. Landfill
 PROJECT LOCATION: Sumterville IFC

NAME: Dale Clayton
 DATE: 5/12/10

TIME	COMMENTS
Well	WL
#	(pt. 6 to c)
MW-1	24.73'
MW-2	23.38'
MW-2A	26.46'
MW-4	24.84'
MW-4A	30.05'
MW-4B	28.12'
MW-6A	31.55'
MW-7	27.41'
MW-8	22.25'
MW-9	26.15'
MW-9A	29.42'
MW-10	22.41'
MW-11	24.62'

1.4

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-2	SAMPLE ID: MW-2
DATE: 5/12/10	

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH 23.38 TO WATER (feet):	PURGE PUMP TYPE OR BAILER: ESP APP							
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY (only fill out if applicable) Well Vol = (31.92' feet - 23.38' feet) X .16 gallons/foot = 1.3664 gallons											
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable) 1 Equip Vol = .02 gallons + (.006 gallons/foot X 28' feet) + .125 gallons = .315 gallons											
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~25	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~28	PURGING INITIATED AT: 1100	PURGING ENDED AT: 1118	TOTAL VOLUME PURGED (gallons): 2.06							
TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1114	1.82	1.82	.06	23.43	7.10	26.45	.235	3.91	6.80	Clear	None
1116	.12	1.94	.06	23.43	7.09	26.49	.235	3.89	5.63	Clear	None
1118	.12	2.06	.06	23.43	7.09	26.51	.236	3.92	3.82	Clear	None
No Sheen											
WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88 TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016											

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.			SAMPLER(S) SIGNATURES: 			SAMPLING INITIATED AT: 1120		SAMPLING ENDED AT: 1135			
PUMP OR TUBING DEPTH IN WELL (feet): ~28			SAMPLE PUMP FLOW RATE (mL per minute): < 250 mL			TUBING MATERIAL CODE: PE					
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N			FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N Filtration Equipment Type: _____			FILTER SIZE: _____ µm					
DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N											
SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION				INTENDED ANALYSIS AND/OR METHOD		SAMPLING EQUIPMENT CODE	
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH					
MW-2	2	PE	1 Ltr	HN03	None	—	GrossAlpha, RA226RA228		ESP APP		
"	1	PE	250 mL	H2S04	None	—	Total Ammonia		ESP APP		
"	1	PE	250 mL	HN03	None	—	Metals: Al, Fe, Mn, Hg, Ni, Chloride, Fluoride, Nitrate, TDS		ESP APP		
"	1	PE	500 mL	None	None	—			ESP APP		

REMARKS:
 1100: Set dedicated 1/4" PE tubing @ ~25' stoc and ~~begin~~ began purging @ .2 gpm with a PP.
 1105: WL @ 23.54' @ .2 gpm, GW is clear. DO is high @ 4.16 mg/L.
 1107: DO is still high @ 4.10 mg/L. Reduced flow to .06 gpm. Lowered tubing to ~28' stoc.
 1112: WL @ 23.43' @ .06 gpm, drawdown is stable. GW is clear. DO has stabilized around 3.80 mg/L. Will use optional stabilization criteria for DO.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
 2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailer; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
 EQUIPMENT CODES: RFPF = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-4	SAMPLE ID: MW-4 DATE: 5/12/10

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL	STATIC DEPTH 24.84	PURGE PUMP TYPE OR BAILER: ESP
DIAMETER (inches):	DIAMETER (inches):	DEPTH: feet to feet	TO WATER (feet):	
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY only fill out if applicable				
= (36.35' feet - feet) X gallons/foot = gallons				
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable)				
1 Equip Vol = .02 gallons + (.006 gallons/foot X 36 feet) + .125 gallons = 0.375 gallons				
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~31'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~31'	PURGING INITIATED AT: 0905	PURGING ENDED AT: 0921	TOTAL VOLUME PURGED (gallons): 4.80

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
0917	3.60	3.60	.3	25.25	7.29	25.92	1.596	1.71	12.3	Clear	None
0919	.60	4.20	.3	25.25	7.27	25.93	1.600	1.71	8.43	Clear	None
0921	.60	4.80	.3	25.25	7.25	25.92	1.602	1.71	7.10	Clear	None
No screen											

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.			SAMPLER(S) SIGNATURES: <i>[Signature]</i>			SAMPLING INITIATED AT: 0922		SAMPLING ENDED AT: 0935			
PUMP OR TUBING DEPTH IN WELL (feet): ~31'			SAMPLE PUMP FLOW RATE (mL per minute): VOC's < 100 mL < 250 mL			TUBING MATERIAL CODE: PE					
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N			FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N FILTER SIZE: _____ µm			DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N					
SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION				INTENDED ANALYSIS AND/OR METHOD		SAMPLING EQUIPMENT CODE	
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH					
MW-4	2	PE	1 Ltr	HN03	None	---	GrossAlpha, RA226RA228		ESP		
"	1	PE	250 mL	H2S04	None	---	Ammonia		ESP		
"	1	PE	250 mL	HN03	None	---	Metals - Al, Fe, Mn, Hg, Ni		ESP		
"	1	PE	500 mL	None	None	---	Chloride, Fluoride, Nitrate, TDS		ESP		

REMARKS:

0905: Inserted SS ESP and dedicated 3/8" PE tubing @ to ~ 31' btoe and began purging @ .3 gpm.

0910: WL 25.21 @ .3 gpm, GW is turbid. Will purge until clear.

0915: WL 25.25 @ .3 gpm drawdown is stable. GW is clear.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
EQUIPMENT CODES: RFPF = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.

130
5:00

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-4A	SAMPLE ID: MW-4A DATE: 5/11/10

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH 30.00 TO WATER (feet):	PURGE PUMP TYPE OR BAILER: ESP
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY (only fill out if applicable)				
= (45.23' feet - feet) X gallons/foot = gallons				
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME $\times 3 = 1.185$ (only fill out if applicable)				
1 Equip Vol = .02 gallons + (.006 gallons/foot X 45' feet) + .125 gallons = .395 gallons				
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~40'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~40'	PURGING INITIATED AT: 1409	PURGING ENDED AT: 1428	TOTAL VOLUME PURGED (gallons): 8.20

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1422	6.40	6.40	.3	30.09	7.46	27.03	.685	.24	24.7	Clear	None
1424	.6	7.00	.3	30.09	7.41	27.03	.683	.27	20.1	Clear	None
1426	.6	7.60	.3	30.09	7.40	26.90	.680	.26	18.2	Clear	None
1428	.6	8.20	.3	30.08	7.37	26.98	.682	.23	13.3	Clear	None
No stream											

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.	SAMPLER(S) SIGNATURES: 	SAMPLING INITIATED AT: 1430	SAMPLING ENDED AT: 1445
PUMP OR TUBING DEPTH IN WELL (feet): ~40'	SAMPLE PUMP FLOW RATE (mL per minute): < 250 mL	TUBING MATERIAL CODE: PE	
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N	FIELD-FILTERED: <input type="radio"/> Y <input checked="" type="radio"/> N FILTER SIZE: _____ µm	DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N	

SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD	SAMPLING EQUIPMENT CODE
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH		
MW-4A	2	PE	1 Ltr	HN03	None	—	GrossAlpha, RA226RA228	ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia	ESP
"	1	PE	250 mL	HN03	None	—	Al, Fe, Mn, Hg, Ni	ESP
"	1	PE	500 mL	None	None	—	Chloride, Fluoride, Nitrate, TDS	ESP

REMARKS:

1409: Inserted SS ESP and dedicated 3/8" PE tubing to ~40' stoc and began purging @ .3 gpm.

1413: GW is extremely turbid; increased flow to 1 gpm to clean out well.

1418: GW has cleared up nicely, decreased flow to .3 gpm.

1420: WL 30.08' @ .3 gpm, drawdown is stable. GW is clear.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
EQUIPMENT CODES: RFPP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill		SITE LOCATION: Sumterville, FL	
WELL NO: MW-4B	SAMPLE ID: MW-4B	DATE: 5/11/10	

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH 28.0' TO WATER (feet):	PURGE PUMP TYPE OR BAILER: ESP							
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY only fill out if applicable) = (38.49' feet - feet) X gallons/foot = gallons											
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable) 1 Equip Vol = .02 gallons + (.006 gallons/foot X 38' feet) + .125 gallons = 1.373 gallons											
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~33'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~33'	PURGING INITIATED AT: 1307	PURGING ENDED AT: 1335	TOTAL VOLUME PURGED (gallons): 5.44							
TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1316	3.60	3.60	.4	28.17	8.84	25.89	1136	6.97	2.68	Clear	None
1331	1.52	5.12	.08	28.10	8.96	27.13	1140	5.29	1.34	Clear	None
1333	.16	5.28	.08	28.10	8.95	27.23	1140	5.36	1.52	Clear	None
1335	.16	5.44	.08	28.10	8.95	27.36	1142	5.40	1.38	Clear	None
<i>No Shear</i>											
WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88 TUBING INSIDE DIA. CAPACITY (Gal./ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016											

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.		SAMPLER(S) SIGNATURES: 		SAMPLING INITIATED AT: 1336	SAMPLING ENDED AT: 1353				
PUMP OR TUBING DEPTH IN WELL (feet): ~33'		SAMPLE PUMP FLOW RATE (mL per minute): < 250 mL		TUBING MATERIAL CODE: PE					
FIELD DECONTAMINATION: (Y) (N)		FIELD-FILTERED: Y (N) FILTER SIZE: _____ µm		DUPLICATE: Y (N)					
SAMPLE CONTAINER SPECIFICATION			SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD		SAMPLING EQUIPMENT CODE	
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH			
MW-4B	2	PE	1 Ltr	HN03	None	—	Gross Alpha, RA226RA228		ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia		ESP
"	1	PE	250 mL	HN03	None	—	Al, Fe, Mn, Hg, Ni		ESP
"	1	PE	500 mL	None	None	—	Chloride, Fluoride, Nitrate, TDS		ESP

REMARKS:
 1307: Inserted SS ESP and dedicated 3/8" PE tubing to ~33' btoe and began purging @ .4 gpm with ~~ESP~~.
 1312: WL 28.17' @ .4 gpm, GW is clear.
 1315: WL 28.18' @ .4 gpm, drawdown is stable. GW is clear.
 1317: DO is extremely high @ 6.97 mg/L. Reduced flow to .08 gpm.
 1320: DO is slowly dropping, is @ 5.32 mg/L. Continuing to purge.
 1325: WL 28.10' @ .08 gpm, DO is @ 5.16 mg/L and still slowly dropping.
 1330: DO is back up to 5.41 mg/L. Will use optional stabilization criteria for DO.

MATERIAL CODES:	AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)
SAMPLING/PURGING EQUIPMENT CODES:	APP = After Peristaltic Pump; B = Bailer; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump; RFP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill		SITE LOCATION: Sumterville, FL	
WELL NO: MW-6A	SAMPLE ID: MW-6A	DATE: 5/12/10	

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL	STATIC DEPTH 31.55'	PURGE PUMP TYPE							
DIAMETER (inches):	DIAMETER (inches):	DEPTH: feet to feet	TO WATER (feet):	OR BAILER: ESP							
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY											
only fill out if applicable)											
= (50.84' feet - feet) X gallons/foot = gallons											
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME X 3 = 1.335											
(only fill out if applicable)											
1 Equip Vol = .02 gallons + (.006 gallons/foot X 50' feet) + .125 gallons = .375 gallons											
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~45'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~45'	PURGING INITIATED AT: 1355	PURGING ENDED AT: 1426	TOTAL VOLUME PURGED (gallons): 1296							
TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1422	12.64	12.64	.08	31.55	7.79	25.93	.260	5.30	20.2	Clear	None
1424	.16	12.80	.08	31.55	7.78	25.98	.261	5.29	19.2	Clear	None
1426	.16	12.96	.08	31.55	7.79	25.99	.261	5.32	13.3	Clear	None
<i>No Sheen</i>											
WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88											
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016											

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.		SAMPLER(S) SIGNATURES: <i>[Signature]</i>		SAMPLING INITIATED AT: 1427	SAMPLING ENDED AT: 1442			
PUMP OR TUBING DEPTH IN WELL (feet): ~45'		SAMPLE PUMP FLOW RATE (mL per minute): < 250 mL		TUBING MATERIAL CODE: PE				
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N		FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N		FILTER SIZE: _____ µm				
DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N								
SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD	SAMPLING EQUIPMENT CODE
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH		
MW-6A	2	PE	1 Ltr	HN03	None	—	GrossAlpha, RA226RA228	ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia	ESP
"	1	PE	250 mL	HN03	None	—	Al,Fe,Mn,Hg,Na	ESP
"	1	PE	500 mL	None	None	—	Chloride,Fluoride, Nitrate, TDS	ESP

REMARKS:
 1355: Inserted SS ESP and dedicated 3/8" PE tubing to ~45' stoc and began purging @ 1 gpm. This well has a history of high turbidity @ beginning of purge requiring over purging to clean it up.
 1410: GW has cleared up nicely, @ 13 NTUs, reduced flow to .15 gpm.
 1414: WL 31.59' @ .5 gpm, DO is high @ 7.15 mg/L. Reduced flow to .08 gpm.
 1417: DO is dropping, continuing to purge.
 1420: DO appears to be stable @ around 5.29 mg/L. Will use optional stabilization criteria for DO.
 Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
 2) Packed samples on ice immediately upon collection

MATERIAL CODES:	AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)
SAMPLING/PURGING EQUIPMENT CODES:	APP = After Peristaltic Pump; B = Bailer; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump RFPP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.
 2. STANDARDIZATION CRITERIA FOR PURGE VOLUMES AND TUBING CAPACITY (SEE DEP 9000-24)

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-8	SAMPLE ID: MW-8
DATE: 5/11/10	

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL	STATIC DEPTH 22.21	PURGE PUMP TYPE
DIAMETER (inches):	DIAMETER (inches):	DEPTH: feet to feet	TO WATER (feet):	OR BAILER: ESP
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY only fill out if applicable				
= (43.24' feet - 22.21 feet) X 1.209 gallons/foot = 403 gallons				
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable)				
1 Equip Vol = .02 gallons + (.006 gallons/foot X 43') + .125 gallons = .50 gallons				
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~38'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~38'	PURGING INITIATED AT: 1054	PURGING ENDED AT: 1112	TOTAL VOLUME PURGED (gallons): 220

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1108	5.60	5.60	.40	22.24	7.39	24.56	.411	3.42	13.0	Clear	None
1110	.80	6.40	.40	22.24	7.38	24.64	.411	3.34	6.38	Clear	None
1112	.80	7.20	.40	22.24	7.37	24.70	.411	3.27	5.01	Clear	None
									No stream		

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.	SAMPLER(S) SIGNATURES: <i>[Signature]</i>	SAMPLING INITIATED AT: 1113	SAMPLING ENDED AT: 1125
PUMP OR TUBING DEPTH IN WELL (feet): ~38'	SAMPLE PUMP FLOW RATE (mL per minute): VOL'S < 100 mL < 250 mL	TUBING MATERIAL CODE: PE	
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N	FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N Filtration Equipment Type: [None]	FILTER SIZE: _____ µm	DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N

SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD	SAMPLING EQUIPMENT CODE
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH		
MW-8	2	PE	1 Ltr	HN03	None	—	Gross Alpha, RA226RA228	ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia	ESP
"	1	PE	250 mL	HN03	None	—	Metals: Al, Fe, Mn, Hg, Ni, Chloride, Fluoride, Nitrate, TDS	ESP
"	1	PE	500 mL	None	None	—		ESP

REMARKS:
 1054: Set dedicated 3/8" PE tubing and SS ESP @ ~38' Stoc and began purging @ 2.4 gpm with a PP.
 1059: WL 22.25' @ .4 gpm, GW is clear. Turbidity is @ 24 NTUs.
 1105: WL 22.24' @ .4 gpm, drawdown is stable. GW is clear.
 1107: WL 22.24' @ .4 gpm. DO is high @ 3.46 mg/L, will use optional stabilization criteria, afo, DO.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
 2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING EQUIPMENT CODES: APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
 RFPF = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-9A	SAMPLE ID: MW-9A DATE: 5/12/10

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH 29.4' TO WATER (feet):	PURGE PUMP TYPE OR BAILER: ESP
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY only fill out if applicable)				
= (50.17' feet - feet) X gallons/foot = gallons				
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable)				
1 Equip Vol = .02 gallons + (.006 gallons/foot X 50' feet) + .125 gallons = 58 gallons				
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~45'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~45'	PURGING INITIATED AT: 1150	PURGING ENDED AT: 1245	TOTAL VOLUME PURGED (gallons): 40.96

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1236	40.60	40.60	0.04	31.80	6.82	25.85	904	0.2	16.10	Clear	V-Slight sulfur
1238	.08	40.68	0.04	31.79	6.81	25.89	906	0.6	22.0	Clear	Same
1241	.12	40.80	0.04	31.79	6.82	25.76	895	1.2	17.1	Clear	Same
1243	.08	40.88	0.04	31.79	6.81	25.65	896	1.07	9.37	Clear	Same
1245	.08	40.96	0.04	31.79	6.80	25.76	898	0.05	6.33	Clear	Same
No shams											

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.		SAMPLER(S) SIGNATURES: <i>[Signature]</i>		SAMPLING INITIATED AT: 1246	SAMPLING ENDED AT: 1300
PUMP OR TUBING DEPTH IN WELL (feet): ~45'		SAMPLE PUMP FLOW RATE (mL per minute):		TUBING MATERIAL CODE: PE	
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N		FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N FILTER SIZE: _____ µm		DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N	

SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD	SAMPLING EQUIPMENT CODE
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH		
MW-9A	2	PE	1 Ltr	HN03	None	—	Gross Alpha, RA226RA228	ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia	ESP
"	1	PE	250 mL	HN03	None	—	Al, Fe, Mn, Hg, Ni	ESP
"	1	PE	500 mL	None	None	—	Chloride, Fluoride, Nitrate, TDS	ESP

REMARKS:
1150: Inserted SS ESP and dedicated 3/8" PE tubing to ~45' stoc and began purging @ 1 gpm. This well historically has high turbidity at beginning of purge requiring over purging to clean it up. Will purge until clear.
1227: GW has cleared up nicely, reduced flow to .4 gpm.
1230: Turbidity @ 32 NTUs, continuing to purge. WL 31.80' and stable.
1235: WL 31.80', GW is clear.
1238: Turbidity is slowly going up again, continuing to purge.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
EQUIPMENT CODES: RFPP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-10	SAMPLE ID: MW-10 DATE: 5/11/10

PURGING DATA

WELL 2" PVC	TUBING 3/8"	WELL SCREEN INTERVAL	STATIC DEPTH 22.38	PURGE PUMP TYPE OR BAILER: ESP
DIAMETER (inches):	DIAMETER (inches):	DEPTH: feet to feet	TO WATER (feet):	

WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY
only fill out if applicable)

= (**45.35'** feet - **22.38'** feet) X **0.016** gallons/foot = **0.38** gallons

EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME
(only fill out if applicable)

1 Equip Vol = **.02** gallons + (**.006** gallons/foot X **45'** feet) + **.125** gallons = **.425** gallons

INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~40'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~40'	PURGING INITIATED AT: 1157	PURGING ENDED AT: 1230	TOTAL VOLUME PURGED (gallons): 24.75
--	--	-----------------------------------	-------------------------------	---

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1226	21.75	21.75	.75	24.10	7.30	25.25	1.572	1.10	11.9	Clear	None
1228	1.50	23.25	.75	24.10	7.23	25.22	1.571	1.09	10.8	Clear	None
1230	1.50	24.75	.75	24.10	7.21	25.20	1.570	1.11	9.47	Clear	None
									No screen		

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.	SAMPLER(S) SIGNATURES: 	SAMPLING INITIATED AT: 1231	SAMPLING ENDED AT: 1245
PUMP OR TUBING DEPTH IN WELL (feet): ~40'	SAMPLE PUMP FLOW RATE (mL per minute): VOL'S < 100 mL < 250 mL	TUBING MATERIAL CODE: PE	
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N	FIELD-FILTERED: <input type="radio"/> Y <input checked="" type="radio"/> N FILTER SIZE: _____ µm	DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N	

SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION			INTENDED ANALYSIS AND/OR METHOD	SAMPLING EQUIPMENT CODE
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH		
MW-10	2	PE	1 Ltr	HN03	None	---	Gross Alpha, RA226RA228	ESP
"	1	PE	250 mL	H2S04	None	---	Total Ammonia	ESP
"	1	PE	250 mL	HN03	None	---	Metal: Al, Fe, Mn, Hg, Ni	ESP
"	1	PE	500 mL	None	None	---	Chloride, Fluoride, Nitrate, TDS	ESP

REMARKS:
 1157: Inserted SS ESP and dedicated 3/8" PE tubing to ~40' static and began purging @ .75 gpm.
 1200: WL 24.00' @ .75 gpm, GW is extremely turbid. This well historically requires over purging to clean up turbidity.
 1210: GW is still turbid, but cleaning up. Continuing to purge.
 1225: WL 24.10' @ .75 gpm, GW has cleared up to 15 NTUs. Drawdown is stable.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
 2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
 EQUIPMENT CODES: RFP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify)

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.
 2. STABILIZATION CRITERIA FOR RANGE VARIATION OF LAST THREE CONSECUTIVE READINGS (SEE FS 2212 SECTION 3)H: + 0.2 units: Temperature: + 0.2

GROUNDWATER SAMPLING LOG

SITE NAME: Sumter County Landfill	SITE LOCATION: Sumterville, FL
WELL NO: MW-11	SAMPLE ID: MW-11 DATE: 5/12/10

PURGING DATA

WELL 2" PVC DIAMETER (inches):	TUBING 3/8" DIAMETER (inches):	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH 24.62 TO WATER (feet):	PURGE PUMP TYPE OR BAILER: ESP							
WELL VOLUME PURGE: 1 WELL VOLUME = (TOTAL WELL DEPTH - STATIC DEPTH TO WATER) X WELL CAPACITY only fill out if applicable)											
= (40.15' feet - 24.62' feet) X 40% gallons/foot = 6.80 gallons											
EQUIPMENT VOLUME PURGE: 1 EQUIPMENT VOL. = PUMP VOLUME + (TUBING CAPACITY X TUBING LENGTH) + FLOW CELL VOLUME (only fill out if applicable)											
1 Equip Vol = .02 gallons + (.006 gallons/foot X 40' feet) + .125 gallons = .405 gallons											
INITIAL PUMP OR TUBING DEPTH IN WELL (feet): ~35'	FINAL PUMP OR TUBING DEPTH IN WELL (feet): ~35'	PURGING INITIATED AT: 0957	PURGING ENDED AT: 1016	TOTAL VOLUME PURGED (gallons): 6.80							
TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (mS/cm)	DISSOLVED OXYGEN (mg/L)	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
1010	5.20	5.20	.4	24.72	6.83	25.49	1416	1.39	12.9	Clear	None
1012	.80	6.00	.4	24.71	6.77	25.55	1422	1.47	16.5	Clear	None
1014	.80	6.80	.4	24.72	6.73	25.59	1437	1.31	19.2	Clear	None
1016									17.8	Clear	None
<i>No Screen</i>											
WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88											
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016											

SAMPLING DATA

SAMPLED BY (PRINT) / AFFILIATION: H. L. Claytor, Colinas Group, Inc.		SAMPLER(S) SIGNATURES: <i>[Signature]</i>		SAMPLING INITIATED AT: 1017	SAMPLING ENDED AT: 1030				
PUMP OR TUBING DEPTH IN WELL (feet): ~35'		SAMPLE PUMP FLOW RATE (mL per minute): < 250 mL		TUBING MATERIAL CODE: PE					
FIELD DECONTAMINATION: <input checked="" type="radio"/> Y <input type="radio"/> N		FIELD-FILTERED: <input checked="" type="radio"/> Y <input type="radio"/> N Filtration Equipment Type: <input checked="" type="radio"/> <input type="radio"/>		FILTER SIZE: _____ µm DUPLICATE: <input type="radio"/> Y <input checked="" type="radio"/> N					
SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION		INTENDED ANALYSIS AND/OR METHOD		SAMPLING EQUIPMENT CODE	
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH			
MW-11	2	PE	1 Ltr	HN03	None	—	Gross Alpha, RA226, RA228		ESP
"	1	PE	250 mL	H2S04	None	—	Total Ammonia		ESP
"	1	PE	250 mL	HN03	None	—	M, Fe, Mn, Hg, Ni		ESP
"	1	PE	500 mL	None	None	—	Chloride, Fluoride, Nitrate, TDS		ESP

REMARKS:
0957: Inserted SS ESP and dedicated 3/8" PE tubing to ~35' bloc and began purging @ .4 gpm.
1001: WL 24.78' @ .4 gpm, GW is slightly turbid. Will over purge to clean up.
1008: WL 24.72' @ .4 gpm, GW is clear. Drawdown is stable.

Notes: 1) Used a graduated 5 gallon bucket and timed to measure purge volumes
2) Packed samples on ice immediately upon collection

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; PE = Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING/PURGING APP = After Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump
EQUIPMENT CODES: RFPF = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); VT = Vacuum Trap; O = Other (Specify) y

Notes: 1. The above do not constitute all the information required by Chapter 62-160, F.A.C.
2. STABILIZATION CRITERIA FOR RANGE VARIATION OF LAST THREE CONSECUTIVE READINGS (SEE FS 2212, SECTION 3)H: ± 0.2 units; Temperature: ± 0.2



www.encolabs.com



ENVIRONMENTAL CONSERVATION LABORATORIES CHAIN-OF-CUSTODY RECORD

10775 Central Port Dr.
Orlando, FL 32834
(407) 856-5314 Fax (407) 859-8945

4810 Executive Park Court, Suite 211
Jacksonville, FL 32216-9699
(904) 296-3007 Fax (904) 296-6210

1015 Passport Way
Cary, NC 27513
(919) 877-1899 Fax (919) 877-9445

Page 1 of 1

Client Name: **The Colinas Group (CO016)**
 Address: **509 N. Virginia Ave.**
 City/ST/Zip: **Winter Park, FL 32789**
 Project Number: **53008**
 Project Name/Desc: **SUMTER COUNTY VOL. RED. & LANDFILL**
 PO # / Billing Info:
 Reporting Contact: **Rick Poits**
 Billing Contact: **Rick Poits**
 Facility # (if required):

Requested Analytes:
 Gross Alpha Radium 226, Radium 228
 Ammonia 350.1
 Preservation (See Codes) (Continue as necessary):
 Ag, Al, Ba, Be, Bi, Cd, Co, Cr, Cu, Fe, Hg, Ni, Pb, Sb, Se, Si, Tl, Zn

Requested Turnaround Times:
 Note: Rush requests subject to acceptance by the facility.
 Standard
 Expedited
 Due: / /
 Lab WorkOrder: **A002462**

Item #	Sample ID (Field Identification)	Collection Date	Collection Time	Container / Grab	Matrix (See codes)	Total # of Containers	H	I	N	S	I	N	Sample Comments
	MW-2	5/12/10	1135	G	GW	0.5	X	X	X	X	X	X	
	MW-4	5/12/10	0935	G	GW	0.5	X	X	X	X	X	X	
	MW-4B	5/11/10	1353	G	GW	0.5	X	X	X	X	X	X	
	MW-4A	5/11/10	1445	G	GW	0.5	X	X	X	X	X	X	
	MW-8A	5/12/10	1442	G	GW	0.5	X	X	X	X	X	X	
	MW-8	5/11/10	1125	G	GW	0.5	X	X	X	X	X	X	
	MW-8A	5/12/10	1300	G	GW	0.5	X	X	X	X	X	X	
	MW-10	5/11/10	1245	G	GW	0.5	X	X	X	X	X	X	
	MW-11	5/12/10	1030	G	GW	0.5	X	X	X	X	X	X	
	EQUIPMENT BLANK	5/11/10	1030	G	0-GW	0.5	X	X	X	X	X	X	
	TRIP BLANK				0	2	X	X	X	X	X	X	O = DI WATER

Sample Kit Prepared By: *SP* Date/Time: *5/11/10 1230*
 Requisitioned By: *hml*
 Date/Time: *5/11/10 1230*
 Comments: *No Appendix 1 parameters this event.*
 Date/Time: *5/12/10 1230*
 Date/Time: *5/12/10 1230*
 Date/Time: *5/12/10 1230*
 Date/Time: *5/12/10 1230*
 Condition Upon Receipt: Acceptable Unacceptable

Matrix: GW - Groundwater, SW - Surface Water, WW - Wastewater, A - Air, O - Other (detail in comments)
 Preservation: I - Ice, H - HCl, H-NO3, S - H2SO4, NO - NaOH, O - Other (detail in comments)
 Note: All samples submitted to ENCO Labs are in accordance with the terms and conditions listed on the reverse of this form, unless prior written agreements exist.

Field Instrument Calibration Records

INSTRUMENT (MAKE/MODEL#) YSI 556/Lamotte 2020e **INSTRUMENT #** _____

PARAMETERS:

- TEMPERATURE
 CONDUCTIVITY
 SALINITY
 pH
 ORP
 TURBIDITY
 RESIDUAL CL
 DO
 OTHER _____

STANDARDS: [Bracket calibrated meters pH 4 – 7 and Turbidity 1 – 10 NTU's]

- Standard A** Oakton pH Standard 4.01 Units Exp: 7/2011
Standard B Oakton pH Standard 7.00 Units Exp: 7/2011
Standard C Oakton Conductivity Standard .447 mS/cm Exp: 8/2010
Standard D Lamotte 1 NTU Standard Exp: 3/2011
Standard E Lamotte 10 NTU Standard Exp: 1/2011

DATE (yy/mm/dd)	TIME (hr:min)	STD (A, B, C)	STD VALUE	INSTRUMENT RESPONSE	% DEV	CALIBRATED (YES, NO)	TYPE (INIT, CONT)	SAMPLER INITIALS	
5/11/10	0850	A	4.01	4.01		Yes	IC	[Signature]	pH
		B	7.00	7.00					pH
		C	.447	.447					Cond
		--	--	8.67					DO
		--	--	22.43					Temp
		D	1	1.00					Turb
		E	10	10.02				Turb	
5/11/10	0910	A	4.01	4.01		Yes	ICU	[Signature]	pH
		B	7.00	7.01					pH
		C	.447	.443					Cond
		--	--	8.33					DO
		--	--	24.56					Temp
		D	1	1.00					Turb
		E	10	10.04				Turb	
		A	4.01						pH
		B	7.00						pH
		C	.447						Cond
		--	--						DO
		--	--						Temp
		D	1						Turb
		E	10						Turb

Field Instrument Calibration Records

INSTRUMENT (MAKE/MODEL#) YSI 556/Lamotte 2020e **INSTRUMENT #** _____

PARAMETERS:

- TEMPERATURE
 CONDUCTIVITY
 SALINITY
 pH
 ORP
 TURBIDITY
 RESIDUAL CL
 DO
 OTHER _____

STANDARDS: [Bracket calibrated meters pH 4 – 7 and Turbidity 1 – 10 NTU's]

Standard A Oakton pH Standard 4.01 Units Exp: 7/2011

Standard B Oakton pH Standard 7.00 Units Exp: 7/2011

Standard C Oakton Conductivity Standard .447 mS/cm Exp: 8/2010

Standard D Lamotte 1 NTU Standard Exp: 3/2011

Standard E Lamotte 10 NTU Standard Exp: 1/2011

DATE (yy/mm/dd)	TIME (hr:min)	STD (A, B, C)	STD VALUE	INSTRUMENT RESPONSE	% DEV	CALIBRATED (YES, NO)	TYPE (INIT, CONT)	SAMPLER INITIALS	
5/12/10	0830	A	4.01	4.01		Yes	IC	JPE	pH
		B	7.00	7.00					pH
		C	.447	.447					Cond
		--	--	8.61					DO
		--	--	22.81					Temp
		D	1	1.00					Turb
		E	10	10.00					Turb
5/12/10	0845	A	4.01	4.01		Yes	ICV	JPE	pH
		B	7.00	6.99					pH
		C	.447	.447					Cond
		--	--	8.61					DO
		--	--	22.78					Temp
		D	1	1.00					Turb
		E	10	9.98					Turb
		A	4.01						pH
		B	7.00						pH
		C	.447						Cond
		--	--						DO
		--	--						Temp
		D	1						Turb
		E	10						Turb



www.encolabs.com

Description: EQUIPMENT BLANK

Lab Sample ID: A002462-10

Received: 05/12/10 16:20

Matrix: Ground Water

Sampled: 05/11/10 10:30

Work Order: A002462

Project: SUMTER COUNTY VOL. RED. &
LANDFILL

Sampled By: Dale Claytor

Metals by EPA 6000/7000 Series Methods

^ - ENCO Orlando certified analyte [NELAC E83182]

Analyte [CAS Number]	Results	Flag	Units	DF	MDL	PQL	Batch	Method	Analyzed	By	Notes
Mercury [7439-97-6] ^	0.0240	U	ug/L	1	0.0240	0.200	0E12042	EPA 7470A	05/19/10 08:31	JMA	



www.encolabs.com

Description: EQUIPMENT BLANK

Lab Sample ID: A002462-10

Received: 05/12/10 16:20

Matrix: Ground Water

Sampled: 05/11/10 10:30

Work Order: A002462

Project: SUMTER COUNTY VOL. RED. & LANDFILL

Sampled By: Dale Claytor

Metals (total recoverable) by EPA 6000/7000 Series Methods

^ - ENCO Orlando certified analyte [NELAC E83182]

Analyte [CAS Number]	Results	Flag	Units	DF	MDL	PQL	Batch	Method	Analyzed	By	Notes
Aluminum [7429-90-5] ^	68.0	U	ug/L	1	68.0	100	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Antimony [7440-36-0] ^	0.700	U	ug/L	1	0.700	20.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Arsenic [7440-38-2] ^	4.00	U	ug/L	1	4.00	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Barium [7440-39-3] ^	11.0	U	ug/L	1	11.0	100	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Beryllium [7440-41-7] ^	0.740	U	ug/L	1	0.740	1.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Cadmium [7440-43-9] ^	1.10	U	ug/L	1	1.10	3.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Chromium [7440-47-3] ^	4.50	U	ug/L	1	4.50	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Cobalt [7440-48-4] ^	1.20	U	ug/L	1	1.20	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Copper [7440-50-8] ^	2.20	U	ug/L	1	2.20	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Iron [7439-89-6] ^	38.0	U	ug/L	1	38.0	50.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	QV-01
Lead [7439-92-1] ^	1.20	U	ug/L	1	1.20	5.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Manganese [7439-96-5] ^	2.00	U	ug/L	1	2.00	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Nickel [7440-02-0] ^	2.30	U	ug/L	1	2.30	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Selenium [7782-49-2] ^	5.20	U	ug/L	1	5.20	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	QV-01
Silver [7440-22-4] ^	0.200	U	ug/L	1	0.200	1.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Sodium [7440-23-5] ^	0.320	U	mg/L	1	0.320	1.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Thallium [7440-28-0] ^	0.260	U	ug/L	1	0.260	1.00	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Vanadium [7440-62-2] ^	0.960	U	ug/L	1	0.960	10.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	
Zinc [7440-66-6] ^	16.0	U	ug/L	1	16.0	50.0	0E13010	EPA 6020A	05/18/10 15:23	JAY	



www.encolabs.com

Description: EQUIPMENT BLANK

Matrix: Ground Water

Project: SUMTER COUNTY VOL. RED. & LANDFILL

Lab Sample ID: A002462-10

Sampled: 05/11/10 10:30

Sampled By: Dale Claytor

Received: 05/12/10 16:20

Work Order: A002462

Classical Chemistry Parameters

^ - ENCO Orlando certified analyte [NELAC E83182]

Analyte [CAS Number]	Results	Flag	Units	DF	MDL	PQL	Batch	Method	Analyzed	By	Notes
Ammonia as N [7664-41-7] ^	0.010	U	mg/L	1	0.010	0.020	0E14019	EPA 350.1	05/14/10 14:48	KG	
Chloride [16887-00-6] ^	1.6	I	mg/L	1	0.24	5.0	0E12035	EPA 300.0	05/13/10 00:50	RSA	
Fluoride [16984-48-8] ^	0.03	U	mg/L	1	0.03	0.20	0E12035	EPA 300.0	05/13/10 00:50	RSA	
Nitrate as N [14797-55-8] ^	0.12	I	mg/L	1	0.10	1.0	0E12035	EPA 300.0	05/13/10 00:50	RSA	
Total Dissolved Solids [ECL-0156] ^	28		mg/L	1	10	10	0E12043	SM18 2540C	05/13/10 23:35	AH	

This report relates only to the sample as received by the laboratory, and may only be reproduced in full.



www.encolabs.com

SAMPLE SUMMARY/LABORATORY CHRONICLE

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/14/10 11:35	05/12/10 16:54	5/12/2010 22:26
EPA 300.0	06/09/10	05/12/10 16:54	5/12/2010 22:26
EPA 350.1	06/09/10	05/14/10 12:15	5/14/2010 14:35
EPA 6020A	11/08/10	05/13/10 17:25	5/17/2010 14:35
EPA 7470A	06/09/10	05/18/10 13:08	5/19/2010 07:13
Field	05/12/10 11:49	05/12/10 11:35	5/14/2010 13:34
Field	05/13/10 11:35 05/13/10 11:35	05/12/10 11:35	5/14/2010 13:34
Field	05/14/10 11:35	05/12/10 11:35	5/14/2010 13:34
SM18 2540C	05/19/10	05/12/10 19:05	5/13/2010 23:35

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/14/10 09:35	05/12/10 16:54	5/12/2010 22:44
EPA 300.0	06/09/10	05/12/10 16:54	5/12/2010 22:44
EPA 350.1	06/09/10	05/14/10 12:15	5/14/2010 14:36
EPA 6020A	11/08/10	05/13/10 17:25	5/18/2010 14:27
EPA 7470A	06/09/10	05/18/10 13:08	5/19/2010 08:00
Field	05/12/10 09:49	05/12/10 09:35	5/14/2010 13:34
Field	05/13/10 09:35 05/13/10 09:35	05/12/10 09:35	5/14/2010 13:34
Field	05/14/10 09:35	05/12/10 09:35	5/14/2010 13:34
SM18 2540C	05/19/10	05/12/10 19:05	5/13/2010 23:35

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/13/10 13:53	05/12/10 16:54	5/12/2010 22:08
EPA 300.0	06/08/10	05/12/10 16:54	5/12/2010 22:08
EPA 350.1	06/08/10	05/14/10 12:15	5/14/2010 14:40
EPA 6020A	11/07/10	05/13/10 17:25	5/18/2010 14:34
EPA 7470A	06/08/10	05/18/10 13:08	5/19/2010 08:03
Field	05/11/10 14:07	05/11/10 13:53	5/14/2010 13:34
Field	05/12/10 13:53 05/12/10 13:53	05/11/10 13:53	5/14/2010 13:34
Field	05/13/10 13:53	05/11/10 13:53	5/14/2010 13:34
SM18 2540C	05/18/10	05/12/10 19:05	5/13/2010 23:35



www.encolabs.com

Client ID:	HW-4A	Lab ID:	HW24422-01	Prep Date:	05/12/10	Analysis Date:	05/12/10
Parameter	Hold Date/Time(s)		Prep Date/Time(s)		Analysis Date/Time(s)		
EPA 300.0	05/13/10	14:45	05/12/10	16:54	5/12/2010 23:02		
EPA 300.0	06/08/10		05/12/10	16:54	5/12/2010 23:02		
EPA 350.1	06/08/10		05/14/10	12:15	5/14/2010 14:41		
EPA 6020A	11/07/10		05/13/10	17:25	5/18/2010 15:30		
EPA 7470A	06/08/10		05/18/10	13:08	5/19/2010 08:06		
Field	05/11/10	14:59	05/11/10	14:45	5/14/2010 13:34		
Field	05/12/10	14:45	05/12/10	14:45	5/14/2010 13:34		
Field	05/13/10	14:45	05/11/10	14:45	5/14/2010 13:34		
SM18 2540C	05/18/10		05/12/10	19:05	5/13/2010 23:35		

Client ID:	HW-4A	Lab ID:	HW24422-01	Prep Date:	05/12/10	Analysis Date:	05/12/10
Parameter	Hold Date/Time(s)		Prep Date/Time(s)		Analysis Date/Time(s)		
EPA 300.0	05/14/10	14:42	05/12/10	16:54	5/12/2010 23:20		
EPA 300.0	06/09/10		05/12/10	16:54	5/12/2010 23:20		
EPA 350.1	06/09/10		05/14/10	12:15	5/14/2010 14:42		
EPA 6020A	11/08/10		05/13/10	17:25	5/18/2010 15:37		
EPA 7470A	06/09/10		05/18/10	13:08	5/19/2010 08:09		
Field	05/12/10	14:56	05/12/10	14:42	5/14/2010 13:34		
Field	05/13/10	14:42	05/13/10	14:42	5/14/2010 13:34		
Field	05/14/10	14:42	05/12/10	14:42	5/14/2010 13:34		
SM18 2540C	05/19/10		05/12/10	19:05	5/13/2010 23:35		

Client ID:	HW-4A	Lab ID:	HW24422-01	Prep Date:	05/13/10	Analysis Date:	05/19/10
Parameter	Hold Date/Time(s)		Prep Date/Time(s)		Analysis Date/Time(s)		
EPA 6020A	11/08/10		05/13/10	17:25	5/19/2010 15:01		

Parameter	Hold Date/Time(s)		Prep Date/Time(s)		Analysis Date/Time(s)		
EPA 300.0	05/13/10	11:25	05/12/10	16:54	5/12/2010 23:38		
EPA 300.0	06/08/10		05/12/10	16:54	5/12/2010 23:38		
EPA 350.1	06/08/10		05/14/10	12:15	5/14/2010 14:43		
EPA 6020A	11/07/10		05/13/10	17:25	5/18/2010 15:47		
EPA 7470A	06/08/10		05/18/10	13:08	5/19/2010 08:18		
Field	05/11/10	11:39	05/11/10	11:25	5/14/2010 13:34		
Field	05/12/10	11:25	05/12/10	11:25	5/14/2010 13:34		
Field	05/13/10	11:25	05/11/10	11:25	5/14/2010 13:34		
SM18 2540C	05/18/10		05/12/10	19:05	5/13/2010 23:35		

Parameter	Hold Date/Time(s)		Prep Date/Time(s)		Analysis Date/Time(s)		
EPA 6020A	11/07/10		05/13/10	17:25	5/19/2010 15:51		



www.encolabs.com

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/14/10 13:00	05/12/10 16:54	5/13/2010 01:08
EPA 300.0	06/09/10	05/12/10 16:54	5/13/2010 01:08
EPA 350.1	06/09/10	05/14/10 12:15	5/14/2010 14:45
EPA 6020A	11/08/10	05/13/10 17:25	5/18/2010 15:54
EPA 7470A	06/09/10	05/18/10 13:08	5/19/2010 08:21
Field	05/12/10 13:14	05/12/10 13:00	5/14/2010 13:34
Field	05/13/10 13:00 05/13/10 13:00	05/12/10 13:00	5/14/2010 13:34
Field	05/14/10 13:00	05/12/10 13:00	5/14/2010 13:34
SM18 2540C	05/19/10	05/12/10 19:05	5/13/2010 23:35

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 6020A	11/08/10	05/13/10 17:25	5/19/2010 15:58

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/13/10 12:45	05/12/10 16:54	5/13/2010 01:26
EPA 300.0	06/08/10	05/12/10 16:54	5/13/2010 01:26
EPA 350.1	06/08/10	05/14/10 12:15	5/14/2010 14:46
EPA 6020A	11/07/10	05/13/10 17:25	5/18/2010 16:01
EPA 7470A	06/08/10	05/18/10 13:08	5/19/2010 08:24
Field	05/11/10 12:59	05/11/10 12:45	5/14/2010 13:34
Field	05/12/10 12:45 05/12/10 12:45	05/11/10 12:45	5/14/2010 13:34
Field	05/13/10 12:45	05/11/10 12:45	5/14/2010 13:34
SM18 2540C	05/18/10	05/12/10 19:05	5/13/2010 23:35

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 6020A	11/07/10	05/13/10 17:25	5/19/2010 16:05


Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/14/10 10:30	05/12/10 16:54	5/13/2010 01:44
EPA 300.0	06/09/10	05/12/10 16:54	5/13/2010 01:44
EPA 350.1	06/09/10	05/14/10 12:15	5/14/2010 14:47
EPA 6020A	11/08/10	05/13/10 17:25	5/18/2010 16:11
EPA 7470A	06/09/10	05/18/10 13:08	5/19/2010 08:27
Field	05/12/10 10:44	05/12/10 10:30	5/14/2010 13:34
Field	05/13/10 10:30 05/13/10 10:30	05/12/10 10:30	5/14/2010 13:34
Field	05/14/10 10:30	05/12/10 10:30	5/14/2010 13:34
SM18 2540C	05/19/10	05/12/10 19:05	5/13/2010 23:35



www.encolabs.com

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 6020A	11/08/10	05/13/10 17:25	5/19/2010 16:15

Parameter	Hold Date/Time(s)	Prep Date/Time(s)	Analysis Date/Time(s)
EPA 300.0	05/13/10 10:30	05/12/10 16:54	5/13/2010 00:50
EPA 300.0	06/08/10	05/12/10 16:54	5/13/2010 00:50
EPA 350.1	06/08/10	05/14/10 12:15	5/14/2010 14:48
EPA 6020A	11/07/10	05/13/10 17:25	5/18/2010 15:23
EPA 7470A	06/08/10	05/18/10 13:08	5/19/2010 08:31
SM18 2540C	05/18/10	05/12/10 19:05	5/13/2010 23:35



Florida Radiochemistry Services, Inc.

Sample Login

Client:	Enco-Orlando	Date / Time Received	Work order #
Client Contact:	Marcia Colon	05/13/10 08:28	1005115
Client P.O.			
Project I.D.	A002462		

Lab Sample I.D.	Client Sample I.D.	Sample Date/Time	Analysis Requested
1005115-01	MW-2	05/12/10 11:35	Ga, Ra226, Ra228
1005115-02	MW-4	05/12/10 09:35	Ga, Ra226, Ra228
1005115-03	MW-4B	5/11/2010 13:53	Ga, Ra226, Ra228
1005115-04	MW-4A	05/11/10 14:45	Ga, Ra226, Ra228
1005115-05	MW-6A	05/12/10 14:42	Ga, Ra226, Ra228
1005115-06	MW-8	05/11/10 11:25	Ga, Ra226, Ra228
1005115-07	MW-9A	05/12/10 13:00	Ga, Ra226, Ra228
1005115-08	MW-10	05/11/10 12:45	Ga, Ra226, Ra228
1005115-09	MW-11	05/12/10 10:30	Ga, Ra226, Ra228
1005115-10	EQUIPMENT BLANK	05/11/10 10:30	Ga, Ra226, Ra228



QA Page

Analyte	Sample #	Date Analyzed	Sample Result	Amount Spiked	Spike Result	Spike /Dup Result	Spike % Rec.	Spike Dup % Rpd
Gross Alpha	1005115-01	05/24/10	<1.0	10.2	10.8	10.0	106	7.7
Radium 226	1005115-08	05/28/10	1.6	25.2	25.9	24.4	96	6.0
Radium 228	1005115-08	05/28/10	<0.8	4.9	4.6	5.3	94	14.1

Quality Control Limits

% RPD % Rec.

Gross Alpha	25.0	60-125
Radium 226	23.4	78-125
Radium 228	23.9	67-125